

pilNLINEx® vacuum generator MINI Si, 6-6 mm, 0122025



- Patented COAX® cartridge technology.
- High vacuum flow capacity in relation to energy consumption.
- Low weight inline design with push-in fittings for vacuum and compressed air.
- Quick and easy installation directly on the hose.
- Si cartridge for extra vacuum flow.
- Pi cartridge for high performance at low feed pressures.
- Xi cartridge when high flow and deep vacuum is needed.

General

Item number, alternative	E12842166
Material	CuZn, PA, SS, Al, Nitrile (NBR)
Noise level	68 – 84 dBA
Temperature	-10 – 80 °C
Weight	23 g

Performance

Feed pressure, max.	0.7 MPa
---------------------	---------


Vacuum flow

Feed pressure	Air consumption	Vacuum flow (NL/s) at different vacuum levels (-kPa)								Max vacuum
		0	10	20	30	40	50	60	70	
MPa	Nl/s	0.69	0.55	0.42	0.28	0.23	0.16	0.12	0.08	75
0.6	0.44									

Evacuation time

Feed pressure	Air consumption	Evacuation time (s/l) to reach different vacuum levels (-kPa)							Max vacuum
		10	20	30	40	50	60	70	
MPa	Nl/s	10	20	30	40	50	60	70	-kPa
0.6	0.44	0.16	0.37	0.66	1.1	1.4	2.1	3.1	75

Dimensional drawings



Values specified in the data sheet are tested at:

Room temperature	(20°C [68°F] ± 3°C [5.5°F])
Standard atmosphere	(101.3 [29.9 inHg] ± 1.0 kPa [0.3 inHg])
Relative humidity	0-100%
Compressed air quality	DIN ISO 8573-1 class 4

Accessories

	Item no.
Snap-in piINLINE® 4x MINI mounting bracket	0123094
Silencer piINLINE® MINI	0125466
Snap-in piINLINE® 1x MINI mounting bracket for silencer	0126009