

pilNLINEx® vacuum generator MINI Pi, 6-6 mm, 0122894



- Patented COAX® cartridge technology.
- High vacuum flow capacity in relation to energy consumption.
- Low weight inline design with push-in fittings for vacuum and compressed air.
- Quick and easy installation directly on the hose.
- Si cartridge for extra vacuum flow.
- Pi cartridge for high performance at low feed pressures.
- Xi cartridge when high flow and deep vacuum is needed.

General

Material	CuZn, PA, SS, Al, Nitrile (NBR)
Noise level	69 – 85 dBA
Temperature	-10 – 80 °C
Weight	23 g

Performance

Feed pressure, max.	0.7 MPa
---------------------	---------


Vacuum flow

Feed pressure	Air consumption	Vacuum flow (NL/s) at different vacuum levels (-kPa)									Max vacuum
MPa	Nl/s	0	10	20	30	40	50	60	70	80	-kPa
0.32	0.44	0.57	0.44	0.31	0.23	0.19	0.14	0.1	0.06	0.03	90

Evacuation time

Feed pressure	Air consumption	Evacuation time (s/l) to reach different vacuum levels (-kPa)									Max vacuum
MPa	Nl/s	10	20	30	40	50	60	70	80	-kPa	
0.32	0.44	0.2	0.46	0.83	1.1	1.8	2.7	4	6.4	90	

Dimensional drawings



Values specified in the data sheet are tested at:

Room temperature	(20°C [68°F] ± 3°C [5.5°F])
Standard atmosphere	(101.3 [29.9 inHg] ± 1.0 kPa [0.3 inHg])
Relative humidity	0-100%
Compressed air quality	DIN ISO 8573-1 class 4

Accessories

	Item no.
Snap-in piINLINE® 4x MINI mounting bracket	0123094
Silencer piINLINE® MINI	0125466
Snap-in piINLINE® 1x MINI mounting bracket for silencer	0126009