Union nut for low-pressure hose nipples

Zinc plated steel

Series: S-6GME



Overview

Material	Zinc plated steel
DN (mm)	3 to 25
Diameter bore (mm)	6.8 to 31.3
Spanner width (mm)	12 to 46
Thread	16 options, see the model table
SKUs in this series	18

Description

Union nuts for low-pressure hose nipples with a collar. The bore slides over the hose nipple, and the nut holds the nipple collar against the male thread. Metric and G threads. Zinc plated steel. For low-pressure hose only.

Key features

- Zinc plated steel

Models

Select the SKU for your application.

SKU	DN (mm)	Thread	Diameter bore (mm)	Spanner width (mm)
F2XTP	3	G 1/8	6.8	14
F2XTE	3	M10×1	6.8	12
F2XTR	4	G 1/4	7.8	17
F2XTF	4	M12×1.5	7.8	14
F2XTQ	6	G 1/4	9.9	17
F2XTG	6	M14×1.5	9.9	17
F2XTS	8	G 3/8	11.8	19
F2XTH	8	M16×1.5	11.8	19
F2XTU	10	G 1/2	13.8	24
F2XTJ	10	M18×1.5	13.8	22
F2XTT	13	G 1/2	17.3	24
F2XTK	13	M22×1.5	17.3	27
F2XTV	16	G 3/4	20.3	32
F2XTM	16	M26×1.5	20.3	32
F2XTW	20	G 1	24.3	41
F2XTC	20	M30×1.5	24.3	36
F2XTN	20	M30×2	24.3	36
F2XTD	25	M38×1.5	31.3	46

Points to note

- For low-pressure hose only, for hydraulic hose choose crimp fittings
- Hose nipple not included

Tameson B.V.
Torenallee 20, 5617 BC Eindhoven, The Netherlands
CoC: 72902531
VAT: NL859280263B01

Contact Information
support@tameson.com
tameson.com

Document Information
Version: 1.0

Specifications subject to change without notice. Verify current specifications before ordering.