Hose sleeve for low-pressure hose

Zinc plated steel

Series: S-6Y5S



Overview

Materials	Zinc plated steel
DN (mm)	2 to 25
Sleeve diameter (inner) (mm)	9 to 40
Floor hole (mm)	5.5 to 29.6
Hose diameter (outer) (mm)	18 options, see the model table
SKUs in this series	20

Description

Hose sleeves (ferrules) for low-pressure hose. Push the sleeve over the hose end, put the hose nipple in, then crimp the sleeve. This holds the hose on the nipple. Choose the sleeve by the outer diameter of the hose, and the hose nipple by the inner diameter and DN. Zinc plated steel. For corrosive environments, choose the stainless steel 1.4301 version.

Key features

- Zinc plated steel

Models

Select the SKU for your application.

SKU	DN (mm)	Sleeve diameter (inner) (mm)	Hose diameter (outer) (mm)	Floor hole (mm)
F2XHY	2	9	7.5 to 8	5.5
F2XJ2	3	10	8.5 to 9	6.2
F2XJ4	4	11	9.5 to 10	7.2
F2XJJ	4	12.5	11 to 11.5	7.3
F2XJW	4	12.5	11 to 11.5	8.8
F2XJ6	6	13.5	12 to 12.5	9.2
F2XJM	6	14.5	13 to 13.5	9.3
F2XJX	6	15	13.5 to 14	9.3
F2XJ8	8	15	13.5 to 14	11.2
F2XJP	8	16	14.5 to 15	11.2
F2XJZ	8	17	15.5 to 16	11.2
F2XJA	10	18	16.5 to 17	14.2
F2XJR	10	19.5	18 to 18.5	14.2
F2XJB	13	22	20.5 to 21	17.2
F2XJT	13	24.5	23 to 23.5	17.2
F2XJC	16	26.5	25 to 25.5	19.7
F2XJU	16	28	26.5 to 27	19.7
F2XJE	20	32	30.5 to 31	23.7
F2XJV	20	33	31.5 to 32	23.9
F2XJG	25	40	35 to 39	29.6

Points to note

- For low-pressure hose only, for hydraulic hose choose crimp fittings
- Permanent crimp, needs a crimping tool
- Zinc plated steel, for corrosive media choose stainless steel 1.4301

Tameson B.V.
Torenallee 20, 5617 BC Eindhoven, The Netherlands
CoC: 72902531
VAT: NL859280263B01

Contact Information
support@tameson.com
tameson.com

Document Information
Version: 1.0

Specifications subject to change without notice. Verify current specifications before ordering.