PVC diaphragm valve, pneumatic, normally closed

PVC body, EPDM diaphragm, solvent cement sockets

Series: S-7JZE



Overview

Diaphragm material	EPDM
Materials	Body: PVC, diaphragms: EPDM / FKM
Temperature range	+5 to +60 °C
Control connection	G 1/4"
Control pressure	1 to 10 bar
Self-draining	3° - 6° suitable for flow direction and 25° - 33° tilted for horizontal
Socket inner diameter (mm)	20 to 63
DN (mm)	15 to 50
Socket outer diameter (mm)	20 to 63
Ends	adhesive socket, bonding nozzle
SKUs in this series	12

Description

Pneumatic, normally closed (NC) diaphragm valves with PVC body and EPDM diaphragm, with solvent cement sockets for PVC pipe. Without control air, the valve is closed, so it closes if the air supply fails. Control air opens the valve. The diaphragm separates the medium from the actuator, so only PVC and the diaphragm touch the medium. The valve is self-draining when installed with a 3° to 6° slope in the flow direction and the valve turned 25° to 33° from horizontal. For liquids. Not suitable for compressed air or other gases under pressure.

Key features

- Control air G 1/4, 1 to 10 bar
- PVC body, EPDM diaphragm
- Medium separated from the actuator
- Self-draining when installed at an angle

Models

Select the SKU for your application.

SKU	Ends	Socket inner diameter (mm)	DN (mm)	Socket outer diameter (mm)
V3MCG	adhesive socket	20	15	-
V3MCH	adhesive socket	25	20	-
V3MCJ	adhesive socket	32	25	-
V3MCK	adhesive socket	40	32	-
V3MCM	adhesive socket	50	40	-
V3MCN	adhesive socket	63	50	-
V3MCP	bonding nozzle	-	15	20
V3MCQ	bonding nozzle	-	20	25
V3MCR	bonding nozzle	-	25	32
V3MCS	bonding nozzle	-	32	40
V3MCT	bonding nozzle	-	40	50
V3MCU	bonding nozzle	-	50	63

Points to note

- Not suitable for compressed air or gases under pressure
- PVC, temperature range +5 to +60 °C only

> **⚠ Warning**
> Not suitable for compressed air or other gases under pressure!

Tameson B.V.
Torenallee 20, 5617 BC Eindhoven, The Netherlands
CoC: 72902531
VAT: NL859280263B01

Contact Information
support@tameson.com
tameson.com

Document Information
Version: 1.0

Specifications subject to change without notice. Verify current specifications before ordering.