Banjo hose nipple

Zinc plated steel, low-pressure hose

Series: S-SND4



Overview

Material	Zinc plated steel
Materials	Zinc plated steel
DN (mm)	3 to 20
Diameter ring (mm)	8 to 26
Hose diameter (inner) (mm)	4 to 5, 5 to 6, 7 to 8, 9 to 10, 11 to 12, 14 to 15, 17 to 18, 21 to 22
For banjo bolt thread	M8×1, M10×1 & G 1/8, M12×1.5, M14×1.5 & G 1/4, M16×1.5, M18×1.5, M22×1.5, M26×1.5
SKUs in this series	17

Description

Banjo hose nipples for low-pressure hose. The ring fits a banjo bolt. Use a banjo bolt and seal rings of the ring size. Choose the hose nipple by the inner diameter of the hose. Secure the hose on the nipple with a hose sleeve or a hose clamp. Both are sold separately. Zinc plated steel. For low-pressure hose only. For hydraulic hose, use crimp fittings.

Key features

- Zinc plated steel

Models

Select the SKU for your application.

SKU	DN (mm)	Hose diameter (inner) (mm)	Diameter ring (mm)	For banjo bolt thread
F2XWV	3	4 to 5	8	M8×1
F2XWY	3	4 to 5	10	M10×1 & G 1/8
F2XWW	4	5 to 6	8	M8×1
F2XWX	4	5 to 6	10	M10×1 & G 1/8
F2XX3	4	5 to 6	12	M12×1.5
F2XX5	4	5 to 6	14	M14×1.5 & G 1/4
F2XWZ	6	7 to 8	10	M10×1 & G 1/8
F2XX2	6	7 to 8	12	M12×1.5
F2XX6	6	7 to 8	14	M14×1.5 & G 1/4
F2XX4	8	9 to 10	14	M14×1.5 & G 1/4
F2XX8	8	9 to 10	16	M16×1.5
F2XXA	8	9 to 10	18	M18×1.5
F2XX7	10	11 to 12	16	M16×1.5
F2XXB	10	11 to 12	18	M18×1.5
F2XX9	13	14 to 15	18	M18×1.5
F2XXC	16	17 to 18	22	M22×1.5
F2XXD	20	21 to 22	26	M26×1.5

Points to note

- For low-pressure hose only, for hydraulic hose choose crimp fittings
- Hose sleeve or clamp not included

Tameson B.V.
Torenallee 20, 5617 BC Eindhoven, The Netherlands
CoC: 72902531
VAT: NL859280263B01

Contact Information
support@tameson.com
tameson.com

Document Information
Version: 1.0

Specifications subject to change without notice. Verify current specifications before ordering.