T-hose connector

Zinc plated steel, low-pressure hose

Series: S-T792



Overview

Materials	Zinc plated steel
DN1 (mm)	3 to 8
DN2 (mm)	3 to 8
DN3 (mm)	3 to 8
Hose diameter 1 (inner) (mm)	4 to 5, 5 to 6, 7 to 8, 9 to 10
Hose diameter 2 (inner) (mm)	4 to 5, 5 to 6, 7 to 8, 9 to 10
Hose diameter 3 (inner) (mm)	4 to 5, 5 to 6, 7 to 8, 9 to 10
SKUs in this series	6

Description

T-hose connectors with hose nipples to join three low-pressure hoses. Choose the connector by the inner diameter of each hose. Secure each hose end with a hose sleeve (crimped) or a hose clamp, both sold separately. Zinc plated steel.

Key features

- Zinc plated steel

Models

Select the SKU for your application.

SKU	Hose diameter 1 (inner) (mm)	DN1 (mm)	Hose diameter 2 (inner) (mm)	DN2 (mm)	Hose diameter 3 (inner) (mm)	DN3 (mm)
F2XSU	4 to 5	3	4 to 5	3	4 to 5	3
F2XSW	5 to 6	4	5 to 6	4	5 to 6	4
F2XSY	7 to 8	6	4 to 5	3	7 to 8	6
F2XT2	7 to 8	6	7 to 8	6	7 to 8	6
F2XT4	9 to 10	8	7 to 8	6	9 to 10	8
F2XT6	9 to 10	8	9 to 10	8	9 to 10	8

Points to note

- For low-pressure hose only, for hydraulic hose choose crimp fittings
- Hose sleeves or clamps not included

Tameson B.V.

Torenallee 20, 5617 BC Eindhoven, The Netherlands
CoC: 72902531
VAT: NL859280263B01

Contact Information

support@tameson.com
tameson.com

Document Information

Version: 1.0

Specifications subject to change without notice. Verify current specifications before ordering.