Hose connector

Zinc plated steel, low-pressure hose

Series: S-UFFA



Overview

Materials	Zinc plated steel
DN1 (mm)	3 to 13
DN2 (mm)	3 to 10
Hose diameter 1 (inner) (mm)	4 to 5, 5 to 6, 7 to 8, 9 to 10, 11 to 12, 14 to 15
Hose diameter 2 (inner) (mm)	4 to 5, 5 to 6, 7 to 8, 9 to 10, 11 to 12
SKUs in this series	10

Description

Hose connectors with hose nipples to join two low-pressure hoses. Straight and reducing versions. Choose the connector by the inner diameter of each hose. Secure each hose end with a hose sleeve (crimped) or a hose clamp, both sold separately. Zinc plated steel.

Key features

- Zinc plated steel

Models

Select the SKU for your application.

SKU	Hose diameter 1 (inner) (mm)	DN1 (mm)	Hose diameter 2 (inner) (mm)	DN2 (mm)
F2XT8	11 to 12	10	7 to 8	6
F2XT9	11 to 12	10	9 to 10	8
F2XTA	11 to 12	10	11 to 12	10
F2XTB	14 to 15	13	11 to 12	10
F2XSV	4 to 5	3	4 to 5	3
F2XSX	5 to 6	4	5 to 6	4
F2XSZ	7 to 8	6	5 to 6	4
F2XT3	7 to 8	6	7 to 8	6
F2XT5	9 to 10	8	7 to 8	6
F2XT7	9 to 10	8	9 to 10	8

Points to note

- For low-pressure hose only, for hydraulic hose choose crimp fittings
- Hose sleeves or clamps not included

Tameson B.V.
Torenallee 20, 5617 BC Eindhoven, The Netherlands
CoC: 72902531
VAT: NL859280263B01

Contact Information
support@tameson.com
tameson.com

Document Information
Version: 1.0

Specifications subject to change without notice. Verify current specifications before ordering.