45° and 90° hose nipple with tube end, light series

Zinc plated steel, low-pressure hose

Series: S-VZAJ



Overview

Material	Zinc plated steel
Series	light model series
DN (mm)	2 to 20
Pipe diameter (outer) (mm)	4 to 22
Hose diameter (inner) (mm)	9 options, see the model table
SKUs in this series	18

Description

45° and 90° hose nipples with a tube end, light series, for low-pressure hose. The tube end goes into a tube fitting for the same tube outer diameter, light series. Choose the hose nipple by the inner diameter of the hose. Secure the hose on the nipple with a hose sleeve or a hose clamp. Both are sold separately. Zinc plated steel. For low-pressure hose only. For hydraulic hose, use crimp fittings.

Key features

- Zinc plated steel

Models

Select the SKU for your application.

SKU	DN (mm)	Hose diameter (inner) (mm)	Pipe diameter (outer) (mm)
F2XW4	2	3 to 4	4
F2XWD	2	3 to 4	4
F2XW5	3	4 to 5	5
F2XWE	3	4 to 5	5
F2XW6	4	5 to 6	6
F2XWF	4	5 to 6	6
F2XW7	6	7 to 8	8
F2XWG	6	7 to 8	8
F2XW8	8	9 to 10	10
F2XWH	8	9 to 10	10
F2XW9	10	11 to 12	12
F2XWJ	10	11 to 12	12
F2XWA	13	14 to 15	15
F2XWK	13	14 to 15	15
F2XWB	16	17 to 18	18
F2XWM	16	17 to 18	18
F2XWC	20	21 to 22	22
F2XWN	20	21 to 22	22

Points to note

- For low-pressure hose only, for hydraulic hose choose crimp fittings
- Hose sleeve or clamp not included

Tameson B.V.
Torenallee 20, 5617 BC Eindhoven, The Netherlands
CoC: 72902531
VAT: NL859280263B01

Contact Information
support@tameson.com
tameson.com

Document Information
Version: 1.0

Specifications subject to change without notice. Verify current specifications before ordering.