Hose sleeve for low-pressure hose

Stainless steel 1.4301

Series: S-XCS4



Overview

Materials	1.4301
DN (mm)	3 to 25
Sleeve diameter (inner) (mm)	10 to 34.5
Floor hole (mm)	6.6 to 26
Hose diameter (outer) (mm)	13 options, see the model table
SKUs in this series	13

Description

Stainless steel hose sleeves (ferrules) for low-pressure hose. Push the sleeve over the hose end, put the hose nipple in, then crimp the sleeve. This holds the hose on the nipple. Choose the sleeve by the outer diameter of the hose, and the hose nipple by the inner diameter and DN. Stainless steel 1.4301.

Key features

- Stainless steel 1.4301

Models

Select the SKU for your application.

SKU	DN (mm)	Sleeve diameter (inner) (mm)	Hose diameter (outer) (mm)	Floor hole (mm)
F2XHZ	3	10	8.5 to 9	6.6
F2XJ3	4	11	9.5 to 10	7.5
F2XJH	4	12	10.5 to 11	7.5
F2XJ5	6	13.5	12 to 12.5	10.1
F2XJK	6	14	12.5 to 13	10
F2XJ7	8	15	13.5 to 14	11.7
F2XJN	8	16	14.5 to 16	11.7
F2XJY	8	17	15.5 to 16	12.2
F2XJ9	10	18	16.5 to 17	13.8
F2XJQ	10	19	17.5 to 18	13.8
F2XJS	13	24.5	23 to 23.5	17
F2XJD	20	28.5	27.5 to 28	20.5
F2XJF	25	34.5	32 to 33.5	26

Points to note

- For low-pressure hose only, for hydraulic hose choose crimp fittings
- Permanent crimp, needs a crimping tool

Tameson B.V.
Torenallee 20, 5617 BC Eindhoven, The Netherlands
CoC: 72902531
VAT: NL859280263B01

Contact Information
support@tameson.com
tameson.com

Document Information
Version: 1.0

Specifications subject to change without notice. Verify current specifications before ordering.