



Main

Device short name	MX
Product or component type	Voltage release
Device application	Control
Range compatibility	ComPact NSX EasyPact CVS PowerPact Multistandard ComPact NSX DC
Voltage release type	Undervoltage release
[Uc] control circuit voltage	250 V DC

Complementary

Threshold tripping voltage	0.35...0.7 x Un opening 0.85 x Un closing
Supply holding power	5 W
Supply inrush power	10 W
Mounting mode	Fixed
Response time	50 ms
Auxiliary connection terminal	Screw terminal 0...1.5 mm ²

Packing Units

Package 1 Weight	125 g
Package 2 Weight	1.328 kg
Package 3 Weight	8.455 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Contractual warranty

Warranty	18 months
----------	-----------

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.