

PRODUCT-DETAILS

CAL5-11

CAL5-11 Auxiliary Contact Block



General Information	
Extended Product Type	CAL5-11
Product ID	1SBN010020R1011
EAN	3471522121073
Catalog Description	CAL5-11 Auxiliary Contact Block
Long Description	CAL5-11 Auxiliary Contact Block

Technical	
Suitable For	AF45 AF50 AF63 AF75 A9 A12 A16 A26 A30 A40 A45 A50 A63 A75 A95 A110 AL9 AL12 AL16 AL26 AL30

AL40
 AE45
 AE50
 AE63
 AE75
 TAL9
 TAL12
 TAL16
 TAL26
 TAL30
 TAL40
 TAE45
 TAE50
 TAE75
 GA75
 GAE75
 UA16
 UA26
 UA30
 UA50
 UA63
 UA75
 UA16RA
 UA26RA
 UA30RA
 UA50RA
 UA63RA
 UA75RA
 UAF75RA
 N22E
 N31E
 N40E
 N44E
 N53E
 N62E
 N71E
 N80E
 N33/11
 N51/11
 NL22E
 NL31E
 NL40E

Rated Operational Voltage	Auxiliary Circuit 690 V
Rated Insulation Voltage (U _i)	acc. to IEC 60947-5-1 and VDE 0110 (Gr. C) 690 V acc. to UL/CSA 600 V
Rated Operational Current AC-15 (I _e)	(500 V) 2 A (690 V) 2 A (24 / 127 V) 6 A (220 / 240 V) 4 A (380 / 400 V) 3 A
Rated Short-time Withstand Current Low Voltage (I _{cw})	for 0.1 s 140 A for 1 s 100 A
Minimum Switching Capacity	A9 ... A75 17 / 5 VLT4K A95 ... AF750 24 / 50 VLT4K
Power Loss	at Rated Operating Conditions per Pole 0.1 W
Short-Circuit Protective Devices	Auxiliary Circuit - gG Type Fuses 10 A
Mechanical Durability	10 million 3 million 2 million
Number of Auxiliary Contacts NC	1
Number of Auxiliary Contacts NO	1
Mounting Type	Side Mounting
Part Type	New
Mounting Position	Side
Remarks	100
Technical Information	AUXILIARY SWITCH

Terminal Type

Screw Terminals

Environmental

Degree of Protection	acc. to IEC 60529, IEC 60947-1, EN 60529 Auxiliary Terminals IP20
RoHS Status	Following EU Directive 2011/65/EU
Environmental Information	1SBD250138E1000

Technical UL/CSA

Pilot Duty UL/CSA	A600
	Q300

Dimensions

Product Net Width	12 mm
Product Net Height	74 mm
Product Net Depth / Length	62 mm
Product Net Weight	0.05 kg

Container Information

Package Level 1 Units	2 piece
Package Level 1 Width	100 mm
Package Level 1 Height	35 mm
Package Level 1 Depth / Length	105.5 mm
Package Level 1 Gross Weight	0.1 kg
Package Level 1 EAN	3471522121073
Package Level 2 Units	box 240 piece
Package Level 2 Width	300 mm
Package Level 2 Height	308 mm
Package Level 2 Depth / Length	245 mm
Package Level 2 Gross Weight	12 kg
Package Level 3 Units	2880 piece

Ordering

Minimum Order Quantity	2 piece
Customs Tariff Number	85389099
E-Number (Finland)	3709188

Certificates and Declarations (Document Number)

CB Certificate	CB_SE_30113
CCC Certificate	CCC_2013010304604041 CCC_2004010305133985
CQC Certificate	CQC2013010304604041
CSA Certificate	CSA_1033838
Declaration of Conformity - CCC	2020980304001626

Declaration of Conformity - CE	1SBD250809U1000
Declaration of Conformity - UKCA	1SBD250826U1000
EAC Certificate	EAC_RU C-FR ME77 B03391
Environmental Information	1SBD250138E1000
GOST Certificate	GOST_POCCFRME77B07175
Instructions and Manuals	FPTC407744P0001
RINA Certificate	RINA_ELE172319XG001
RoHS Information	1SBD250809U1000
UL Certificate	UL_071301E48139

Popular Downloads

Data Sheet, Technical Information	1SBC100122C0202_Ch04
Instructions and Manuals	FPTC407744P0001

Classifications

ETIM 7	EC000041 - Auxiliary contact block
ETIM 8	EC000041 - Auxiliary contact block
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
WEEE B2C / B2B	Business To Business
CN8	8538 90 99
UNSPSC	39120000
eClass	V11.0 : 27371302
Object Classification Code	K

Categories

Low Voltage Products and Systems → Control Products → Contactors → Block Contactors Accessories

