

Rittal – The System.

Faster – better – everywhere.

► OM adaptors with spring terminals – SV 9340.650

Date : Oct 26, 2021

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



OM adaptors with spring terminals – SV 9340.650

created: 26.10.2021 on www.rittal.com/com-en



Product description

Material:	Polyamide Fire protection corresponding to UL 94-V0
Colour:	Chassis: RAL 7035
Note on Model No.:	According to a heat dissipation test to IEC 61 439-1, a current carrying capacity of up to 80 A is supported

Product description

To fit busbars:	with cross-section height: 5 mm with cross-section height: 10 mm
Number of poles:	3-pole
For bar systems with centre-to-centre spacing:	60 mm
Dimensions:	Width: 55 mm Height: 272 mm
Rated current max.:	65 A
Rated operating voltage:	690 V, 3~
Connection for round conductor cross-sections:	2,5 mm ² - 16 mm ²
Support frame:	Width: 55 mm

Height: 237 mm

Number of support rails:	2
Height of support rails:	10 mm
Support rail type:	TS 55E TS 55D-V
Support frame support:	yes
Packs of:	1 pc(s).
Weight/pack:	0.34 kg
Copper weight (kg per piece):	0.06
EAN:	4028177502673
Customs tariff number:	85369095
ETIM 7.0:	EC001531
ETIM 6.0:	EC001531
eCl@ss 8.0/8.1:	27370304
eCl@ss 6.0/6.1:	27370304
Product description:	SV OM adaptor, 65 A, 690 V, 3-pole, tension spring clamp 2,5-16 mm ² , WH: 55x272 mm, support frame, support rail TS 55E, TS 55D-V
Approvals	
Approvals:	ABS DNV-GL Lloyds Register of Shipping
Certificates:	EAC
Declarations:	Declaration of conformity