

Bell transformer, 14VA Primary 230-240 V AC, 50 Hz, secondary 8 V, 12V, 24V AC With PTC fuse, 2MW++



Model	
product brand name	SETRON
product designation	Bell transformer
design of the transformer	Standard bell transformer
General technical data	
supplied active power / maximum	14 W
Voltage	
input voltage	230 V
output voltage	
• _1 / rated value	8 V
• _2 / rated value	12 V
• _3 / rated value	24 V
Dissipation	
power loss [W] / for rated value of the current / at AC / in hot operating state / per pole	11 W
Current	
output current	

- maximum 2 A
- \_1 / rated value 2 A
- \_2 / rated value 1.3 A
- \_3 / rated value 0.6 A

### Suitability

#### suitability for integration

- surface-mounted installation No
- flush mounting No

### Product details

product component / switch No

### Product function

product function / thermal protection Yes

### Inputs Outputs

property of the output / short-circuit proof Yes

### Mechanical Design

height 64 mm

width 36 mm

length 90 mm

number of width units 2

fastening method / side-by-side mounting Yes

### Certificates

**Declaration of Conformity**

**other**

[Confirmation](#)



EG-Konf.

### Further information

#### Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

#### Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=4AC3214-0>

#### Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/4AC3214-0>

#### Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=4AC3214-0](http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=4AC3214-0)

#### CAX-Online-Generator

<http://www.siemens.com/cax>

#### Tender specifications

<http://www.siemens.com/specifications>

