Rittal - The System.

Faster – better – everywhere.

Enclosure heater with fan – SK 3105.380

Date: Apr 26, 2021



NCLOSURES POWER DISTRIBUTION CLIMATE CONTROL IT INFRASTRUCTURE SOFTWARE & SERVICES

Enclosure heater with fan – SK 3105.380

created: 26.04.2021 build on www.rittal.com/uk-en



Product description		
Description:	Enclosure heaters to regulate relative humidity, prevent temperatures from dropping below the dew point and stop condensation forming inside the enclosure. This prevents consequential damage associated with corrosion or electrical short circuits.	
Material:	Plastic	
Protection category IP to IEC 60 529:	IP 20	
Supply includes:	PTC heater with fan Assembly parts	
Note:	A thermostat is recommended for precise temperature control inside the enclosure. In order to prevent condensation on assemblies, a hygrostat is recommended to regulate heating In larger enclosures, even heat distribution is best achieved by installing several low-output heaters.	

Continuous thermal	250 W - 265 W	
output at 10 °C:	Note: Continuous thermal output with fan	
Rated operating voltage:	230 V, 1~, 50 Hz/60 Hz	
Dimensions:	Width: 103 mm	
	Height: 200 mm	
	Depth: 103 mm	
Miniature circuit- breaker/fuse:	4 A	

© Rittal 2021

Fans pre-integrated:	yes
e CI@ss 8.0/8.1:	27180710
Packs of:	1 pc(s).
Weight/pack:	1.22 kg
EAN:	4028177662865
Customs tariff number:	85162999
ETIM 7.0:	EC000737
ETIM 6.0:	EC000737
eCl@ss 8.0/8.1:	27180710
eCl@ss 6.0/6.1:	27180710
Product description:	SK enclosure heater, with fan, 250/265 W, 230 V, 1~, 50/60 Hz, WHD: 103 x 200 x 103 mm
Approvals	
Approvals:	Approval overview CSA UR + C-UR VDE
Certificates:	EAC
Declarations:	Declaration of conformity

© Rittal 2021