

Rittal – The System.

Faster – better – everywhere.

Enclosure heater with fan – SK 3105.400

Date : Apr 26, 2021

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



Enclosure heater with fan – SK 3105.400

created: 26.04.2021 build on www.rittal.com/uk-en



Product description

Description:	Enclosure heaters to regulate relative humidity, prevent temperatures from dropping below the dew point and stop condensation forming inside the enclosure. This prevents consequential damage associated with corrosion or electrical short circuits.
Material:	Plastic
Protection category IP to IEC 60 529:	IP 20
Supply includes:	PTC heater with fan Assembly parts
Note:	A thermostat is recommended for precise temperature control inside the enclosure. In order to prevent condensation on assemblies, a hygrostat is recommended to regulate heating In larger enclosures, even heat distribution is best achieved by installing several low-output heaters.

Product description

Continuous thermal output at 10 °C:	800 W - 870 W Note: Continuous thermal output with fan
Rated operating voltage:	230 V, 1~, 50 Hz/60 Hz
Dimensions:	Width: 103 mm Height: 200 mm Depth: 103 mm
Miniature circuit- breaker/fuse:	6 A

Fans pre-integrated:	yes
eCl@ss 8.0/8.1:	27180710
Packs of:	1 pc(s).
Weight/pack:	1.22 kg
EAN:	4028177662889
Customs tariff number:	85162999
ETIM 7.0:	EC000737
ETIM 6.0:	EC000737
eCl@ss 8.0/8.1:	27180710
eCl@ss 6.0/6.1:	27180710
Product description:	SK enclosure heater, with fan, 800/870 W, 230 V, 1~, 50/60 Hz, WHD: 103 x 200 x 103 mm
Approvals	
Approvals:	Approval overview CSA UR + C-UR VDE
Certificates:	EAC
Declarations:	Declaration of conformity