Rittal - The System.

Faster – better – everywhere.

OM adaptors with connection cables – SV 9340.460

Date : Apr 26, 202



ENCLOSURES >> POWER DISTRIBUTION >> CLIMATE CONTROL >> IT INFRASTRUCTURE >> SOFTWARE & SERVICES >>

OM adaptors with connection cables - SV 9340.460

created: 26.04.2021 build on www.rittal.com/uk-en



			4.
UKAA	111242	escri	α
		-	
			~~

Material: Polyamide

Fire protection corresponding to UL 94-V0

Colour: Chassis: RAL 7035

Note: The technical data may vary for UL applications

Product description

To fit busbars: with cross-section height: 5 mm

with cross-section height: 10 mm

Number of poles: 3-pole

For bar systems with centre-to-centre

spacing:

60 mm

Dimensions: Width: 55 mm

Height: 208 mm

Rated current max.: 32 A

Rated operating

voltage:

690 V, 3~

Connection cable: Cross-section: AWG 10

Length: 130 mm

Support frame: Width: 55 mm

Height: 170 mm

© Rittal 2021

Number of support rails:	1
Height of support rails:	10 mm
Support rail type:	TS 55D
Packs of:	1 pc(s).
Weight/pack:	0.34 kg
Copper weight (kg per piece):	0.07
EAN:	4028177502567
Customs tariff number:	85369095
ETIM 7.0:	EC001531
ETIM 6.0:	EC001531
eCl@ss 8.0/8.1:	27370304
eCl@ss 6.0/6.1:	27370304
Product description:	SV OM adaptor, 32 A, 690 V, 3-pole, connection cable AWG 10, WH: 55x208 mm, support frame, support rail TS 55D
Approvals	
Approvals:	ABS C-UL DNV-GL Lloyds Register of Shipping UL + C-UL
Certificates:	EAC
Declarations:	Declaration of conformity

© Rittal 2021 2