

Rittal – The System.

Faster – better – everywhere.

Connection adaptor – SV 9342.210

Date : Oct 26, 2021

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



Connection adaptor – SV 9342.210

created: 26.10.2021 on www.rittal.com/com-en



Product description

Material: Cover: ABS
Punched section: Polyamide
Chassis 3439.010: Fibreglass-reinforced, thermoplastic polyester (PBT)
Fire protection corresponding to UL 94-V0
Punched section: Polyamide

Colour: RAL 7035

Note: The technical data may vary for UL applications
UL approval only applies in conjunction with AC application
The rated operating voltage for DC applications depends on the busbar arrangement in the busbar supports 9340.050/9341.050/9342.050.

Product description

To fit busbars: with cross-section height: 5 mm
with cross-section height: 10 mm

Number of poles: 3-pole

For bar systems with centre-to-centre spacing: 60 mm

Dimensions: Width: 20 mm
Height: 215 mm

Rated current max.: 63 A

Rated operating voltage: 690 V, 3~

Connection for round conductor cross-sections: fine wire with wire end ferrule: 2,5 mm² - 10 mm²
multi-wire: 2,5 mm² - 10 mm²
solid: 2,5 mm² - 10 mm²

Cable outlet: Bottom

Packs of: 1 pc(s).

Weight/pack: 0.22 kg

Copper weight (kg per piece): 0.02

EAN: 4028177503601

Customs tariff number: 85369010

ETIM 7.0: EC001531

ETIM 6.0: EC001531

eCl@ss 8.0/8.1: 27370304

eCl@ss 6.0/6.1: 27370304

Product description: SV Connection adaptor, 63 A, 690 V, 3-pole, cable outlet bottom, round conductor connection 2,5-10 mm²

Approvals

Approvals: ABS
C-UL
DNV-GL
Lloyds Register of Shipping
UL + C-UL

Certificates: EAC

Declarations: Declaration of conformity