

PRODUCT-DETAILS

SN201 L-C10

SN201 L-C10 Miniature circuit breaker - 1+NP - C - 10 A



General Information

Extended Product Type	SN201 L-C10
Product ID	2CSS245101R0104
EAN	8012542088554
Catalog Description	SN201 L-C10 Miniature circuit breaker - 1+NP - C - 10 A
Long Description	The SN201 series miniature circuit breaker is a 1P+N device in 1 module for the protection of circuits against overload and short circuit. Neutral is on the right

Technical

Standards	IEC/EN 60898-1
Tripping Characteristic	C
Rated Voltage (U_r)	230 V AC
Rated Operational Voltage	acc. to IEC 60898-1 230/240 V AC
Rated Insulation Voltage (U_i)	500 V AC
Rated Impulse Withstand Voltage (U_{imp})	4 kV
Dielectric Test Voltage	2.5 kV
Primary Rated Impulse Withstand Voltage	4 kV
Input Voltage Type	AC

Rated Current (I_n)	10 A
Rated Short-Circuit Capacity	(230 V AC) 4.5 kA
Rated Ultimate Short-Circuit Breaking Capacity (I_{cu})	(230 V AC) 6 kA
Rated Service Short-Circuit Breaking Capacity (I_{cs})	(230 V AC) 4.5 kA
Rated Frequency (f)	50/60 Hz
Power Loss	1.9 W
Power Supply Connection	Arbitrary
Contact Position Indication	Red ON / Green OFF
Energy Limiting Class	3
Electrical Endurance	10000 cycle
Mechanical Endurance	20000 cycle
Number of Poles	1+N
Number of Protected Poles	1
Number of Modular Spacings per DIN Rail	1
Overvoltage Category	III
Position of Neutral Terminals	Right
Tightening Torque	1.2 N·m
Accessory Type	Auxiliary contact Signal contact / auxiliary contact Shunt trip Undervoltage release
Actuator Type	Toggle - Insulation group IIIA, black, sealable in ON-OFF positions
Housing Type	Insulation group II, RAL 7035
Screw Terminal Type	Cage Terminal
Mounting Position	Any
Accessories Available	Yes
Connecting Capacity	Busbar 10 mm ² Rigid 1 ... 16 mm ² Flexible 1 ... 10 mm ²
Wire Stripping Length	11 mm
Terminal Type	Screw Terminals

Environmental

Ambient Temperature	-25...55 °C
Ambient Air Temperature	Operation -25 ... 55 °C Storage -40 ... 70 °C
Reference Ambient Air Temperature	30 °C
Degree of Protection	Housing IP40 Terminals IP20
Pollution Degree	2
Environmental Conditions	28 cycles ;with 55 °C / 90-96 %

;and 25 °C / 95-100 %

Resistance to Vibrations acc. to IEC 60068-2-6	0.35mm or 5g - 20 cycles at 5...150...5 Hz without load
---	---

Resistance to Shock acc. to IEC 60068-2-27	30g 2 shocks 13 ms
---	--------------------

RoHS Status	Following EU Directive 2011/65/EU
-------------	-----------------------------------

Environmental Information	refer to RoHS information
---------------------------	---------------------------

Dimensions

Width in Number of Modular Spacings	1
Product Net Width	0.018 m
Product Net Height	0.085 m
Product Net Depth / Length	0.069 m
Product Net Weight	0.110 kg
Built-In Depth (t ₂)	76 mm

Container Information

Package Level 1 Units	box 6 piece
Package Level 1 Width	0.11 m
Package Level 1 Height	0.075 m
Package Level 1 Depth / Length	0.092 m
Package Level 1 Gross Weight	0.684 kg
Package Level 1 EAN	8012542088561

Ordering

Minimum Order Quantity	1 piece
Customs Tariff Number	85362010
E-Number (Finland)	3217710
Country of Origin	Italy (IT)

Certificates and Declarations (Document Number)

Declaration of Conformity - CE	9AKK106713A5572
Environmental Information	refer to RoHS information
Instructions and Manuals	No document needed
RoHS Information	9AKK106713A5572

Popular Downloads

Data Sheet, Technical Information	2CSC400002D0209
--------------------------------------	-----------------

Instructions and Manuals

No document needed

Classifications

ETIM 7	EC000042 - Miniature circuit breaker (MCB)
ETIM 8	EC000042 - Miniature circuit breaker (MCB)
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
WEEE B2C / B2B	Business To Consumer
CN8	85362010
eClass	V11.0 : 27141901
Object Classification Code	F

Categories

Low Voltage Products and Systems → Modular DIN Rail Products → Miniature Circuit Breakers MCBs

