

Rittal – The System.

Faster – better – everywhere.

LED system light – SZ 2500.220

Date : Jun 14, 2019

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



LED system light – SZ 2500.220

created: 14.06.2019 on www.rittal.com/com-en



Product description

Description:	LED system light – the first light especially for enclosures! Highly innovative LED technology for even more light into the very last corner.
Benefits:	Optimum illumination of the entire enclosure Optionally with clip, screw and magnetic attachment A configuration to suit every application
Equipment:	90° rotating connector Adjustable light distribution
Material:	Light body: Extruded aluminium Light cover: Polycarbonate (halogen-free) Light ends: PC-ABS (halogen-free)
Colour:	Enclosure: RAL 7016
Protection category IP to IEC 60 529:	IP 20
Supply includes:	Assembly screws

Product features

Dimensions:	Width: 437 mm Height: 75 mm Depth: 23 mm
Rated operating voltage:	24 V (DC)
Operating temperature:	Operation (environment): -20°C...+55°C

Power consumption:	11 W
Luminous flux:	900 lm
Light colour:	4000 K (neutral white)
Protection category:	III (SELV)
Connection options:	Infeed, 2-pole Through-wiring, 2-pole Door-operated switch
Light – installation type:	Screw-fastening Clip attachment Magnetic attachment (accessory)
Packs of:	1 pc(s).
Weight/pack:	0.54 kg
Copper weight (kg per piece):	0
EAN:	4028177806979
Customs tariff number:	94054099
ETIM 6.0:	EC000321
ETIM 5.0:	EC000321
eCl@ss 8.0/8.1:	27189241
eCl@ss 7.0/7.1:	27189241
eCl@ss 6.0/6.1:	27189241
eCl@ss 5.1/5.1.4:	27189241
Product description:	SZ System Light LED, 900 Lumen, L: 437 mm, 24 V DC
Approvals	
Approvals:	CQC CSA ENEC UL + C-UL
Certificates:	EAC

Declarations:

Declaration of conformity
