

## Ferrule - Al 0,34- 8 TQ - 3203066

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)

Ferrule, Sleeve length: 8 mm, Length: 12.5 mm, Color: turquoise



The figure shows the version Al  
2,5-12 BU

### Why buy this product

- ✓ The Al 0,25... can also be used to process 0.14 mm<sup>2</sup> conductors
- ✓ The ferrules with plastic sleeve are made from soft tin-plated electrolytic copper
- ✓ In terms of dimensions, they correspond to DIN 46228-4: 1990-09



### Key commercial data

|                                      |                                                                                                         |
|--------------------------------------|---------------------------------------------------------------------------------------------------------|
| Packing unit                         | 100 pc                                                                                                  |
| Minimum order quantity               | 100 pc                                                                                                  |
| GTIN                                 | <br>4 046356 013017 |
| Weight per Piece (excluding packing) | 0.06 g                                                                                                  |
| Custom tariff number                 | 85369010                                                                                                |
| Country of origin                    | Germany                                                                                                 |

### Technical data

#### Dimensions

|                                              |         |
|----------------------------------------------|---------|
| Length (b)                                   | 12.5 mm |
| Sleeve length                                | 8 mm    |
| Inner dimension of the insulating collar (d) | 2 mm    |
| Ferrule diameter                             | 0.8 mm  |
| Insulating collar thickness                  | 0.25 mm |
| Sleeve wall thickness                        | 0.15 mm |

#### Ambient conditions

|                            |        |
|----------------------------|--------|
| Short-term temperature     | 120 °C |
| Max. permanent temperature | 105 °C |

## Ferrule - Al 0,34- 8 TQ - 3203066

### Technical data

#### General

|                                         |                                |
|-----------------------------------------|--------------------------------|
| Color                                   | turquoise                      |
| Components                              | free from silicone and halogen |
| Inflammability class according to UL 94 | HB                             |
| Material                                | E-CU                           |

### Classifications

#### eCl@ss

|            |          |
|------------|----------|
| eCl@ss 4.0 | 27060701 |
| eCl@ss 4.1 | 27060701 |
| eCl@ss 5.0 | 27400201 |
| eCl@ss 5.1 | 27400201 |
| eCl@ss 6.0 | 27400201 |
| eCl@ss 7.0 | 27400201 |
| eCl@ss 8.0 | 27400201 |

#### ETIM

|          |          |
|----------|----------|
| ETIM 2.0 | EC000005 |
| ETIM 3.0 | EC000005 |
| ETIM 4.0 | EC000005 |
| ETIM 5.0 | EC000005 |

#### UNSPSC

|               |          |
|---------------|----------|
| UNSPSC 6.01   | 30212109 |
| UNSPSC 7.0901 | 27121703 |
| UNSPSC 11     | 27121703 |
| UNSPSC 12.01  | 27121703 |
| UNSPSC 13.2   | 27121703 |

### Approvals

#### Approvals

---

##### Approvals

CSA / CSAus / cCSAus

---

##### Ex Approvals

---

##### Approvals submitted

## Ferrule - Al 0,34- 8 TQ - 3203066

### Approvals

#### Approval details

CSA 

CSAus

cCSAus

### Drawings

Dimensioned drawing

