

BUSBAR VOOR AARDING EN N-GELEIDER, MESSING, 12 AANSL.

CATALOG NUMBER

EB12



nVent ERIFLEX Connecting, Earthing and Neutral Busbars are used to connect several earthing conductors within a panel and can be used in a variety of different applications including switchgear and control equipment, electrical equipment, for wind and solar power generation and in data centers.

CERTIFICATIONS



FEATURES

Use to connect several earthing conductors

Chamfered holes allow for easy connections

Rigid bar

RoHS compliant

PRODUCTKENMERKEN

Article Number: 568610

Material: Messing

Number of Connections: 12

Conductor Size, IEC: (2) 16 - 35 mm² Stranded;(10) 4 - 16 mm² Stranded

Ferrule Conductor Size, IEC: (2) 10 - 35 mm²;(10) 2.5 - 16 mm²

Conductor Size, UL: (2) #6 Solid;(10) #8 - #6 Solid;(2) #6 Stranded;(10) #8 - #6 Stranded

Max Current Rating: 250 A

Depth: 6 mm

Height: 13 mm

Width: 120 mm


A: 105 mm

B: 9 mm

Unit Weight: 0.068 kg

Complies With: IEC® 61439.1

DIAGRAMS



WAARSCHUWING

Producten van nVent moeten worden geïnstalleerd en gebruikt op de manier zoals is aangegeven in de nVent productinformatiebladen en trainingsmaterialen. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Door onjuist installeren, verkeerd gebruik, verkeerde toepassing of enige andere handeling in strijd met de instructies en waarschuwingen van nVent kan het product mogelijk niet correct werken, ernstig of fataal letsel en materiële schade veroorzaken en/of uw garantie ongeldig maken.

Noord-Amerika

+1.800.753.9221

Option 1 – Customer Care

Option 2 – Technical Support

Europa

Netherlands:

+31 800-0200135

France:

+33 800 901 793

Europa

Germany:

800 1890272

Other Countries:

+31 13 5835404

APAC

Shanghai:

+ 86 21 2412 1618/19

Sydney:

+61 2 9751 8500



Our powerful portfolio of brands:
nVent.com CADDY ERICO HOFFMAN RAYCHEM SCHROFF
TRACER