

PRODUCT-DETAILS

BE/S4.20.2.1

BE/S4.20.2.1 Binary Input, 4-fold, Contact Scanning, MDRC



General Information

Extended Product Type	BE/S4.20.2.1
Product ID	2CDG110090R0011
EAN	4016779710787
Catalog Description	BE/S4.20.2.1 Binary Input, 4-fold, Contact Scanning, MDRC
Long Description	The device interrogates 4 floating contacts using an internally generated scanning voltage. State inputs via 4 LEDs. Max. 4 signals (in 2 groups) are detectable. Each channel one push button for manual operation. Supplied by ABB i-bus®.

Ordering

EAN	4016779710787
Customs Tariff Number	85389091
Minimum Order Quantity	1 piece
E-Number (Switzerland)	405607305
E-Number (Finland)	2815304
E-Number (Sweden)	1750242

Dimensions

Product Net Depth / Length	64.5 mm
Product Net Height	90 mm
Product Net Width	36 mm
Product Net Weight	0.1 kg

Container Information

Package Level 1 Units	box 1 piece
Package Level 1 EAN	4016779710787
Package Level 1 Depth / Length	41 mm
Package Level 1 Height	65 mm
Package Level 1 Width	92 mm
Package Level 1 Gross Weight	0.12 kg

Technical

Compatible Bus Systems	KNX (TP)
Degree of Protection	IP20
Mounting Type	DIN-Rail
Width in Number of Modular Spacings	2

Certificates and Declarations (Document Number)

CB Certificate	9AKK107991A3185
Data Sheet, Technical Information	2CDC504041D0202 2CDC504076D0202
Declaration of Conformity - CE	2CDK504018D2701
Instructions and Manuals	2CDG941070P0005
RoHS Information	2CDK504018D2701

Environmental

RoHS Status	Following EU Directive 2011/65/EU
-------------	-----------------------------------

Classifications

ETIM 7	EC000688 - Binary input for bus system
ETIM 8	EC000688 - Binary input for bus system
eClass	V11.0 : 27143121
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categories

Low Voltage Products and Systems → Home and Building Automation → KNX → Standard Inputs → Binary Inputs Contact Scanning

