

Product data sheet

Item No. 92.232.3010.1

Cable assembly GST18i3K1BS 15W 30SW

geis® Extension cable female - male; length: 3m; type GST18i3;
3-pole;250 V / 16 A; colour of coding: black with black strain-relief;
cable: H05V2V2-F 3G1,5, colour: black



Item No.	92.232.3010.1
EAN	4015573692404
Order Unit	25 Piece(s)

Certificates / Approvals

Technical data

General

Rated current	16 A
Rated voltage	250 V
Rated impulse voltage	4 kV
Pollution degree	2
Mechanical coding	Code 1
Interlockable	Yes
Color of coding/ contact carrier	Black
Marking of poles	
Color of housing inclusive strain relief	Black

Model

Number of poles	3
Nominal cross section conductor	1.5 mm ²
Degree of protection (IP)	IP40
Cable type	H05V2V2-F
Cable colour	Black
Cable diameter	8.3 mm
Version of cable	Female - male
Type of cord set	Connecting cable
Version cable end 1	GST18i3 socket



Version cable end 2	GST18i3 plug
---------------------	--------------

Material

Surface finish	Tin-plated
Halogen free	No
Continuous temperature of cable	90 °C
Insulation components continuous temperature	100 °C

Dimensions

Total length	3 m
--------------	-----

Technical drawing

.F	Farbe colour	Codierung *X* <small>Stecker female</small>	Codierung *Y* <small>Stecker male</small>	Kabelfarbe cable colour
.1	schwarz black			schwarz black
.2	weiß white			weiß white
.3	grau grey			schwarz black
.5	rot red			schwarz black

Buchenteil/female connector **Steckerteil/male connector**

Kabel/cable H05 V2V2-F3G1,5
 wärmebeständig 90°C / heat resistant 90°C
 Farbe/colour: siehe Tabelle/see table

Teile-Nr. part-no.	L	Beispiel (Farbe: schwarz) example (colour: black)	Typ type
92.232.XX10.F	XX in dm-Schritten	92.232.1010.1 = 10dm/L= 1000mm	GST1813K1BS 15W 10SW
U2.232.XX10.F	XX in m-Schritten	U2.232.1210.1 = 12 m/L=12000mm	GST1813K1BS 15W X12SW

Typ/type: GST1813K1BS 15W ..
 SW = schwarz/black
 WS = weiß/white
 GR01 = grau/grey
 RT03 = rot/red

Zeichnung nach DIN 1302/Reference system acc. to DIN 7102. This DIN standard describes the envelope principle. According to the envelope principle the deviations of form and position are limited by the size tolerances.		series 02 <small>Steckersteckverbindungen nach IEC 60643-1 für ungeschützte Leitungen</small> (Customized with Wieland document U2-50M-10/13 (list of prohibited / acceptable hazardous substances) to be declared)	
The reference work: General tolerance:	CAD - Drawing, keine manuellen Änderungen CAD - Drawing, no manual modifications allowed	L: Verwendung: - First Use: -	Blatt: 1 von: 1
Werkstoff/Material:	2007 Tag/Date: Name:	Zeichnung Nr./Drawing No.:	
Maßstab/Scale:	05.06.11 Erstsch. T.	92.232.0210.1 01K	
Maßstab/Scale:	1:1	Maße in mm/Dimensions are in mm	
Maßstab/Scale:	1:1	Ersatz für/Replacement for: -	
Maßstab/Scale:	1:1	Type:	
Maßstab/Scale:	1:1	Bezeichnung/Title:	
Maßstab/Scale:	1:1	INSTALL. COUPLER KONFEKT-LEITUNG Buchse/female - Stecker/male 1,5mm Crimpversion K1 25DV 190°C-Leitung/cable	
Änderung/Revision:	1:1	00-PEM-05/91	

Weitere Daten siehe Katalog
 further data see catalog