

Product data sheet

Item No. 92.238.6000.1

Cable assembly GST1813K1BS 25 60SW

geis® Extension cable female - male; length: 6m; type GST1813;
3-pole;250 V / 20 A; colour of coding: black with black strain-relief;
cable: H05VV-F 3G2,5, colour: black



Item No.	92.238.6000.1
EAN	4015573369733
Order Unit	10 Piece(s)

Certificates / Approvals



Technical data

General

Rated current	20 A
Rated voltage	250 V
Rated impulse voltage	4 kV
Pollution degree	2
Mechanical coding	Code 1
Interlockable	Yes
Color of coding/ contact carrier	Black
Marking of poles	
Color of housing inclusive strain relief	Black

Model

Number of poles	3
Nominal cross section conductor	2.5 mm ²
Degree of protection (IP)	IP40
Cable type	H05VV-F
Cable colour	Black
Cable diameter	10.2 mm
Version of cable	Female - male



Type of cord set	Connecting cable
Version cable end 1	GST18i3 socket
Version cable end 2	GST18i3 plug

Material

Surface finish	Tin-plated
Halogen free	No
Continuous temperature of cable	70 °C
Insulation components continuous temperature	100 °C

Dimensions

Total length	6 m
--------------	-----

Technical drawing

.F	Farbe colour	Codierung Buchse Female	Codierung Stecker male	Kabelfarbe cable colour
.1	schwarz black	N R L	L R N	schwarz black
.2	weiß white	N R L	L R N	weiß white
.3	grau grey	N R L	L R N	schwarz black
.5	rot red	N R L	L R N	schwarz black

Kabel/cable: H05VV-F3G2,5
Farbe/colour: siehe Tabelle/see table

Teile-Nr. part-no.	L	Beispiel (Farbe: schwarz) example (colour: black)	Typ type
92.238.XX00.F	XX in dm-Schritten	92.238.1000.1 = 10dm/L= 1000mm	GST18i3K1BS 25 10SW
U2.238.XX00.F	XX in m-Schritten	U2.238.1200.1 = 12 m/L=12000mm	GST18i3K1BS 25 X12SW

SW = schwarz/black
WS = weiß/white
GR01 = grau/grey
RT03 = rot/red

Typ/type: GST18i3K1BS 25

Weitere Daten siehe Katalog
further data see catalog

Interferenz Size ISO 14242/Tolerance system Size ISO 14242
This ISO-standard describes the envelope principle. According to the envelope principle the deviations of form and parallelism are limited by the size tolerances.
Freifertigung nach Serial tolerance
3D - Drückung, keine manuellen Änderungen
3D - drawing, no manual modifications allowed
1. Fertigung First Use
Zust: () von ()
Zust: () von ()

Material	Werkstoff/Material	ZUGB	Tag/Date	Name	Zeichnung Nr./Drawing No.	Index
Material	Werkstoff/Material	Tag/Date	Tag/Date	Tag/Date	92.238.0200.1 01K	a

Made in mm/Dimensions are in mm

wieland
Wieland Electric
Wieland Group

PRE-ASSEMBLED CABLE
KONFEKT-LEITUNG
Buchse/female-Stecker/male Crimpversion K1
250V AC 20A 2,5mm

WU-FEM-88/916