


Item no.: 224-201  
 Product description: SERVICE CONNECTOR; CAGE CLAMP®CONNECTION



Packing unit 50 pieces



Product group	7 (Push Wire Conn.)
Cross section from [mm <sup>2</sup> ]	0,5 mm <sup>2</sup>
Cross section to [mm <sup>2</sup> ]	2,5 mm <sup>2</sup>
Cross section from [AWG]	20 AWG
Cross section to [AWG]	16 AWG
Wiring method	e+f
Connection method	CAGE CLAMP®CONNECTION
Measured voltage EN	400 V
Measured shock voltage	4 kV
Pollution degree	2
Current intensity EN	24 A
Weight	4,4 g
Color	grey
Wiring type	Side-entry
No. of connection Points	2
No. of potentials	1
Height	15,5 mm
Height	0,61 in
Width	8,5 mm
Width	0,335 in
Depth	42 mm
Depth	1,654 in



Strip length from	9 mm
Strip length to	11 mm
Strip length	0,39 in



Item number	Admission office	Approval no.	Voltage [V]	Current [A]	Cross section [ mm <sup>2</sup> ]
224-201	ABS	04-HG476172-PDA	400	24	0,5-2,5
224-201	BV	11914/BO	300	24	2,5
224-201	CCA	DK2527	400	24	2,5
224-201	CSA	154112-1059435	300		20-16
224-201	DEMKO	143835-01	400	24	2,5
224-201	DNV	E7569	400	24	0,5-2,5
224-201	FIMKO	163400-01			2,5
224-201	GL	17294-00HH	300	24	2,5
224-201	KEMA	96.1739.01	400	24	2,5
224-201	LR	04/20013(E1)	400	24	2,5
224-201	NEMKO	P96191377			2,5
224-201	ÖVE	1193-032-02	400	24	0,5-2,5
224-201	PSE	JET0695-43040-1001	300	20	20-16
224-201	RMR	11130002	400	24	0,5-2,5
224-201	SEMKO	9617079			2,5
224-201	UL	E69654	300	20	20-16

Sorting criteria: admission office - approval number

© WAGO Kontakttechnik GmbH & Co. KG

Specifications are subject to changes and errors may be expected