

Item no.: 243-208  
 Product description: Micro push-wire connector for junction boxes 8-conductor terminal block



Produkt kann von Bild abweichen / product may differ

Packing unit 500 10\*50 pieces

Product group	7 (Push Wire Conn.)
pole count	8
Connection method	PUSH WIRE®
Cross section [AWG]	22 - 20 AWG
Diameter from	0.6 mm
Diameter to	0.8 mm
Measured voltage EN	100 V
Measured shock voltage	1.5 kV
Pollution degree	2
Current intensity EN	6 A
Weight	1.44 g
Color	dark grey
Wiring type	Side-entry
No. of connection Points	8
No. of potentials	1
Height	6.8 mm
Height	0.268 in
Width	18.4 mm
Width	0.725 in
Depth	10 mm

Depth	0.394 in
Strip length from	5 mm
Strip length to	6 mm
Strip length	0.22 in



Item number	Admission office	Approval no.	Voltage [V]	Current [A]	Cross section [ mm <sup>2</sup> ]
243-208	ABS	04-HG476172/1-PDA	100	6	0,5-0,75
243-208	ABS	10-HN17750340X	100	6	4x0,5-1,0
243-208	CSA	18677-31	150	7	22-20
243-208	DEMKO	105047	100	6	4x0,5-1,0
243-208	KEMA	123448.01	100	6	05-1,0 sol
243-208	LR	04/20013(E3)	100	6	0,5-0,75
243-208	RMR	11130002	100	6	0,5-0,75
243-208	SEMKO	9144043	100	6	0,33-0,52/4x0,82
243-208	UR	E45172	150/150	7	22-18

Sorting criteria: admission office - approval number

© WAGO Kontakttechnik GmbH & Co. KG

Specifications are subject to changes and errors may be expected