

Product data sheet

Item No. 92.230.0504.1

Cable assembly

geis® Connection cable male - free end; length: 0,5m; type GST18I3; 3-pole; 250 V / 6 A; colour of coding: black with black strain-relief; cable: H05VV-F 3G0,75, colour: black



Item No.	92.230.0504.1
EAN	4015573791473
Order Unit	150 Piece(s)

Certificates / Approvals



Technical data

General

Rated current	6 A
Rated voltage	250 V
Rated impulse voltage	4 kV
Pollution degree	2
Mechanical coding	Code 1
Interlockable	Yes
Color of coding/ contact carrier	Black
Marking of poles	
Color of housing inclusive strain relief	Black

Model

Number of poles	3
Nominal cross section conductor	0.75 mm ²
Degree of protection (IP)	IP40
Wire strip length	9 mm
sheath strip length	37 mm
Preparation of conductor ends	Ultrasonically compressed wire ends
Cable type	H05VV-F

Cable colour	Black
Cable diameter	6.7 mm
Version of cable	Male - free end
Type of cord set	Connection cable
Version cable end 1	GST18i3 plug
Version cable end 2	Free end

Material

Surface finish	Tin-plated
Halogen free	No
Continuous temperature of cable	60 °C
Insulation components continuous temperature	100 °C

Dimensions

Total length	0.5 m
--------------	-------

Technical drawing

Technical drawing showing cable and plug views with dimensions and a table of part numbers.

Dimensions: 12.6, 37, 69, 19.5, 28.4

Table of part numbers:

Teile - Nr. / part-no.:	Farbe / colour:	Kabellänge / cable length:	Teile - Nr. / part-no.:	Farbe / colour:	Kabellänge / cable length:	Teile - Nr. / part-no.:	Farbe / colour:	Kabellänge / cable length:
92.230.0204.F	1	186	92.230.3504.F		3486			
92.230.0304.F		286				92.230.7004.F		6986
92.230.0404.F		386						
92.230.0504.F		486						
92.230.0604.F		586						
92.230.0704.F		686	92.230.4004.F		3986			
92.230.0804.F		786						
92.230.0904.F		886						
92.230.1004.F		986						
92.230.1104.F		1086						
92.230.1204.F		1186	92.230.4504.F		4286			
92.230.1304.F		1286						
92.230.1404.F		1386				92.230.8004.F		7986
92.230.1504.F		1486						
92.230.1604.F		1586						
92.230.1704.F		1686	92.230.5004.F		4986			
92.230.1804.F		1786						
92.230.1904.F		1886						
92.230.2004.F		1986						
92.230.2104.F		2086						
92.230.2204.F		2186						
92.230.2304.F		2286						
92.230.2404.F		2386				92.230.9004.F		8986
92.230.2504.F		2486						
92.230.2604.F		2586						
92.230.2704.F		2686	92.230.6004.F		5986			
92.230.2804.F		2786						
92.230.2904.F		2886						
92.230.3004.F		2986						

0,2m ± 3% entspricht 92.230.0204.F
 0,2m ± 3% equivalent to 92.230.0204.F

9,9m ± 3% entspricht 92.230.9904.F
 9,9m ± 3% equivalent to 92.230.9904.F

Ansicht "X" view "X"

Typ: GST18i3K1-S 75 . SW

Freifertigung nach / Manufactured to: Maßstab / Scale: 1:1, Zeichnung / Drawing: 92.230.0204.1 01K, Zeichnung Nr. / Drawing No.: 92.230.0204.1 01K

Wieland logo and product name: INST_STECKVERB_M_KABEL (Stecker/male-free end Cable/Free end 6,75mm/6A)