


PRODUCT-DETAILS

SZ-KS16/12NB

SZ-KS16/12NB Busbar



General Information

Extended Product Type	SZ-KS16/12NB
Product ID	GHV0360503R0025
EAN	4016779158800
Catalog Description	SZ-KS16/12NB Busbar
Long Description	SZ-KL16/12NB BUS BAR

Technical

Rated Operational Voltage	400 V Maximum 400 V
Voltage Protection Level (Up)	4.5 kV
Rated Short-time Withstand Current Low Voltage (I_{cw})	25 kA
Rated Uninterrupted Current (I_u)	63 A
Pitch	17.5
Number of Poles	12
Number of Phases	1
Number of Mountable Devices	12
Accessory Type	Busbar
Connection Type	Pin
Rated Cross-Section	10 mm ²

Environmental

RoHS Status	Following EU Directive 2011/65/EU
-------------	-----------------------------------

Dimensions

Product Net Depth / Length	230 mm
Product Net Weight	0.04 kg
Product Net Length	230 mm

Container Information

Package Level 1 Units	carton 30 piece
Package Level 1 Width	84 mm
Package Level 1 Height	50 mm
Package Level 1 Depth / Length	100 mm
Package Level 1 Gross Weight	1.3 kg
Package Level 1 EAN	4016779158800

Ordering

Minimum Order Quantity	1 piece
Customs Tariff Number	85389099
Country of Origin	Germany (DE)

Certificates and Declarations (Document Number)

Declaration of Conformity - CE	2CDK446006D0401
Instructions and Manuals	No document needed

Popular Downloads

Data Sheet, Technical Information	No document needed
Instructions and Manuals	No document needed

Classifications

ETIM 7	EC000215 - Phase busbar
ETIM 8	EC000215 - Phase busbar
EPLAN Catalog Tree	Electrical engineering / Protection devices / General
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
WEEE B2C / B2B	Business To Business
CN8	8538 90 99
UNSPSC	39121614
eClass	V11.0 : 27371306

Categories

Low Voltage Products and Systems → Modular DIN Rail Products → Miniature Circuit Breakers MCBs Accessories → Busbars and Accessories (IEC Range)

