

Fuse plug - ST-SI-UK 4 - 0921011

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Fuse plug, Nominal current: 6.3 A, Length: 33.1 mm, Width: 6.1 mm, Height: 45.7 mm, Color: black

Key Commercial Data

Packing unit	50 pc
GTIN	 4 017918 010270
Weight per Piece (excluding packing)	5.73 g
Custom tariff number	85363010
Country of origin	Poland

Technical data

General

Color	black
Insulating material	PA
Flammability rating according to UL 94	V2

Dimensions

Width	6.1 mm
Length	33.1 mm

General

Fuse	G / 5 x 20
Insulating material group	CTI 600
Maximum load current	6.3 A
Nominal current I_N	6.3 A
Nominal voltage U_N	250 V

Connection data

Connection method	Plug connection
-------------------	-----------------

Standards and Regulations

Connection in acc. with standard	CSA
Flammability rating according to UL 94	V2

Fuse plug - ST-SI-UK 4 - 0921011

Classifications

eCl@ss

eCl@ss 4.0	27141199
eCl@ss 4.1	27141199
eCl@ss 5.0	27141145
eCl@ss 5.1	27141145
eCl@ss 6.0	27141149
eCl@ss 7.0	27141149
eCl@ss 8.0	27142001

ETIM

ETIM 2.0	EC000897
ETIM 3.0	EC000897
ETIM 4.0	EC002018
ETIM 5.0	EC000036

UNSPSC

UNSPSC 6.01	30211811
UNSPSC 7.0901	39121409
UNSPSC 11	39121409
UNSPSC 12.01	39121409
UNSPSC 13.2	39121409

Approvals

Approvals

Approvals

CSA / UL Recognized / cUL Recognized / ABS / EAC / cULus Recognized

Ex Approvals

Approvals submitted

Approval details

CSA 	
Nominal current I _N	10 A

Fuse plug - ST-SI-UK 4 - 0921011

Approvals

Nominal voltage UN	300 V

UL Recognized 	
Nominal current IN	6.3 A
Nominal voltage UN	300 V

cUL Recognized 	
Nominal current IN	6.3 A
Nominal voltage UN	300 V

ABS	
Nominal current IN	10 A
Nominal voltage UN	300 V

EAC

cULus Recognized 
--