

## UL Online Certifications Directory

### XCFR2.E60425 Terminal Blocks - Component

[Page Bottom](#)

### Terminal Blocks - Component

[See General Information for Terminal Blocks - Component](#)

**PHOENIX CONTACT GMBH & CO KG**

E60425

FLACHSMARKTSTRASSE 8

32825 BLOMBERG, GERMANY

Cat. No.	Wire Size	Wire Type	FW	TQ Lb In.	V	A	UG	CA
BK4	28-12	CU	2	5-7	600	25	C	2(105)
BK4-FS	28-12	CU	2	5-7	150	20	C	2(105)
BK4-FS/FS	N/A	CU	1	N/A	150	20	C	2(105)
BK10	26-8	CU	2	11-15	600	50	C	2(105)
BK16	26-6	CU	2	11-15	600	65	C	2(105)
BK25/E	22-4	CU	2	18-25	600	85	C	2(105)
BK35/E	18-2	CU	2	30-50	600	115	C	2(105)
UK10-DREHSI(1)	6-24	CU	2	11-20	300	20	C	2(105)
<b>Note:</b> (1) Followed by suffixes LA, LA/K, LED or LED/K, followed by 12, 24, 60, or 250, followed by (5x20), (5x25), (5x30), or (5.3x32), with or without suffixes -TE, -M, -W, -K, -DM								
ZFK10,ZFK110	16-6	CU	2	—	600,600	60	B,C	2(105),4
ZFKN10	16-6	CU	2	—	600,600	55	B,C	2(105),4
ZFK10PE,ZFK110PE	16-6	CU	2	—	—	60	B,C	2(105),4,6&
ZFK16,ZFK116,ZFKN16	14-4	CU	2	—	600,600	65	B,C	2(105),4
ZFK16PE,ZFK116PE	14-4	CU	2	—	—	65	B,C	2(105),4,6,18
ZFK35	12-2	CU	2	—	600	120	C	2(105),4
ZFK35-PE	12-2	CU	2	—	—	—	C	2(105),4
<b>Note:</b> (6,18) Protective conductor terminal block. Spacings to be evaluated in the end-use equipment								
UK10.3-HESI	8-24	CU	2	11-20	600	35	B,C	2(105)
UKH25,UHV25(1)	6-4	CU	2	40	600	85	B,C	2(105)
UKH50, UHV50,	6-1/0	CU	2	70	600	150	B,C	2
UKH50IB (1)								(105)
UKH95,UHV95(1)	2-4/0	CU	2	175	600	230	B,C	2(105)
UKH150	2-300	CU	2	270	600	285	B,C	2(105)
UHV150(1)	2-300	CU	2	270	600	285	B,C	2(105)
UKH240	2/0-500	CU	2	270	600	380	B,C	2(105)
UHV240(1)	500	CU	2	270	600	380	B,C	2(105)

AGK10-UKH	6-24	CU	2	11-20	600	65	B,C	2(105)	
<b>Note:</b> (1)Followed by suffixes -M8, -M10, -M12, -M16, -AS or KH, additionally followed by suffixed /M8, /M10, /M12, /M16, /AS, or /KH.									
FKDS,	16-22	CU	2	N/A	300	10	B,D	2	
FKDSA(1)(4)								(105)	
FKDSV, FKDSVA	16-22	CU	2	N/A	300	10	B,D	2	
(1)(2)(4)								(6)	(105)
FFKDS, FFKDSA	16-22	CU	2	N/A	300	10	B,D	2	
(2)(4)(5)								(6)	(105)
FFKDSA(2A)	16-22	CU	21	N/A	600	5(8)	B,D	2(105)	
FKDSP, FKDSPA1	16-22	CU	2	N/A	300	10	B,D	2	
(4)(7)								(105)	
MFKDSP(2)(3)	18-22	CU	2	N/A	300	3.6	B,D	2(105)	
MFKDS-5.08(4)	16-22	CU	2	N/A	300	10	B,D	2(105)	
MFKDSA-7.62(4)	16-22	CU	2	N/A	300	10	B,D	2(105)	
<b>Note:</b> (1)With or without suffix 1, followed by -5.08 or -7.62, may be followed by suffixes /SA and/or 5.08 or 10.16.									
<b>Note:</b> (2)With or without suffix 1, followed by suffix /H1, /H2, /V1 or /V2, followed by -5.08.									
<b>Note:</b> (2A)With or without 1, followed by /H1, /H2, /V1, /V2 followed by -7.62.									
<b>Note:</b> (3)Followed by /2, /3, /4, /6 or /7, followed by -5.80.									
<b>Note:</b> (4)Additional wire size of No. 12 AWG Sol.									
<b>Note:</b> (5)With or without 1, followed by /H or /V, followed by -2.54or -5.08.									
<b>Note:</b> (6)13.5 max., for factory-wiring.									
<b>Note:</b> (7)With or without suffix -MT, followed by -5.08 or -7.62.									
<b>Note:</b> (8) 10A max. 300V, 5A max. 600V, also 13A max. factory wiring at 150V.									
FFKDS(5)	20-26	CU	2	N/A	150	6	B,D	2(105),4	
FFKDS(6)	16-26	CU	2	N/A	300	6	B,C	2(105),4	
FFKDSA(6)	16-26	CU	2	NA	300	6	B,C	2(105),4	
FFKDSA(5)	20-26	CU	2	N/A	150	6	B,D	2(105),4	
UK3-RETURN	12-30	CU	2	5-7	300	20	B,D	2(105)	
UK5-RETURN	10-30	CU	2	5-7	300	30	B,D	2(105)	
UK10-RETURN	6-24	CU	2	11-20	300	65	B,D	2(105)	
UK3-RETURN-PE	12-30	CU	2	5-7	N/A	N/A	B,D	2(105)	
UK5-RETURN-PE	10-30	CU	2	5-7	N/A	N/A	B,D	2(105)	
UK10-RETURN-PE	6-24	CU	2	11-20	N/A	N/A	B,D	2(105)	
DFK4-Si(1)	30-10	CU	1	5-7	300	10	B,D	2(105)	
<b>Note:</b> (1)Followed by 5 X 20/25, 5 X 30 or 6.3 X 32.									
<b>Note:</b> (5)With or without suffix 1, followed by /H, or /V and -2.54, or -5.08.									
<b>Note:</b> (6) With or without 1, followed by /H, or /V and -3.81, or -6.35.									
SLKK5	10-26	CU	2	5-7	600	30	B,C	2(105)	
TT-SLKK5,	26-10/	CU	2	5-7	600	30	B,C	2(105)	

TT-SLKK5-S,									
f/b suffixes	26-12								
/12./24./48,									
/60./110 f/b									
suffix AC or DC									
GSTB3/3-ST-7.62	30-10	CU	2	5-7	300	10	B,D	2(105)	
GSTB3/3-G-7.62	N/A	CU	1	N/A	300	10	B,D	2(105)	
STB3/3-ST-5.08	30-10	CU	2	5-7	300	10	B,D	2(105)	
STB3/4-ST-5.08	30-10	CU	2	5-7	300	10	B,D	2(105)	
STB3/3-G-5.08	N/A	CU	1	N/A	300	10	B,D	2(105)	
STB3/4-G-5.08	N/A	CU	1	N/A	300	10	B,D	2(105)	
DIK1.5(1)	14-30	CU	2	5-7	300	15	B,D	2(105)	
DIKD1.5(1)	14-30	CU	2	5-7	300	15	B,D	2(105)	
DIKD1.5-PV(1)	14-30	CU	2	5-7	300	15	B,D	2(105)	
DOK1.5(1)	14-30	CU	2	5-7	300	15	B,D	2(105)	
DOK1.5(1)	14-30	CU	2	5-7	300	15	B,D	2(105)	
DOK1.5-2D(1)	14-30	CU	2	5-7	300	15	B,D	2(105)	
DOK1.5-TG	14-30	CU	2	5-7	300	15	B,D	2(105)	
DOKD1.5-TG	14-30	CU	2	5-7	300	15	B,D	2(105)	
DLK2.5-PE	14-30	CU	2	5-7	300	15	B,D	2(105)	
DLK4-PE	10-30	CU	2	5-7	600	30	B,D	2(105)	
DLKB2.5-PE	14-30	CU	2	5-7	300	15	B,D	2(105)	
<b>Note:</b> (1) May be followed by suffixes -LA, -LA12, -LA24, -LA48, -LA60, followed by RD or RT, -220, -24GN, -60GN, -220GN, with or without suffixes /O-M, /U-O, /O-MO, /MU-O.									
VIOK1.5(2)(1)	14-30	CU	2	5-7	300	15	B,D	2(105)	
VIOK1.5-2D(1)	14-30	CU	2	5-7	300	15	B,D	2(105)	
VIOK1.5-3D-PE(1)	14-30	CU	2	5-7	300	15	B,D	2(105)	
<b>Note:</b> (1) May be followed by suffixes -LA, -LA12, -LA24, -LA48, -LA60, followed by RD or RT, -220, -24GN, -60GN, -220GN, with or without suffixes /O-M, /U-O, /O-MO, /MU-O.									
GKDS,GKDS/E,LOE	30-14	CU	1	5-7	250	15	B,C,D	2(105)	
KDS	30-14	CU	2	5-7	250	15	B,C,D	2(105)	
KDS2.5(1)	30-12	CU	1	5-7	300	15	B,C,D	2(105)	
KDS3(2)	28-12	CU	2	5-7	300	15	B,C,D	2(105)	
KDS3(3)	28-12	CU	2	5-7	300	15	B,D	2(105)	
<b>Note:</b> (1) Followed by suffixes -LA12, -LA24, -LA48, -LA60, followed by RD or RT, -LA/EK.									
<b>Note:</b> (2) Followed by suffixes -MT, -PMT or -Si.									
<b>Note:</b> (3) Followed by suffixes -SILED12, -SILED24, -SILED60, -SILED250.									
GMKDS1.5 (1)	30-14	CU	2	5.0	300	10	B	2(105)	
GSMKDS1.5 (1)	30-14	CU	2	5.0	300	10	B	2(105)	
GSMKDSP1.5	30-14	CU	2	5.0	300	10	B	2(105)	
<b>Note:</b> (1) Followed by /1 or 2 digit number, with or without -7.62.									

HC-KA(1)	22-12	CU	2	5.0	300	15	B,C	2(105)
<b>Note:</b> (1) Followed by suffix number 6, 10, 16 or 24.								
MBK4(1)	26-10	CU	2	5-7	600	30	B,C	2(130)
<b>Note:</b> (1) With or without suffixes -PE, -2PE, -TK/2 or -TK/3.								
MSLKG2.5	28-12	CU	2	5-7	300	10	B,C	2(105)
MSLKG4	28-12	CU	2	5-7	N/A	N/A	B,C	2(105)
MSLKG5	26-10	CU	2	5-7	N/A	N/A	B,C	2(105)
MTK(1)	28-12	CU	2	5-7	300	10	B,D	2(105)
MTKD(2)	28-12	CU	2	5-7	300	10	B,D	2(105)
<b>Note:</b> (1) With or without suffixes -Loe/Loe, -Loel, -Loel/PR, -P/P, -D or -D-P/P.								
<b>Note:</b> (2) Followed by suffix -CU/CUNI, -FE/CUNI, -NICR/CUNI, -NICR/NI, -NICRSI/NISI, -E-CU/A-CU or -S-CU/E-CU.								
OTTA2.5	N/A	CU	1	11	600	20	B,C	2(105)
OTTA2.5-P/P	N/A	CU	1	11	600	20	B,C	2(105)
OTTA6	N/A	CU	1	20	600	30	B,C	2(105)
OTTA66-P/P	N/A	CU	1	20	600	30	B,C	2(130)
OTTA6-T	N/A	CU	1	20	600	30	B,C	2(105)
OTTA6-T-P/P	N/A	CU	1	20	600	30	B,C	2(105)
OTTA25-M5	N/A	CU	1	40	600	115	B,C	2(105)
OTTA250M6	N/A	CU	1	40	600	115	B,C	2(105)
OTTA2.5-PE	N/A	CU	1	11	600	20	B,C	2(105)
OTTA6-PE	N/A	CU	1	20	600	30	B,C	2(105)
UDKE3-PE	12-30	CU	2	5-7	N/A	N/A	B,C	2(105),4
UDK4-PE	10-30	CU	2	5-7	N/A	N/A	B,C	2(105)
USK4-FS/FS(1)	N/A	CU	1	N/A	600	20	B,C	2(105)
<b>Note:</b> (1) Followed by suffixes (6-2.8-0.8), (8-2.8-0.8), (4-2.8-0.8/2VR-2.8) or (4-2.8-0.8/3-2.8).								
U3K2.5(1)	30-12	CU	2	5-7	600	20	B,C	2(105)
<b>Note:</b> (1) With or without suffixes -LA12, -LA24, -LA48, -LA60 followed by RD or RT and /OM, or -LA220.								
USIGST-Si(1)	8-18	CU	2	20	600	40	C	2(105)
USIGST1-Si(1)	8-18	CU	2	20	600	40	C	2(105)
<b>Note:</b> (1) With suffixes ST-Si, or ST1-Si, with or without suffixes SILED 12, SILED 24, SILED 60, SILA 250, or SILA 5000.								
PIK4(2)	28-12	CU	2	5-7	300	20	B,C	2(105)
PIK4-PE(2)	28-12	CU	2	5-7	300	20	B,C	2(105)
PIK6 (1)	26-8	CU	2	5-7	300	50	B,C	2(105)
PIK6-PE (1)	26-8	CU	2	5-7	300	50	B,C	2(105)
UK-SI	28-12	CU	2	5-7	300	10	B,C	2(105)
Note: (1) With suffixes -L/L, -L/N, or -L/NT.								
Note: (2) With suffixes -L or /L, with or without suffixes /L, /N, /NT, /NTB.								
Note: (3) 25A max. factory-wiring only.								
GESK(1)	22-12	CU	2	5.0	600	7	B,C	2(105)

<b>Note:</b> (1) With or without suffixes -K, -K2, -ST, -ST2, may be followed by -F1 or -F2.								
DKBD(1)	30-14	CU	2	5-7	300	10	B,D	2(105)
<b>Note:</b> (1) Followed by /one or two digit number, by suffix -MT or MT2L, with or without suffix -5.08.								
TRKS10(1)	6-24	CU	1	11-20	300	65	B,C	2(105)
TRKSD10(1)	6-24	CU	1	11-20	600	65	B,D	2(105)
TRKSD10/3(1)	6-24	CU	1	11-20	600	65	B,D	2(105)
<b>Note:</b> (1)With suffix Gray or Orange.								
UK5-HESI(1)	26-10	CU	2	5-7	600	12	C	2(105)
<b>Note:</b> (1)With suffix -LED followed by 12, 24or 60, or -LA followed by 250 or 500.								
UKK3MSTBVH5.08.	30-12	CU	2	5-7	300	10	B,C,D	2(105)
UKK4-FS	10-30	CU	2	5-7	300	20	B,C	2(105)
VBST4-FS(6-2.0-8)ST4	10-30	CU	2	5-7	300	20	B,C	2(105)
UKK4-FS/FS	N/A	CU	1	N/A	300	20	B,C	2(105)
UVKB4-FS	28-12	CU	2	5-7	300	12	C	2(105)
UVKB4-FS/FS	N/A	CU	1	N/A	300	25	C	2(105)
UK3MSTBV5.08(1)	26-12	CU	2	5.0	300	20	B,D	2(105)
<b>Note:</b> (1)With or without suffixes -LA12, -LA24, -LA48, -LA60 followed by -RD or -RT.								
UK6.3-HESI(1)	26-8	CU	2	11-15	600	10	B,C	2(105)
<b>Note:</b> (1)With or without suffixes -LED followed by 12, 24or 60, or suffix -LA followed by 250 or 500.								
VIOK1.5(2)(1)	14-30	CU	—	5-7	300	15	B,D	2(105)
VIOK1.5-2D(1)	14-30	CU	—	5-7	300	15	B,D	2(105)
VIOK1.5-3D-PE(1)	14-30	CU	—	5-7	300	15	B,D	2(105)
USEN14	2-20	CU	—	35-40	600	16	B,C	2(105),4
USEN18	2-20	CU	—	35-40	600	63	B,C	2(105),4

(1)May be followed by suffixes -LA, -LA12, -LA24, -LA48, -LA60, followed by RD or RT, -220, -24GN, -60GN, -220GN, with or without suffixes /O-M, /U-O, /O-MO, /MU-O.

Cat. No.	Wire Range	Wire Type	FW	TQ Lb In.	V	A	UG	CA
MBK3/E-Z	28-12	CU	2	5-7	600	20	B,C	2(105)
MBK3/E-ZBU	28-12	CU	2	5-7	600	20	B,C	2(105)
MBK6/E	8-26	CU	2	11-15	600	50	B,C	2(105)
MBK5/E-Z,BU	26-10	CU	2	5-7	600	30	B,C	2(105),4
MBK5/E-Z-PE	26-14	CU	2	5-7	—	—	B,C	2(105),4
MSLKG6	8-26	CU	2	11-15	N/A	N/A	B,C	2(105)
UK1.5N	30-14	CU	2	4	300	15	B,C	2(105)
UK2.5N	12-30	CU	2	5-7	300	20	B,C	2(105)
UK2.5	14-30	CU	2	5-7	300	15	B,C	2(105)

UK3	12-28	CU	2	5-7	600	20	B,C	2(105)
UK4	12-28 (#)	CU	2	5-7	600	20	B,C	2(105)
UK5	10-26 (#)	CU	2	5-7	600	30	B,C	2(105)
UK10	8-26	CU	2	11-15	600	50	B,C	2(105)
UK16	6-24	CU	2	11-15	600	65	B,C	2(105)
UK3N	12-28	CU	2	5-7	600	20	B,C	2(105)
UK5N, UK5N CB	10-30 (#) (##)	CU	2	5-7	600	30	B,C	2(105)
UK6N	8-26(1)	CU	2	15	600	50	B,C	2(105)
UK6-FSI/C,-LED12, -LED24	26-8	CU	2	15	300	30	B,C	2 (105),4
UK10N	6-24	CU	2	11-20	600	65	B,C	2(105)
UK16N	4-22	CU	2	18-25	600	85	B,C	2(105)
UIK16	4-22	CU	2	18-25	600	85	B,C	2 (105),4
UIK35	2-18	CU	2	30-50	600	115(+)	B,C	2 (105),4
UK25	4-22	CU	2	18-25	600	85	B,C	2 (105),4
UK35	1/0-18	CU	2	30-50	1000	150	B,C	2(105)
UK35-PE/N	1/0-18	CU	2	30-50	600	150	B,C	2(105)
<b>Note:</b> (#) Additional wire combination rating of two No. 14AWG Cu stranded wires.								
<b>Note:</b> (##) Additional multiple wire rating of three No. 18 AWG Cu. stranded for field and factory-wiring.								
<b>Note:</b> (+) 130A max for factory-wiring only.								
<b>Note:</b> (1) Additional multiple wiring combination rating of two No. 12 AWG Cu. str. to 2 No. 18 AWG Cu. str. for field and factory-wiring, same size wires only.								
UHSK/S2000	26-8	CU	2	11-15	1000	50	—	2 (105),4
UKK5(2)	10-26	CU	2	5-7	600	30	B,C	2(105)
UKK5-PV	26-10	Cu	2	5-7	300	15	B,C	2 (105),4
UKKB5	10-26	CU	2	5-7	600	30	B,C	2(105)
UKK5-HESI(5x20)	26-10	CU	2	5-7	600	15(3)	B,C	2 (105),4
UKK5-HESI(6.3x32)	26-10	CU	2	5-7	600	15(3)	B,C	2 (105),4
UKK5-DIO/O-U	26-10	CU	2	5-7	600	30	B,C	2(105)
UKK5-DIO/U-O	26-10	CU	2	5-7	600	30	B,C	2(105)
UKK5-DIO/UL-UR	26-10	CU	2	5-7	600	30/1	B,C	2(105)
UKK5-2DIO/O-UL/UR-UL	26-10	CU	2	5-7	600	30/1	B,C	2(105)

UKK3	12-28 (3A)	CU	2	5-7	600	20	B,C	2(105)
UKKB3	12-28 (3A)	CU	2	5-7	600	20	B,C	2(105)
UKKB3-TP(2.4X0.8)L	24- 20/28- 12	CU	2/1	5-7	300	5	B,D	2 (105),4
UKKB3-TP(2.4X0.8)Q	24- 20/28- 12	CU	2/1	5-7	300	5	B	2 (105),4
UKKB10	6-24	CU	2	20	600	65	B,C	2(105)
UKKB10-2.5	6-24(1)	CU	2	20	600	65	B,C	2(105)
UKKB10-2.5PV	6-24(1)	CU	2	20	600	65	B,C	2(105)
<b>Note:</b> (1) Top level terminals are rated No. 12-30 AWG cu sol/str (field/factory-wiring), 20A, 600v, 7 lb.-in. torque.								
<b>Note:</b> (2)May be followed by suffixes -LA60RD/U-O, or LA230.								
<b>Note:</b> (3)Lower level terminals rated 30A max; fused upper level rated 15A max.								
<b>Note:</b> (3A) - (7) Additional multiple wire rating of two No. 16-28 AWG Cu. stranded for field and factory-wiring , same size wires only.								
USK4	12-28	CU	2	5-7	600	20	B,C	2(105)
USK10	8-26	CU	2	11- 15	600	50	B,C	2(105)
USK16	6-24	CU	2	11- 15	600	65	B,C	2(105)
USST6	14 max.	Cu	1	11- 15	600	15	B,C	2(105)
TT-UK5 w/suffixes/12,/24,/48,/60 and by AC or DC	26-10	CU	2	5-7	12-110	30	B,C	2(105), 4
URK-ND, -ND2	24-6	CU	2	11- 15	600	65	B,C	2 (105),4
SDKK6(4)	24-8	CU	2	15	600	26	B,C	2(105)
GMKDS3/2(2)	12-30	CU	2	5-7	300	15	B,D	2(105)
GMKDS3/3(2)	12-30	CU	2	5-7	300	15	B,D	2(105)
GMKDSP3/2(2)	12-30	CU	2	5-7	300	15	B,C	2(105)
GMKDSP3/3(2)	12-30	CU	2	5-7	300	15	B,C	2(105)
GSMKDS3/2(2)	12-30	CU	2	5-7	300	15	B,D	2(105)
GSMKDS3/3(2)	12-30	CU	2	5-7	300	15	B,D	2(105)
<b>Note:</b> (2)May be followed by -7.62.								
<b>Note:</b> (4)Followed by one or two digit number , with orwithout suffixes OBEN, UNTEN and/or NZ.								
MKDSF3/2(1)	12-30	CU	2	5-7	300	15	B,D	2(105)
MKDSF3/3(1)	12-30	CU	2	5-7	300	15	B,D	2(105)
MKDSF3/4(1)	12-30	CU	2	5-7	300	15	B,D	2(105)
MKDSF3/8(1)	12-30	CU	2	5-7	300	15	B,D	2(105)
MKDSF3/12(1)	12-30	CU	2	5-7	300	15	B,D	2(105)
MKDSF3/2-S01(1)	12-30	CU	2	5-7	300	10	B,D	2(105)
MKDSF3/3-S01(1)	12-30	CU	2	5-7	300	10	B,D	2(105)

MKDSF3/4-S01(1)	12-30	CU	2	5-7	300	10	B,D	2(105)
<b>Note:</b> (1)May be followed by -5.08.								
MKDSF3/8-S01(1)	12-30	CU	2	5-7	300	10	B,D	2(105)
MKDSF3/12-S01(1)	12-30	CU	2	5-7	300	10	B,D	2(105)
MKDSFW3/2	12-30	CU	2	5	300	15	B,D	2(105)
MKDSFW3/3	12-30	CU	2	5	300	15	B,D	2(105)
MKDSP3/2(1)	12-30	CU	2	5	300	15	B,D	2(105)
MKDSP3/3(1)	12-30	CU	2	5	300	15	B,D	2(105)
SMKDS1.5/2(3)	12-30	CU	2	5-7	300	10	B,D	2(105)
SMKDS1.5/3(3)	12-30	CU	2	5	300	10	B,D	2(105)
SMDKS2.5/2###	30-12	CU	2	5-7	300	10	B,D	2(105)
SMKDS2.5/3###	30-12	CU	2	5-7	300	10	B,D	2(105)
<b>Note:</b> (1)May be followed by -5.08.								
<b>Note:</b> (3)May be followed by -5.08, -6.35 or -9.5.								
SMKDS3/2(3)	12-30	CU	2	5-7	300	15	B,D	2(105)
SMKDS3/3(3)	12-30	CU	2	5-7	300	15	B,D	2(105)
SMKDS5/2(3)	10-30	CU	2	5-7	300	30	B,C	2(105)
SMKDS5/3(3)	10-30	CU	2	5-7	300	30	B,C	2(105)
SMKDSP1.5(3)	14-30	CU	2	5.0	300	15	B,C	2(105)
SMKDSFU2.5/X-5.08	12-30	CU	2	5-7	300	10	B,D	2(105)
UK5-MTK-P/P	22-12	CU	2	5	600	15	B,C	2(105)
DFLK-D(1) Sub/B	12-30	CU	2	5-7	125	2.5	B	2(105)
DFLK-D(1) Sub/S	12-30	CU	2	5-7	125	2.5	B	2(105)
<b>Note:</b> (1)Followed by one or two-digit number.								
<b>Note:</b> (3)May be followed by -5.08, -6.35 or -9.5.								
UDK4-MTK	30-10	CU	2	5-7	600	15	B,C	2(105)
UDK4-MTK-P/P	30-10	CU	2	5-7	600	15	B,C	2(105)
UKK5-MTK-P/P	26-12	CU	2	5-7	300	15	B,C	2(105)
UKK5-MTK-P/P-LA,-MTKD(++)	26-12	CU	2	5-7	300	15	B,C	2(105)
UKK5-T	26-12	CU	2	5-7	300	15/25	B,C	2(105)
UKK5-TG	26-12	CU	2	5-7	300	15/25	B,C	2(105)
URELG(1)PMTK, -RD	30-12	CU	2	5-7	300	10	B,C	2(105)
TT-UKK5-TBE	26-12	CU	2	5-7	300	15	B,C	2(105)
<b>Note:</b> (1) Followed by 2, 3, 4, or 7.								
<b>Note:</b> (++) May be followed by 24, 48 or 60, may be followed by RT/O-U.								
UDMTK5-TWIN-P/P	26-12	CU	2	5-7	300	8	B,C	2(105)
UDK-RELG	30-12	CU	2	5-7	300	20	B,C	2(105),4
UDK4-TG	30-12	CU	2	5-7	300	15	B,C	2(105),4
DFK4-PE	30-10	CU	2	5-7	N/A	N/A	B,D	2



								(105),4
DFK4	10-30	CU	2	5-7	300	15	B,D	2 (105),4
DFK/DB4	10-30	CU	2	5-7	300	15	B,D	2 (105),4
DFK-WW(1x1)	28-12	CU	2	5-7	300	10	B,D	2 (105),4
DFK-TP(1.6x0.8)	28-12	CU	2	5-7	300	10	B,D	2 (105),4
DFK-TP(2.4x0.8)	28-12	CU	2	5-7	300	10	B,D	2 (105),4
DFK-2.8	28-12	CU	2	5-7	300	15	B,D	2 (105),4
DFK/DP-2.8	28-12	CU	2	5-7	300	15	B,D	2 (105),4
DFK-2.8	28-12	CU	2	5-7	300	15	B,D	2(105),
FRONT 2.5								4
DFK/DP-2.8	28-12	CU	2	5-7	300	15	B,D	2(105),
FRONT 2.5								4
TRK1.5,-N,-S,-S01,	22-14	CU	2	7	300	15	B,C	2(105)
TRK1.5-S02,-FS,								
TRK1.5-Blau So1								
TRK2.5,TRK2.5-FS	22-12	CU	2	7	600	20	B,C	2(105)
TRK2.5N,-GY,-FS-GY,	22-12	CU	2	7	600	20	B,C	2(105)
TRK2.5N-OG,-FS-OG,								
TRK2.5BU SO1								
TRK4,-FS,-Blau So1	16-10	CU	2	11	600	30	B,C	2(105)
TRKS4,TRKS4-FS	30-10	CU	2	5-7	600	30	B,C	2(105)
TRKS4-Si	30-10	CU	2	5-7	600	8	B,C	2(105)
TRKS4-Si/K	30-10	CU	2	5-7	600	8	B,C	2(105)
TRK1.5/2(1)	22-14	CU	2	7	300	15	B,C	2(105)
TRK1.5/3(1)	22-14	CU	2	7	300	15	B,C	2(105)
<b>Note:</b> (1) With or without suffixes -N, -FS, -N-FS followed by OG.								
TRKS4/1-Si(6.3x32), (5x30)	30-10	CU	2	5-7	600	10	B,C	2(105)
TRKS4/3GY,OR	30-10	CU	2	5-7	600	30	B,C	2(105)
TRK10	10-6	CU	2	11	600	55	B,C	2(105)
TRK10 Blau Sol	10-6	CU	2	11	600	55	B,C	2(105)
VTRK(Z)4, -GY, -OG	30-10	CU	2	5-7	300	30	B,C	2(105)
VTRK(Z)4-SI/C,-GY, -OG	30-10	CU	2	5-7	300	10	B,C	2(105)
TRK2.5-Si	22-12	CU	2	7	300	8	B,C	2(105)
TRKSD4,-FS	30-10	CU	2	5-7	600	30	B,C	2(105)
ZTRK4	24-10	CU	2	N/A	600	30	B,C	2(105)
ZTRK4-SI	24-16	CU	2	N/A	300	10	B,C	2 (105),4

USLKG2.5, -1	30-12	CU	2	5-7	N/A	N/A	B,C	2 (105),4
USLKG1.5N	30-14	CU	2	5-7	N/A	N/A	B,C	2 (105),4
USLKG2.5N	30-12	CU	2	5-7	N/A	N/A	B,C	2 (105),4
USLKG3, -1	28-12	CU	2	5-7	N/A	N/A	B,C	2 (105),4
USLKG4, -1	26-12	CU	2	5-7	N/A	N/A	B,C	2 (105),4
USLKG5, -1,	26-10	CU	2	5-7	N/A	N/A	B,C	2 (105),4
USLKG6N	26-8	CU	2	11-15	N/A	N/A	B,C	2 (105),4
USLKG10, -1	26-8	CU	2	11-15	N/A	N/A	B,C	2 (105),4
USLKG10N, -1	24-6	CU	2	11-20	N/A	N/A	B,C	2 (105),4
USLKG16, -1	24-6	CU	2	11-15	N/A	N/A	B,C	2 (105),4
USLKG35, -1	18-1/0	CU	2	30-50	N/A	N/A	B,C	2 (105),4
USLKG50, USLKG50IB	1/0-6	CU	2	70	N/A	N/A	B,C	2 (105),4
USLKG95	2-4/0	CU	2	200	N/A	N/A	B,C	2 (105),4
UISLKG16	22-4	CU	2	18-25	N/A	N/A	B,C	2 (105),4
USLKG16N, -1	22-4	CU	2	18-25	N/A	N/A	B,C	2 (105),4
UKK5-PE	26-10	CU	2	5-7	N/A	N/A	B,C	2 (105),4
UKKB5-PE	26-10	CU	2	5-7	N/A	N/A	B,C	2 (105),4
UK10-PE/N	26-8	CU	2	11-15	N/A	N/A	B,C	2 (105),4
UK16-PE/N	24-6	CU	2	11-15	N/A	N/A	B,C	2 (105),4
FAA40,FAA40/20	12-28	CU	2	5-7	300	10	B,	2 (105),4
MC1.5/X-ST(1), -ST1(1)	14-30	CU	2	2-4	300	8	B,D	2(105)
MC1.5/X-STF(1), -STF1(1)	14-30	CU	2	2-4	300	8	B,D	2(105)
MC1.5/X-STZ, -STZF(1)	14-30	CU	2	2-4	300	8	B,D	2(105)
MCVR1.5/X-ST, -STF(1)	14-30	CU	2	4	300	8	B,D	2(105)
MCVR1.5/X-STFL(1)	14-30CU	CU	2	4	300	8	B,D	2(105)
MCVR1.5/X-STFR(1)	14-30	CU	2	4	300	8	B,D	2(105)
MCVW1.5/X-ST(1)	14-30	CU	2	4	300	8	B,D	2(105)
MCVW1.5/X-STF(1)	14-30	CU	2	4	300	8	B,D	2(105)
MCVW1.5/X-STFL(1)	14-30	CU	2	4	300	8	B,D	2(105)

MCVW1.5/X-STFR(1)	14-30	CU	2	4	300	8	B,D	2(105)
IMC1.5/X-ST(1)	14-30	CU	2	4	300	8	B,D	2(105)
IMC1.5/X-SRF(1)	14-30	CU	2	4	300	8	B,D	2(105)
<b>Note:</b> (1) Followed by suffix -3.5, -3.81 or -5.08.								
FRONT-MC1.5/X-ST(1)	16-30	CU	2	4	300	8	B,D	2(105)
FRONT-MC1.5/X-STF(1)	16-30	CU	2	4	300	8	B,D	2(105)
MCV1.5/X-G-3.81-SMD	—	CU	1	—	300	8	B,D	2(105)
MCV1.5/X(2)(1), -THT	—	CU	1	—	300	8	B,D	2(105)
DFX1.5/X(2)(1)	—	CU	1	—	300	8	B,D	2(105)
MCDVU1.5/X(2)(1)	—	CU	1	—	300	8	B,D	2(105)
SMC1.5/X(2)(1)	—	CU	1	—	300	8	B,D	2(105)
MC1.5/X(2)(1), -THT	—	CU	1	—	300	8	B,D	2(105)
MCD1.5/X(2)(1)	—	CU	1	—	300	8	B,D	2(105)
MCDV1.5/X(2)(1)	—	CU	1	—	300	8	B,D	2(105)
IMC1.5/X-G-3.81	—	CU	1	—	300	8	B,D	2(105)
IMCV1.5/X-G-3.81	—	CU	1	—	300	8	B,D	2(105)
MCO1.5/X-GL,-GR-3.81	—	CU	1	—	300	8	B,D	2(105)
MCVU1.5/X(2)(1)	—	CU	1	—	300	8	B,D	2(105)
MCVK1.5/X(2)(1)	—	CU	1	—	300	8	B,D	2(105)
EMC1.5/X-G, -GF-3.5	—	CU	1	—	300	8	B,D	2 (105)
EMC1.5/X-G, -GF-3.81	—	CU	1	—	300	8	B,D	2 (105)
EMCV1.5-G, -GF-3.5	—	CU	1	—	300	8	B,D	2 (105)
EMCV1.5-G, -GF-3.81	—	CU	1	—	300	8	B,D	2 (105)
MCC1/.X-ST-3.81	(3)	CU	1	N/A	300	(4)	B,D	2 (105)
MCC1/X-STF-3.81	(3)	CU	1	N/A	300	(4)	B,D	2 (105)
MCC1/X-STZ-3.81	(3)	CU	1	N/A	300	(4)	B,D	2 (105)
MCC1/X-STZF-3.81	(3)	CU	1	N/A	300	(4)	B,D	2 (105)
<b>Note:</b> (1) Followed by suffix -3.5, -3.81 or -5.08.								
<b>Note:</b> (2) Followed by suffix -G, -G1, -GF, -G1F, -GFD, -G0, GW, or G1W, THR.								
<b>Note:</b> (3) No. 24-22 AWG Cu, stranded with MCC-MT0.25-0.5 crimp contact; No. 20-18 AWG Cu, stranded with MCC-MT0/.5-1 crimp contact.								
<b>Note:</b> (4) 5A max. with MCC-MT0.25-0.5 crimp contact; 8A max. with MCC-MT0.5-1 crimp contact.								
PSC1.5(/3 or /5)-F	16-30	CU	2	4	300	8	B,D	2(105)
PSC1.5(/3 or /5)-M,-PE	14-30	CU	1	—	300	8	B,D	2(105)
FK-MCP1.5/X-ST, -STF or -STZW (1)	16-28	CU	2	—	300	8	B,D	2(105)
MCVU1.5/X-GFD	14-30	CU	2	4	300	8	B,D	2(105)
MCVK1.5/X-GFD	14-30	CU	2	4	300	8	B,D	2(105)
FMC1.5/X-ST, or -STF,	24-16	CU	2	—	150	8	B,D	2(105)
f/b -3.5, w/wo -RF								
MCDN1.5/X, MCDNV1.5/X,	—	CU	1	—	150	8	B,D	2(105)

f/b G1 and -3.5 and P14THR,								
P26THR, RNP14THR, or RNP26THR								
DFK5-9.5#(3)	30-10	CU	2	5-7	300	30	B,C	2(105)
DMKDS2.5	30-14	CU	2	5-7	300	10	B,D	2(105)
DMKDS-FS, -FSI	—	CU	1	—	300	10	B,D	2(105)
<b>Note:</b> (1) Followed by suffix -3.5, -3.81 or -5.08.								
FL#(4)	—	—	1	—	300	10	B,D	2(105)
KDS4#(3)	30-10	CU	2	5-7	300	30	B,D	2(105)
KDSP1.5/X(3)	30-14	CU	2	5-7	300	15	B,D	2(105)
KDSP4/X(3)	30-10	CU	2	5-7	300	30	B,D	2(105)
MKDS1#(3)	30-16	CU	2	2.5	300	10	B,D	2(105)
MKDS1.5/X#(3), -5.08	30-12	CU	2	5	300	15	B,D	2(105)
MK3DS1/X-3.81 (14)	30-16	CU	2	4	300	10	B,D	2(105)
MKDS3/X	30-12	CU	2	5-7	300	15	B,D	2(105)
MKDSA3/X#(3)	30-12	CU	2	5-7	300	#(6)	B,D	2(105)
MKDS3/X-B5.08, -BK, -BU, -GNYE	30-12	CU	2	5-7	300	#(6)	B,D	2(105)
MKDS5/X#(3)	30-10	CU	2	5-7	300	30	B,C	2(105)
MKDS5 (8A)								
MKDSV5 (8A)	30-10	CU	2	5-7	300	30	B,C	2 (105),4
MKDS5HV (8A)	30-10	CU	2	5-7	300 (10)	30	B,C	2 (105),4
MKDSV5HV (8A)	30-10	CU	2	5-7	300	30	B,C	2 (105),4
MKDS5 (9A)	30-10	CU	2	5-7	600	30	B,C	2 (105),4
MKDSV5 (9A)	30-10	CU	2	5-7	600	30	B,C	2 (105),4
MKDS5HV (9A)	30-10	CU	2	5-7	600	30	B,C	2 (105),4
MKDSV5HV (9A)	30-10	CU	2	5-7	600	30	B,C	2 (105),4
MKDSO5/3(4)	30-10	CU	2	5-7	300	30	B,C	2(105)
MKDSO2.5/X-L,-R	30-12	CU	2	5-7	300	10	B,C	2(105)
SMKDSNF1.5X(5)(6)	30-14	CU	2	4.5	300	10	B,C	2(105)
MKDS5/2-7.62, MKDS5/3-7.62,	30-10	CU	2	5-7	300	30	B,D	2(105)
MKDS5/2-7.62#								
MKDS5/3-7.62#								
MKDSN1.5(6), MKDSNB1.5#(3)	30-14	CU	2	4.5	300	10	B,D	2(105)
MKDSN2.5(3)	30-12	CU	2	5-7	300	10	B,D	2(105)
MKDS1.5/2,/3N-5.08	30-14	CU	2	5-7	300	10	B,D	2(105)
MKDSFW1.5(3)#	30-12	CU	2	2.5	300	10	B,D	2(105)
MK3DSN1.5/X#(6) (14)	30-14	CU	2	4.5	300	10	B,D	2(105)

MK3DSNMH/X#	30-14	CU	2	4.5	300	10	B,D	2(105)
GMKDSN1.5/X##	30-14	CU	2	4.5	300	10	B,D	2(105)
<b>Note:</b> (3) Followed by /one or two digit number.								
<b>Note:</b> (4) Followed by -L or -R and 6.35, with or without -BK.								
<b>Note:</b> (5) Followed by 5.08, with or without BK.								
<b>Note:</b> (6) Also covered for multiple wire combination of two No. 18 AWG Cu. str. for field or factory-wiring.								
<b>Note:</b> (14) Multiple wire combination of three No. 26, 24, or No. 22 AWG Cu stranded wires for field and factory-wiring.								
<b>Note:</b> (#) May be followed by suffixes -3.5, -3.81, -5.08, -6.35, -7.62, may be followed by Suffix -HT and/or -PIN 1.65.								
<b>Note:</b> (8A) Followed by suffixes /2 or /3 and -9.5 or -9.52.								
<b>Note:</b> (9A) Followed by suffixes /2 or /3 and -9.5 or -9.52 and by Suffix Z.								
GSMKDSN1.5/X##	30-14	CU	2	4.5	300	10	B,D	2(105)
MKKDS1#(3)	30-16	CU	2	2.5	300	10	B,D	2(105)
SMKDS1#(3) (7)	30-16	CU	2	2.5	300	10	B,D	2(105)
SMKDS1.5(/2, /3)-3.05,	30-16	CU	2	2.5	300	10	B,D	2 (105),4
SMKDSV1.5(/2, /3)-3.05								
MKDSP1.5#(3), -5.08	30-12	CU	2	5	300	10	B,D	2(105)
MKDSP2.5#(3)	30-12	CU	2	5-7	300	10	B,D	2(105)
MKDSP10/2-10.16	20-6	CU	2	15	300	57	B,C	2(105)
MKDSP10/3-10.16	20-6	CU	2	15	300	57	B,C	2(105)
MKDSP10HV/1 or /2-digit number, -10.16	20-6	CU	2	15	300	57	B,D	2 (105),4
MKDSP10HV/1 or /2-digit number, -12.7	20-6	CU	2	15	600	57	B,D	2 (105),4
MKDS10HV/1 or 2-digit number, -ZB, or -ZF, -10.16	20-6	CU	2	15	600	57	B,D	2 (105),4
EMKDSP2.5#(3)	30-12	CU	2	5-7	300	10	B,D	2(105)
EMKDS1.5(3)#	30-14	CU	2	2.5	300	10	B,D	2(105)
MKDSD1.5/X(3)#	30-14	CU	2	2.5	300	10	B,D	2(105)
MKDSD2.5#(3)	30-12	CU	2	5-7	300	20	B,D	2(105)
MKDSFW1.5/X#(3)	30-14	CU	2	5	300	10	B,D	2(105)
MKDSW3/X#(3)	30-12	CU	2	5-7	300	#(6)	B,D	2(105)
MKKDS5/X#(3)	30-10	CU	2	5-7	600	30	B,C	2(105)
MKKDSN1.5#(3)(6)	30-14	CU	2	4.5	300	10	B,D	2(105)
MKKDSN1.5/X(3)H1L	30-14	CU	2	4.5	300	10	B,D	2(105)
MKKDSNH1.5(3)(4)(6)	30-14	CU	2	4.5	300	10	B,D	2(105)
MK3DSNMH1.5#(3)(6)	30-14	CU	2	4.5	300	10	B,D	2(105)
MKDSP25X-15.00, -F	20-10,	CU	2	22,	600	125	B,C	2 (105),4
-FL, -FR	8-2			40				
<b>Note:</b> (3) Followed by /one or two digit number.								

<b>Note:</b> (#) May be followed by suffixes -3.5, -3.81, -5.08, -6.35, -7.62, may be followed by Suffix -HT and/or -PIN 1.65.								
<b>Note:</b> (6) Also covered for multiple wire combination of two No. 18 AWG Cu. str. for field or factory-wiring.								
<b>Note:</b> (7) May be followed by suffix BK, HT, VO.								
SMKDSN1.5#(3)(6)	30-14	CU	2	4.5	300	10	B,D	2(105)
UEGM22.5,25,40/1,40/2	30-12	CU	2	5-7	300	10	B,D	2(105)
UEGH(8)	30-12	CU	2	5-7	300	10	B,D	2(105)
MPT0.5/X#-2.54	30-20	CU	2	1.0	125	6	B	2(105)
VDFK4(7)	30-10	CU	2	5-7	300	30	B,D	2(105)
VDFK6(7)	8-26	CU	2	15	300 (10)	50	B,D	2(105)
HK4-FS,-FS/FS#(1)	12-28	CU	2	—	250	25	B,C	2(130)
K4/E, SSK/N0525,UK4#(2)	12-28	CU	2	—	250	25	B,C	2(130)
<b>Note:</b> "X" in Cat. No. denotes 1 or 2 digit number.								
<b>Note:</b> ++ May be followed by suffixes 24, 48 or 60, and/or RT/O-U.								
<b>Note:</b> (7) With or without suffix /K and/or -DP, -GYNE, or WH.								
<b>Note:</b> (8) Followed by suffixes 22.5, 25, 27.5, 40, 42.5, or 45 with or without /1, or /2, and/or SMD.								
PCVK4-7.62(3)	30-10	Cu	2	5-7	600	30	B,C	2 (105),4
UPCV3K4-G-7.62	30-10	Cu	2	5-7	300	30	B,C	2 (105),4
PCC4/X-ST-7.62(A)	20-18,	Cu	1	—	600	10	B,C	2 (105),4
	16-14							
PC4/X(-G, -GF, -GU)-7.62	—	—	1	—	300	30	B,C	2 (105),4
DFK-PC4/X-G-7.62-LOE,or-FS4.8	—	—	1	—	300	30	B,C	2 (105),4
DFK-PC4/X-GF-7.62	—	—	1	—	300	30	B,C	2 (105),4
PCV4/X(-G, -GF, -GU)-7.62	—	—	1	—	300	30	B,C	2 (105),4
PC4 w/wo HV, f/b /X(1)-7.62, w/wo suffix RAE	30-10	CU	2	5-7	600	30	B,C	2 (105),4
PC4 w/wo HV, f/b /X(1)-15.24-1	30-10	CU	2	5-7	600	30	B,C	2 (105),4
PC4 w/wo HV, f/b /X(1)-15.24-2	30-10	CU	2	5-7	600	30	B,C	2 (105),4
<b>Note:</b> (A) 2 Crimp barrel sizes.								
<b>Note:</b> (1) Followed by -ST, -STF, -STF, -SH, -STFL or -STFR.								
<b>Note:</b> (2) May be used at 600V where printed circuit board is conformal coated or equivalent to provide acceptable spacings at the solder pins.								
<b>Note:</b> (3) Multiple wire rating for field and factory-wiring of 3 No. AWG Cu. stranded wires.								
<b>Note:</b> Suffix "X" in the Cat. Nos. above represent a one or two-digit number.								
PC4/X-G-15.24-1	—	—	1	—	600	30	B,C	2 (105),4
PC4/X-G-15.24-2	—	—	1	—	600	30	B,C	2 (105),4

PCV4/X-G-15.24-1	—	—	1	—	600	30	B,C	2 (105),4
PCV4/X-G-15.24-2	—	—	1	—	600	30	B,C	2 (105),4
PC5/X w/Suffixes -ST, -STF, foll. by -7.62, w/wo -SH	24-10	CU	2	7	600	30	B,C	1 (105).4
<b>Note:</b> Suffix "X" in the Cat. Nos. above represent a one or two-digit number.								
AK4, AKG4	12-22	CU	2	7	300	20	B,C	2 (105),4
AKG16	6-18	CU	2	25	300	50(1)	B,C	2 (105),4
AKG35	2-18	CU	2	50	300	115	B,C	2 (105),4
<b>Note:</b> (1) For factory-wiring, AKG16 is suitable for 65A max.								
<b>Note:</b> AKG4, -16, -35 are followed by suffix Black, Blue or Green/Yellow.								
HDFK25(1,2), HDFKV25(1,2)	2-8	CU	2	35	600	115	B,C	2 (105),4
HDFK50(1)(3), HDFKV50(1)(3)	1/0-6	CU	2	75	600	150	B,C	2 (105),4
<b>Note:</b> (1) - With or without one or more suffixes -DP, -F, -GNYE (Green/Yellow), -PE and/or -VP.								
<b>Note:</b> (2) One No. 2-8 AWG Cu. str. with one No. 14AWG Cu. str. for field and factory-wiring.								
<b>Note:</b> (3) One No. 2 AWG Cu. str. with one No. 8-12 AWG Cu. str. for field and factory-wiring.								
HDFK95(1), HDFKV95(1)	4/0-4	CU	2	175	600	230	B,C	2 (105),4
<b>Note:</b> (1) - With or without one or more suffixes -DP, -F, -GNYE (Green/Yellow), -PE and/or -VP.								
HDFK4(1), HDFKV4(1)	10-30	CU	2	5-7	300	30	B,D	2 (105),4
HDFK10(1), HDFKV10(1)	6-24	CU	2	11-20	300	65	B,D	2 (105),4
HDFK10HV	24-6	CU	2	11-20	600	65	B,C	2(105)
HDFK10-VP-HV	24-6	CU	2	11-20	600	65	B,C	2 (105),4
HDFKV10-VP-HV	24-6	CU	2	11-20	600	65	B,C	2 (105),4
HDFK16, -GNYE(1)	4-20	CU	2	18	600	85	B,C	2 (105),4
HDFKV16, -GNYE(1)	4-20	CU	2	18	600	85	B,C	2 (105),4
<b>Note:</b> (1) - May be followed by suffixes -GNYE (Green/Yellow) -TWIN, -TWIN-DP, and/or -VP.								
DFK-MSTB(1)(4)	—	CU	1	N/A	300	15	B,D	2(105)
DFK-MSTB(1)(2)	—	CU	1	N/A	600	15	B,D	2(105)
DFK-MSTBA(1)(4)	—	CU	1	N/A	300	15	B,D	2 (105),4
DFK-MSTBA(1)(4)	—	CU	1	N/A	300	15	B,D	2 (105),4
FRONT-MSTB(1)(5)	30-12	CU	2	5-7	300	15	B,D	2 (105),4

FRONT-MSTB(1)(3)	30-12	CU	2	5-7	600	15	B,D	2 (105),4
<b>Note:</b> (1)Suffixes 2.5, followed by /one or two-digit number.								
<b>Note:</b> (2)Suffixes -G or -GF, w/wo WW1X1, followed by -5.08, -10.16-1, or -10.16-2.								
<b>Note:</b> (3)Suffixes -ST or -STF, followed by -5.08, -10.16-1, or -10.16-2, w/wo -AU, -BK and/or -ABGY, HT BK.								
<b>Note:</b> (4)Suffixes -G or -GF, w/wo WW1X1, followed by -5.08.								
<b>Note:</b> (5)Suffixes -ST or -STF followed by -5.08 w/wo -AU, -BK and/or -ABGX.								
MDSTB(1)(4)	—	CU	1	N/A	600	15	B,D	2(105)
MDSTB(1)(2)	—	CU	1	N/A	300	15	B,D	2(105)
MDSTBA(1)(4)	—	CU	1	N/A	600	15	B,D	2(105)
MDSTBA(1)(2)	—	CU	1	N/A	300	15	B,D	2(105)
MDSTBV(1)(4)	—	CU	1	N/A	600	15	B,D	2(105)
MDSTBV(1)(2)	—	CU	1	N/A	300	15	B,D	2(105)
MDSTBVA(1)(2)	—	CU	1	N/A	300	15	B,D	2(105)
MDSTBVA(1)(4)	—	CU	1	N/A	300	15	B,D	2(105)
MDSTBVH(1)(4)	—	CU	1	N/A	600	15	B,D	2(105)
MDSTBVH(1)(2)	—	CU	1	N/A	300	15	B,D	2(105)
MDSTBVHA(1)(4)	—	CU	1	N/A	600	15	B,D	2(105)
MDSTBVHA(1)(2)	—	CU	1	N/A	300	15	B,D	2(105)
MDSTBW(1)(4)	—	CU	1	N/A	600	15	B,D	2(105)
MDSTBW(1)(2)	—	CU	1	N/A	300	15	B,D	2(105)
MSTB(1)(5)	30-12	CU	2	5-7	600	15	B,D	2 (105),4
MSTB(1)(3)	30-12	CU	2	5-7	300	15	B,D	2(105)
MSTB(1B)(3)	30-12	CU	2	5.7	300	16	B,D	2(105), 4
MSTBP(1)(1B)(5)	30-12	CU	2	5-7	600	15	B,D	2 (105),4
MSTBP(1)(1B)(3)	30-12	CU	2	5-7	300	15	B,D	2(105)
MSTBT(1)(1B)(5)	30-12	CU	2	5-7	600	15	B,D	2 (105),4
MSTBT(1)(1B)(3)	30-12	CU	2	5-7	300	15	B,D	2(105)
MSTB (1)(8)	28-12	CU	2	5-7	600	15	B,D	2 (105),4
MSTB(1)(1A)(6)	—	CU	1	N/A	600	16	B,D	2(105)
MSTB(1)(1A)(7)	—	CU	1	N/A	300	16	B,D	2(105)
MSTBA(1)(1A)(6)	—	CU	1	N/A	600	16	B,D	2(105)
MSTBA(1)(1A)(7)	—	CU	1	N/A	300	16	B,D	2(105)
<b>Note:</b> (1)Suffixes 2.5, followed by /one or two-digit number.								
<b>Note:</b> (1A)With or without suffixes HC and/or L.								
<b>Note:</b> (1B) Suffixes 2.5, followed by HC, followed by / one or two digit number								
<b>Note:</b> (2) Suffixes -G, -GF, -GFL, -GFR, -GL, -GR or -G2, w/wo -HT, followed by -5.08								
<b>Note:</b> (3) Suffixes -ST, -STF or -STZ followed by -5.08 w/wo -AB, -AU, PF and/or SO								



<b>Note:</b> (4) Suffixes -G, -GF, -GL, -GR, -GFL, -GFR or -G1, w/wo -HT, followed by -10.16-1, or -10.16-2								
<b>Note:</b> (5) Suffixes -ST, -STF or -STZ, followed by -5.08, -10.16-1 or -10.6.2 w/wo -AB, -AU, PF and/or SO								
<b>Note:</b> (6) Suffixes -G, -G0.5, -GF or -GEH, followed by -10.16-1 or -10.16-2, w/wo -THT, -LA, -LAB/RD, -KM, -H, -R, -AU, -BK, -ABGY, -A.45, -6.03								
<b>Note:</b> (7) Suffixes -G, -G0.5, -GF or -GEH, followed by -5.08, w/wo -THT, -LA, LAB/RD, -KM, -H, -R, -RN, -AU, -BK, -ABGY, -A.45, -6.03.								
<b>Note:</b> (8) Followed by suffix -ST-5.08, and by BGH1L SO1.								
MSTBAG(1)(1A)(6)	—	CU	1	N/A	600	16	B,D	2(105)
MSTBAG(1)(1A)(2)	—	CU	1	N/A	300	16	B,D	2(105)
MSTBV(1)(1A)(6)	—	CU	1	N/A	600	16	B,D	2(105)
MSTBV(1)(1A)(2)	—	CU	1	N/A	300	16	B,D	2(105)
MSTBVW(1)(2)	—	CU	2	—	300	16	B,D	2(105)
MSTBVA(1)(1A)(6), -THT	—	CU	1	N/A	600	16	B,D	2(105)
MSTBVA(1)(1A)(2)	—	CU	1	N/A	300	16	B,D	2(105)
A-MSTBV(1)(1A)(6)	—	CU	1	N/A	600	16	B,D	2(105)
A-MSTBV(1)(1A)(2)	—	CU	1	N/A	300	16	B,D	2(105)
A-MSTBVA(1)(1A)(6)	—	CU	1	N/A	600	16	B,D	2(105)
A-MSTBVA(1)(1A)(2)	—	CU	1	N/A	300	16	B,D	2(105)
EMSTBVA(1)-G-5.08	—	CU	1	N/A	300	15	B,D	2(105)
MSTBVAG(1)(1A)(6)	—	CU	1	N/A	600	16	B,D	2(105)
MSTBVAG(1)(1A)(2)	—	CU	1	N/A	300	16	B,D	2(105)
MSTBW(1)(1A)(6)	—	CU	1	N/A	600	16	B,D	2(105)
MSTBW(1)(1A)(2)	—	CU	1	N/A	300	16	B,D	2(105)
MVSTBN(1)(1B)(7)	30-12	CU	2	5-7	600	15	B,D	2(105),4
MVSTBN(1)(1B)(8)	30-12	CU	2	5-7	300	15	B,D	2(105)
MVSTBR(1)(7)	30-12	CU	2	5-7	600	15	B,D	2(105),4
MVSTBR(1)(8)	30-12	CU	2	5-7	300	15	B,D	2(105)
MVSTBW(1)(7)	30-12	CU	2	5-7	600	15	B,D	2(105),4
MVSTBW(1)(8)	30-12	CU	2	5-7	300	15	B,D	
MVSTBR(1B)(8)	30-12	CU	2	5.7	300	16	B,D	2(105),4
MVSTBW(1B)(8)	30-12	CU	2	5.7	300	16	B,D	2(105),4
<b>Note:</b> (1)-Suffixes 2.5, followed by /one or two-digit number.								
<b>Note:</b> (1A) With or without suffixes HC and/or L.								
<b>Note:</b> (1B) Suffixes 2.5, followed by HC, followed by / one or two digit number.								
<b>Note:</b> (2) Suffixes -G, -GB, -G0.5, -GF or -GEH, followed by -5.08, w/wo -THT, -LA, -LAB/RD, -KM, -H, -R, -RF, -RN, -AU, -BK, -ABGY, -4.45, -6.03								
<b>Note:</b> (6) Suffixes -G, -G0.5, -GF or -GEH, followed by -10.16.1, -10.16-2, w/wo -THT, -LA, -LAB/RD, -KM, -H, -R, -AU, -BK, -ABGY, -4.45, -6.03.								
<b>Note:</b> (7) Suffixes -ST or -STF, followed by -10.16-1, -10.16-2, w/wo -KM, -AU, -BK and/or -ABGY, HT BK.								

<b>Note:</b> (8) Suffixes -ST or -STF, followed by -5.08, w/wo -KM, -AU, -BK and/or -ABGY, HT BK.								
SMSTB(1)(5)	30-12	CU	2	5-7	300	15	B,D	2 (105),4
SMSTB(1)(8)	30-12	CU	2	5-7	600	15	B,D	2 (105),4
SMSTB(1)(7)	30-12	CU	2	5-7	600	15	B,D	2(105)
SMSTB(1)(9)	—	CU	1	N/A	600	15	B,D	2(105)
SMSTB(1)(6)	—	CU	1	N/A	300	15	B,D	2(105)
SMSTBA(1)(9)	—	CU	1	N/A	600	15	B,D	2(105)
SMSTBA(1)(6)	—	CU	1	N/A	300	15	B,D	2(105)
FKC, FKCS(1)(10)	26-12	CU	2	N/A	600	1016A Suffix -HC	B,D	2 (105),4
FKC, FKCT(1)(5)	26-12	CU	2	N/A	300	1016A Suffix -HC	B,D	2(105)
TFKC(1)(4)	26-12	CU	2	N/A	300	1016A Suffix -HC	B,D	2 (105),4
FKIC, FKICS(1)(10)	26-12	CU	2	N/A	600	1016A Suffix -HC	B,D	2 (105),4
FKIC(1)(5)	26-12	CU	2	N/A	300	1016A Suffix -HC	B,D	2(105)
FKCVR(1)(10)	26-12	CU	2	N/A	600	1016A Suffix -HC	B,D	2 (105),4
FKCVR(1)(5)	26-12	CU	2	N/A	300	1016A Suffix -HC	B,D	2(105)
FKCVW(1)(10)	26-12	CU	2	N/A	600	1016A Suffix -HC	B,D	2 (105),4
FKCVW(1)(5)	26-12	CU	2	N/A	300	10	B,D	2(105)
TMSTBP(1)(11)	30-12	CU	2	5-7	600	15	B,D	2 (105),4
TMSTBP(1)(4)	30-12	CU	2	5-7	300	15	B,D	2(105)
MSTBO(1)(12)	—	CU	1	N/A	600	8	B,D	2(105)
MSTBO(1)(3)	—	CU	1	N/A	300	8	B,D	2(105)
MSTB2.5/2-GFL-5.08	—	CU	1	—	300	15	B,D	2(105)
MSTB2.5/2-STFL-5.08	30-12	CU	2	5-7	300	15	B,D	2(105)
MVSTBR2.5/X-STF-	30-12	CU	2	5-7	600	10	B,C	2(105)
10.16-1, -2								
CC, CCA, CCV, CCVA (1)(13)	—	CU	1	N/A	300	10	B,C	2(105)
<b>Note:</b> (1) Suffixes 2.5, /one or two digit number.								
<b>Note:</b> (3) Suffixes -GL or -GR, followed by -5.08.								
<b>Note:</b> (4) Suffixes -ST or STF followed by -5.08, w/wo -AU and/or -ABGY.								
<b>Note:</b> (5) Suffixes -ST or STF, followed by -5.08, w/wo -RF, -RN or -A.								
<b>Note:</b> (6) Suffixes -G followed by -5.08, w/wo -AU, BK, and or -ABGY.								
<b>Note:</b> (7) Suffixes ST followed by -5.08, w/wo -AU, -BK, and/or -ABGY, HT BK								
<b>Note:</b> (8) Suffixes -ST followed by -10.16-1, or -10.16-2, w/wo -AU, -BK and/or -ABGY, HT BK								
<b>Note:</b> (9) Suffix -G, followed by -10.16-1, or -10.16-2, w/wo -AU, -BK and/or -ABGY, HT BK								

<b>Note:</b> (10) Suffixes -ST, -STF or -STZ followed by -10.16-1, or -10.16-2 with or without NZ:EH.								
<b>Note:</b> (11) Suffixes -ST or -STF, followed by -10.16-1, or -10.16-2, w/wo -AU and/or -ABGY, HT BK.								
<b>Note:</b> (12) Suffixes -GL or -GR, followed by -5.08, -10.16-1, or -10.16-2.								
<b>Note:</b> (13) Suffixes -G,GF, GL,GR,GFL, or GFR followed by -5.08P26THR, or -5.08RNP26THR.								
DFK-MSTB(1)(2)	—	CU	1	N/A	300	15	B,D	2(105)
FRONT-MSTB(1)(3)	30-12	CU	2	5-7	300	15	B,D	2(105),4
MDSTB(1)(4)	—	CU	1	N/A	600	15	B,D	2(105)
MDSTBA(1)(4)	—	CU	1	N/A	600	15	B,D	2(105)
MDSTBA(1)(2)	—	CU	1	N/A	300	15	B,D	2(105)
MDSTB(1)(2)	—	CU	1	N/A	300	15	B,D	2(105)
MDSTBV(1)(2)	—	CU	1	N/A	300	15	B,D	2(105)
MDSTBV(1)(4)	—	CU	1	N/A	600	15	B,D	2(105)
MDSTBV(1)(6)	—	CU	1	N/A	600	15	B,D	2(105)
MDSTBVA(1)(2)	—	CU	1	N/A	300	15	B,D	2(105)
MDSTBVA(1)(4)	—	CU	1	N/A	600	15	B,D	2(105)
MDSTBVA(1)(6)	—	CU	1	N/A	600	15	B,D	2(105)
MDSTBVH(1)(2)	—	CU	1	N/A	300	15	B,D	2(105)
MDSTBVH(1)(4)	—	CU	1	N/A	600	15	B,D	2(105)
MDSTBVH(1)(6)	—	CU	1	N/A	600	15	B,D	2(105)
MDSTBVHA(1)(2)	—	CU	1	N/A	300	15	B,D	2(105)
MDSTBVHA(1)(4)	—	CU	1	N/A	600	15	B,D	2(105)
MDSTBVHA(1)(6)	—	CU	1	N/A	600	15	B,D	2(105)
MDSTBW(1)(2)	—	CU	1	N/A	300	15	B,D	2(105)
MDSTBW(1)(4)	—	CU	1	N/A	600	15	B,D	2(105)
MDSTBW(1)(6)	—	CU	1	N/A	600	15	B,D	2(105)
MSTB(1)(1B)(5)	30-12	CU	2	5-7	600	15	B,D	2(105),4
MSTBP(1)(1B)(5)	30-12	CU	2	5-7	300	15	B,D	2(105),4
<b>Note:</b> (1) Suffixes 2.5, followed by /one or two-digit number.								
<b>Note:</b> (2) Suffixes -G, -GF, -GFL, -GFR, -GL or -GR, w/wo WW1X1, w/wo -HT.								
<b>Note:</b> (3) Suffixes -ST or -STF, w/wo -AU, -BK and/or -ABGY.								
<b>Note:</b> (4) Suffixes -G, -GF, -GL, -GR, -GFL, -GFR, or -G1, w/wo-HT, followed by -10.1 or -10.2.								
<b>Note:</b> (5) Suffixes -ST, -STF or -STZ, w/wo -10.1 or -10.2.								
<b>Note:</b> (6) Suffixes -G, -GF, or -G1 w/wo -HT, followed by -10-1, or 10-2.								
MSTBT(1)(1B)(5)	30-12	CU	2	5-7	300	15	B,D	2(105),4
MSTB(1)(1A)(6)	—	CU	1	N/A	600	16	B,D	2(105)
MSTB(1)(1A)(7)	—	CU	1	N/A	300	16	B,D	2(105)
MSTBA(1)(1A)(6)	—	CU	1	N/A	600	16	B,D	2(105)
MSTBA(1)(1A)(7)	—	CU	1	N/A	300	16	B,D	2(105)

MSTBAG(1)(1A)(6)	—	CU	1	N/A	600	16	B,D	2(105)
MSTBAG(1)(1A)(7)	—	CU	1	N/A	300	16	B,D	2(105)
MSTBAGKL(1)(1A)(6)	—	CU	1	N/A	600	16	B,D	2(105)
MSTBAGKL(1)(1A)(7)	—	CU	1	N/A	300	16	B,D	2(105)
MSTBV(1)(1A)(6)	—	CU	1	N/A	600	16	B,D	2(105)
MSTBV(1)(1A)(7)	—	CU	1	N/A	300	16	B,D	2(105)
MSTBVA(1)(1A)(6)	—	CU	1	N/A	600	16	B,D	2(105)
MSTBVA(1)(1A)(7)	—	CU	1	N/A	300	16	B,D	2(105)
MSTBVAG(1)(1A)(6)	—	CU	1	N/A	600	16	B,D	2(105)
MSTBVAG(1)(1A)(7)	—	CU	1	N/A	300	16	B,D	2(105)
MSTBW(1)(1A)(6)	—	CU	1	N/A	300	16	B,D	2(105)
MSTBW(1)(1A)(7)	—	CU	1	N/A	300	16	B,D	2(105)
<b>Note:</b> (1)Suffixes 2.5, followed by /one or two-digit number.								
<b>Note:</b> (1A)With or without suffixes HC and/or L.								
<b>Note:</b> (1B)Suffixes 2.5 followed by HC, followed by /one or two-digit number.								
<b>Note:</b> (5)Suffixes -ST, -STF or -STZ, w/wo -10.1 or -10.2.								
<b>Note:</b> (6)Suffixes -G, -G0.5 or -GF, w/wo -10.1, -10.2, w/wo -THT, -LA, -LAB/RD, -R, -AU, -BK and/or -ABGY.								
<b>Note:</b> (7)Suffixes -G, -G0.5, or -GF, w/wo -THT, -LA, -LAB/RD, -R, -AU, -BK, and/or -ABGY.								
MVSTBN(1)(1B)(7)	30-12	CU	2	5-7	300	15	B,D	2(105),4
MVSTBR(1)(1B)(7)	30-12	CU	2	5-7	300	15	B,D	2(105),4
MVSTBW(1)(1B)(7)	30-12	CU	2	5-7	300	15	B,D	2(105),4
SMSTB(1)(8)	30-12	CU	2	5-7	300	15	B,D	2(105),4
SMSTB(1)(9)	—	CU	1	N/A	300	15	B,D	2(105)
SMSTBA(1)(9)	—	CU	1	N/A	300	15	B,D	2(105)
MSTBO f/b /1 or /2 digit No., by -GL, -G1L, -GR or -G1R and -5.08	—	CU	1	N/A	300	15	B,D	2(105)
MSTBO f/b /1 or /2 digit No., by -G1L or -G1R, w/wo -THR and -5.08	—	CU	1	N/A	300	15	B,D	2(105)
FKC(1)(10)	26-12	CU	2	N/A	600	1016A Suffix -HC	B,D	2(105)
FKCT(1)(5)	26-12	CU	2	N/A	300	1016A Suffix -HC	B,D	2(105)
FKC, FKCS(1)(5)	26-12	CU	2	N/A	300	1016A Suffix -HC	B,D	2(105),4
FKIC(1)(10)	26-12	CU	2	N/A	600	1016A Suffix -HC	B,D	2(105)
FKIC, FKICS(1)(5)	26-12	CU	2	N/A	300	1016A Suffix -HC	B,D	2(105)
FKCVR(1)(10)	26-12	CU	2	N/A	600	1016A Suffix -HC	B,D	2(105)
FKCVR(1)(5)	26-12	CU	2	N/A	300	1016A Suffix -HC	B,D	2(105)

FKCVW(1)(10)	26-12	CU	2	N/A	600	1016A Suffix -HC	B,D	2(105)
FKCVW(1)(5)	26-12	CU	2	N/A	300	1016A Suffix -HC	B,D	2(105)
QC1.5/X-	25-16	CU	2	N/A	300	10	B,D	2 (105),4
<b>Note:</b> (1)Suffixes 2.5, followed by /one or two-digit number.								
<b>Note:</b> (5)Suffixes -ST, -STF or -STZ.								
<b>Note:</b> (7)Suffixes -ST or -STF, w/wo -AU, -BK and/or -ABGY, may be followed by -10-1, or 10-2.								
<b>Note:</b> (8)Suffixes -ST, w/wo -AU, -BK and/or -ABGY, may be followed by -10-1, or 10-2.								
<b>Note:</b> (9)Suffixes -G, w/wo -AU, -BK and/or -ABGY, may be followed by -10-1, or 10-2.								
<b>Note:</b> (10)Suffixes -ST or -STF, followed by -10-1 or -10-2.								
FRONT-GMSTB(1)(2)	30-12	CU	2	5-7	300	15	B,D	2 (105),4
GMSTB(1)(3)	30-12	CU	2	5-7	600	15	B,D	2 (105),4
GMSTB(1B)(3)	30-12	CU	2	5.7	300	16	B,D	2 (105),4
GMSTBP(3)	30-12	CU	2	5-7	600	15	B,D	2 (105),4
GMSTBP(5)	30-12	CU	2	5-7	300	15	B,D	2(105)
GMSTB(1)(4)	—	CU	1	N/A	600	15	B,D	2(105)
GMSTB(1)(6)	—	CU	1	N/A	300	15	B,D	2(105)
GMSTBA(1)(4)	—	CU	1	N/A	600	15	B,D	2(105)
GMSTBA(1)(6)	—	CU	1	N/A	300	15	B,D	2(105)
GMSTBV(1)(4)	—	CU	1	N/A	600	15	B,D	2(105)
GMSTBV(1)(6)	—	CU	1	N/A	300	15	B,D	2(105)
GMSTBVA(1)(4)	—	CU	1	N/A	600	15	B,D	2(105)
GMSTBVA(1)(6)	—	CU	1	N/A	300	15	B,D	2(105)
GMSTBAS2.5/4-G-7.62	—	CU	1	—	600	15	B,D	2(105)
<b>Note:</b> (1)Suffixes 2.5, followed by /one or two-digit number.								
<b>Note:</b> (1B) Suffixes 2.5, followed by HC, followed by / one or two digit number.								
<b>Note:</b> (2)Suffixes -ST or -STF, followed by -7.62, w/wo -AU, -BK and/or -ABGY.								
<b>Note:</b> (3)Suffixes -ST, w/wo -15.24, -1, -2, -AU, -BK and/or -ABGY.								
<b>Note:</b> (4)Suffixes -G or -GF, w/wo -15.24, -1, -2, -LA, -R, -AU, -BK and/or -ABGY.								
<b>Note:</b> (5)Suffixes -ST, w/wo -7.62, -AU, -BK and/or -ABGY.								
<b>Note:</b> (6)Suffixes -G, -GF w/wo -7.62, -LA, -R, -AU, -BK and/or -ABGY.								
GMVSTBR(1)(5)	30-12	CU	2	5-7	300	15	B,D	2 (105),4
GMVSTBW(1)(5)	30-12	CU	2	5-7	300	15	B,D	2 (105),4
GMVSTBR(1B)(3)	30-12	CU	2	5.7	300	16	B,D	2 (105),4
GMVSTBR(1B)(5)	30-12	CU	2	5.7	300	16	B,D	2 (105),4

GMVSTBW(1B)(5)	30-12	CU	2	5.7	300	16	B,D	2 (105),4
GMVSTBR(1)(6)	30-12	CU	2	5-7	600	15	B,C	2 (105),4
GMVSTBW(1)(6)	30-12	CU	2	5-7	600	15	B,C	2 (105),4
UGMSTBHK(1)(7)	30-12	CU	2	5-7	300	15	B,D	2 (105),4
GMSTBHK(1)(7)	30-12	CU	2	5-7	300	15	B,D	2 (105),4
GFKC (1) -ST, -STF	22-12	CU	2	N/A	300	10	B,D	2 (105),4
f/b -7.5 or -7.62								
<b>Note:</b> (1)Suffixes 2.5, followed by /one or two-digit number.								
<b>Note:</b> (1B) Suffixes 2.5, followed by HC, followed by / one or two digit number.								
<b>Note:</b> (5)Suffixes -ST or -STF, followed by -7.62, -AU, -BK and/or -ABGY.								
<b>Note:</b> (6)Suffixes -HV, followed by -ST or -ST.762 or /8-STGY3XEB2.								
<b>Note:</b> (7)Suffixes /10-G, w/wo -7.62.								
GIC, GICV(1)(2)	—	CU	1	N/A	300	1516ASuffix- HC	B,D	2(105)
GIC, GICV(1)(3)	30-12	CU	2	5-7	300	1516ASuffix- HC	B,D	2 (105),4
IC,ICV, AICV (1)(4)	—	CU	1	N/A	300	1516ASuffix- HC	B,D	2(105)
IC, ICV(1)(5)	30-12	CU	2	5-7	300	1516ASuffix- HC	B,D	2 (105),4
MSTBH(6)	—	CU	1	N/A	300	15	B,D	2(105)
MSTBHK(6)	30-12	CU	2	5-7	300	15	B,D	2 (105),4
MSTBHKT(6)	30-12	CU	2	5-7	300	15	B,D	2 (105),4
<b>Note:</b> (1)Suffixes 2.5, followed by /one of two-digit number.								
<b>Note:</b> (2)Suffixes -G, -GF, followed by -7.62.								
<b>Note:</b> (3)Suffixes -ST, -STF, -STGF, followed by -7.62.								
<b>Note:</b> (4)Suffixes -G, -GF, followed by -5.08.								
<b>Note:</b> (5)Suffixes -ST, -STF, -STGF, followed by -5.08.								
<b>Note:</b> (6)Suffixes 2.5, followed by /10G, followed by -5.08.								
UMSTBHK(6)	30-12	CU	2	5-7	300	15	B,D	2 (105),4
UMSTBHKT(6)	30-12	CU	2	5-7	300	15	B,D	2 (105),4
MSTBU(1)(7)	30-12	CU	2	5-7	300	15	B,D	2 (105),4
MVSTBU(1)(8)	—	CU	1	N/A	300	15	B,D	2(105)
MVSTBU(1)(9)(11)(14)	30-12	CU	2	5-7	300	15	B,D	2 (105),4
MSTBVK(1)(10)	—	CU	1	N/A	300	15	B,D	2(105)
<b>Note:</b> (1)Suffixes 2.5, followed by /one of two-digit number.								

<b>Note:</b> (6) Suffixes 2.5, followed by /10G, followed by -5.08.								
<b>Note:</b> (7) Suffixes -ST, -STD, followed by -5.08, w/wo -FL.								
<b>Note:</b> (8) Suffixes -GB, -GFB, followed by -5.08.								
<b>Note:</b> (9) Suffixes -STF, followed by -5.08.								
<b>Note:</b> (10) Suffixes -G, -GF, followed by -5.08.								
<b>Note:</b> (11) -STSO CEAG, STFSO CEAG followed by -5.08.								
<b>Note:</b> (14) -Cat. No. MVSTBU2.5 additionally has a multiple wire rating of 2 No. 16 AWG Cu. stranded wires for field and factory-wiring.								
MVSTBK(1)(11)	30-12	CU	2	5-7	300	15	B,D	2 (105),4
UMSTBVK(1)(10)	—	CU	1	N/A	300	15	B,D	2(105)
UMSTBVK(1)(11)	30-12	CU	2	5-7	300	15	B,D	2 (105),4
UMSTBVK2.5/X-STF-	30-12	CU	2	5-7	600	10	B,C	2(105)
10.16-1, -2								
UMSTBVK2.5/X-GF	—	CU	1	N/A	600	10	B,C	2(105)
SKLB(13)	—	CU	1	N/A	300	10	B,D	2(105)
SKLB(12)	30-12	CU	2	5-7	300	10	B,D	2 (105),4
<b>Note:</b> (1) Suffixes 2.5, followed by /one of two-digit number.								
<b>Note:</b> (10) Suffixes -G, -GF, followed by -5.08.								
<b>Note:</b> (11) Suffixes -ST, -STF, followed by -5.08.								
<b>Note:</b> (12) Suffixes 2.5, /12.								
<b>Note:</b> (13) Suffixes 2.5, /12, followed by -ST.								
HCC4-F, -M	30-10	CU	2	5-7	300	15	B,C	2 (105),4
UISLKG35	2-18	CU	2	18	NA	NA	B,C	2 (105),4
MSTBC2.5(1)	30-12	CU	1	—	300	10	B,D	2(105)
ICC2.5(2)	30-12	CU	1	—	300	10	B,D	2(105)
MSTBC2.5/X-STZF-	20- 18/16- 14	CU	1	N/A	600	10	B,C	2(105)
10.16-1, -2								
ICC2.5/X-STZF-	20- 18/16- 14	CU	1	N/A	600	10	B,C	2(105)
10.16-1, -2								
<b>Note:</b> (1) Followed by /one or two digit number suffix -ST, -STZ, -STZF or -STZFD and by -5.08.								
<b>Note:</b> (2) Followed by /one or two digit number, Suffix -STZ, -STZD or -STZF, and by -5.08.								
<b>Note:</b> (#) The terminal blocks are to be installed on the manufactures 35mm wide copper (only) mounting rails, intended for the purpose.								
IDC0.5-DL(1)	20-30 (2)	CU	2	—	300	5	B,D	2(105)
IDC0.8-DP(1)	18-30 (2)	CU	2	—	300	10(3)	B,D	2(105)

<b>Note:</b> (1) Followed by /one or two digit number.								
<b>Note:</b> (2) Factory-wiring only for wires smaller than No. 22 AWG.								
<b>Note:</b> (3) 7A max for field-wiring.								
UGMSTBHK, GMSTBHK	30-12	CU	2	5-7	300	10	B,D	2(75)
with suffix 2.5,								
f/b /10-G,w/wo -7.62								
MBK5/E-T or-TG	28-12	CU	2	5-7	300	20	B,C	2 (105),4
MBT2.5, -BU, -T10	30-12	CU	2	5-7	300	20	B,C	2 (105),4
MBT2.5-PE	30-12	CU	2	5-7	—	—	B,C	2 (105),4
UK2.5(1)	30-12	CU	2	5-7	600	20	B,C	2 (105),4
UK3(1)	30-12	CU	2	5-7	300	20	B,C	2 (105),4
UK4(1)	28-12	CU	2	5-7	600	20	B,C	2 (105),4
UXKK4	28-12	CU	2	5-7	600	20	B,C	2 (105),4
<b>Note:</b> (1)Followed by suffix B, -MSTB-5.08, -PLUS, -T, -TG, -T-P/P or -TWIN.								
UK5(1)	30-10	CU	2	5-7	300	30	B,C	2 (105),4
UK10(1)	24-6	CU	2	11- 20	300	65	B,C	2 (105),4
UK3-TWIN-PE	301-2	CU	2	5-7	300	—	B,D	2 (105),4
UK5-TWIN-PE	30-10	CU	2	5-7	—	—	B,C	2 (105),4
UK10-TWIN-PE	24-6	CU	2	11- 20	—	—	B,C	2 (105),4
UK10-PLUS-PE	24-6	CU	2	11- 20	—	—	B,C	2 (105),4
UK3D-MSTBV-5.08(2)	30-12	CU	2	5-7	300	20	B,C	2 (105),4
UKK3-MSTB-5.08	30-12	CU	2	5-7	300	10	B,C	2 (105),4
USK4-FSR(3)	28-12	CU	2	5-7	600	20	B,C	2 (105),4
<b>Note:</b> (1)Followed by suffix B, -MSTB-5.08, -PLUS, -T, -TG, -T-P/P or -TWIN.								
<b>Note:</b> (2)With or without suffixes /EK, -LA12RD, -LA12RT, -LA24RD, -LA24RT, -LA48RD, -LA48RT, -LA60RD, -LA60RT.								
<b>Note:</b> (3)Followed by suffix (3-2.8-0.8) or (4-2.8-0.8).								
G5(1)	26-10	CU	2	5-7	300#	30	B	2 (105),4
K2.5(2)	30-14	CU	2	5-7	300	15	B,D	2 (105),4
K3(2)	28-12	CU	2	5-7	600	20	B,C	2 (105),4
K4(2)	28-12	CU	2	5-7	600	20	B,C	2



								(105),4
K4-TG(2)	28-12	CU	2	5-7	300	20	B,D	2 (105),4
K5(2)	26-10	CU	2	5-7	600	30	B,D	2 (105),4
K10(2)	26-8	CU	2	11-15	600	50	B,C	2 (105),4
K16, K16/E	24-6	CU	2	11-15	600	65	B,C	2 (105),4
K25, K25/E	22-4	CU	2	18-25	600	85	B,C	2 (105),4
K35, K35/E	18-1/0	CU	2	30-50	600	140	B,C	2 (105),4
MBK	30-14	CU	2	5-7	300	15	B,D	2 (105),4
MBK2.5/E	30-12	CU	2	5-7	300	20	B,D	2 (105),4
MBKKB2.5-PV	30-12	CU	2	5-7	300	20	B,D	2 (105),4
MBK2.5/E-PE	30-12	CU	2	5-7	—	—	B,D	2 (105),4
UGSK/S	26-8	CU	2	11-15	600	50	B,2	2(105)
<b>Note:</b> (1) Followed by suffixes /2, /3, /4, /6, /12, /2B.								
<b>Note:</b> (2) May be followed by suffixes /E, /M.								
GTF76/230	26-8	CU	2	11-15	250	50	B,C	2(105)
ST-BE	14-30	CU	2	5-7	300	10	B,C	2(105)
ST-BE-VIERPOL	14-30	CU	2	5-7	300	10	B,C	2(105)
ST-1N4007	14-30	CU	2	5-7	300	1	B,C	2(105)
MBK3/E-Z-PE	30-12	CU	2	5-7	—	—	B,D	2 (105),4
MBK3	28-12	CU	2	5-7	600	20	B,C	2 (105),4
MBK5, MBK5/E	26-10	CU	2	5-7	600	30	B,C	2 (105),4
MBK5/E-FS	26-10	CU	2	5-7	300	5	B,D	2 (105),4
MBK5/E-FS/FS	26-10	CU	1	—	300	—	B,D	2 (105),4
MBK10	26-8	CU	2	11-15	600	50	B,C	2 (105),4
SSK5(3)	26-10	CU	2	5-7	600	30	B,C	2 (105),4
SSK0525-TG(3)	28-12	CU	2	5-7	300	20	B,D	2 (105),4
SSK/N0525-LB1(3)	28-12	CU	2	5-7	600	20	B,C	2 (105),4
SSK110(3)	26-8	CU	2	11-15	600	50	B,C	2 (105),4
SSK116(3)	24-6	CU	2	11-	600	65	B,C	2

				15				(105),4
SSK125(3)	22-4	CU	2	18-25	600	85	B,C	2 (105),4
SSK135(3)	18-2	CU	2	20-50	600	115	B,C	2 (105),4
ST-Si(4)	—	CU	1	—	300	10	B,D	2 (105),4
UDK3	30-12	CU	2	5-7	300#	20	B,D	2 (105),4
UDK4	30-10	CU	2	5-7	600#	30	B,D	2 (105),4
UDK4-ILA500	30-10	CU	2	5-7	600	0.5	B,D	2 (105),4
UDK4-ILA1000	30-10	CU	2	5-7	600	1	B,D	2 (105),4
UDK4-ULA(5)	30-10	CU	2	5-7	600#	30	B,D	2 (105),4
URTK/S,	26-8	CU	2	11-15	300	50	B,D	2 (105),4
URTK/S-Ben	26-8	CU	2	11-15	300	50	B,D	2 (105),4
<b>Note:</b> (3) May be followed by suffix Kri.								
<b>Note:</b> (4) May be followed by suffixes LA250, LED12, LED24, LED60, -UK4.								
<b>Note:</b> (5) May be followed by suffixes -12RD/O-U, -12RT/O-U, -24RD/O-U, -24RT/O-U, -48RD/O-U, -48RT/O-U, -60RD/O-U, -60RT/O-U, 220, -/UK.								
<b>Note:</b> #Limited amp rating at max voltage of 300v or 600v.								
URTK/SP	26-8	CU	2	15	300	45	B,D	2 (105),4
URTK/S-Ben 10	26-8	CU	2	20	600	50	B,D	2 (105),4
URTK/SS	28-12	CU	2	5-7	300	20	B,D	2 (105),4
URDK6	26-8	CU	2	15	300	50	B,C	2(105)
URTK6	26-8	CU	2	15	300	50	B,C	2(105)
UGSK6	26-8	CU	2	15	300	50	B,C	2(105)
MT1.5	30-14	CU	2	4	300	15	B,D	2 (105),4
MT1.5-TWIN	30-14	CU	2	4	300	15	B,D	2 (105),4
MT1.5-QUATTRO	30-14	CU	2	4	300	15	B,D	2 (105),4
MT1.5-PE	30-14	CU	2	4	—	—	B,D	2 (105),4
MTTB1.5	30-14	CU	2	4	300	15	B,D	2 (105),4
SI-H-FKS15	N/A	CU	1	N/A	32	15	B,C	2(125)
SI-H-FKS30	N/A	CU	1	N/A	32	30	B,C	2(125)
MT1.5-TWIN-PE	14-30	CU	2	4	—	—	B,D	2(105)
MT1.5-QUATTRO-PE	14-30	CU	2	4	—	—	B,D	2(105)

ZFK1.5(4)	14-26	CU	2	N/A	300	—	B,C	2(105)
ZFK1.5PE(4)	14-26	CU	2	N/A	—	—	B,C	2(105)
ZKKB1.5(4)	26-14	CU	2	N/A	600	15	B,C	2 (105),4
ZFK2.5(4)	12-26	CU	2	N/A	600	20	B,C	2(105)
ZFK2.5-PE(4)	12-26	CU	2	N/A	—	—	B,C	2(105)
ZFK2.5-MT(4)	12-26	CU	2	N/A	300	15	B,C	2(105)
ZDMTK2.5(4)	26-12	CU	2	N/A	300	10	B,C	2(105)
ZDMTK2.5-TWIN(4)	26-12	CU	2	N/A	300	10	B,C	2(105)
ZFKK2.5-MT(4)	26-14	CU	2	N/A	600	15,20	B,C	2 (105),4
ZFK2.5-TWIN(4)	12-26	CU	2	N/A	600	20	B,C	2(105)
ZFK2.5-TWIN-PE(4)	12-26	CU	2	N/A	—	—	B,C	2(105)
ZFKI2.5(4)	12-26	CU	2	N/A	600	20	B,C	2(105)
ZFKI2.5-PE(4)	12-26	CU	2	N/A	—	—	B,C	2(105)
ZFDK2.5(4)	12-26	CU	2	N/A	600	20	B,C	2(105)
ZFDK2.5-MT(4)	12-26	CU	2	N/A	300	15	B,C	2(105)
<b>Note:</b> (4) All may be followed by suffix BU.								
ZFDK2.5-PE(4)	12-26	CU	2	N/A	—	—	B,C	2(105)
ZFKKB2.5(4)	12-26	CU	2	N/A	600	20	B,C	2(105)
ZFK4(4)	10-24	CU	2	N/A	600	30	B,C	2(105)
ZFK4-PE(4)	12-24	CU	2	N/A	—	—	B,C	2(105)
ZFK4-TG(4)	10-24	CU	2	N/A	600	15	B,C	2(105)
ZFK4-HESI	10-24	CU	2	N/A	600	10	B,C	2 (105),4
ZFK4-HESILED	10-24	CU	2	N/A	600	10	B,C	2 (105),4
ZFK4-HESILA	10-24	CU	2	N/A	600	10	B,C	2 (105),4
ZGSK4	24-10	CU	2	N/A	300	30	B,C	2 (105),4
ZRTK4	24-10	CU	2	N/A	300	30	B,C	2 (105),4
ZFKI4(4)	10-24	CU	2	N/A	600	30	B,C	2(105)
ZFKI4-PE(4)	12-24	CU	2	N/A	—	—	B,C	2(105)
ZFK4-TWIN(4)	24-10	CU	2	N/A	600	30	B,C	2 (105),4
ZFK4-TWIN-PE(4)	24-10	CU	2	N/A	—	—	B,C	2 (105),4
ZFKK4(4)	24-10	CU	2	N/A	600	30	B,C	2 (105),4
ZFKD4-PE(4)	24-12	CU	2	N/A	—	—	B,C	2 (105),4
ZFKKB4(4)	24-10	CU	2	N/A	600	30	B,C	2 (105),4
ZFK6(4)	20-8	CU	2	N/A	600	50	B,C	2

								(105),4
ZFK6-DREHSI (5X20) (4)	20-8	CU	2	N/A	600	20	B,C	2 (105),4
ZFK6-DREHSI (6.3X32) (4)	20-8	CU	2	N/A	600	20	B,C	2 (105),4
<b>Note:</b> (4) All may be followed by suffix BU.								
ZFK6-PE	8-20	CU	2	N/A	600	N/A	B,C	2 (105),4
ZFK6(4)	20-8	CU	2	N/A	600	50	B,C	2 (105),4
ZFK6-DREHSI (5X20) (4)	20-8	CU	2	N/A	600	20	B,C	2 (105),4
ZFK6-DREHSI (6.3X32) (4)	20-8	CU	2	N/A	600	20	B,C	2 (105),4
ZFKDS(1)	26-12	CU	2	N/A	300	10	B,C	2(105)
ZFKDSA1.5-7.62(4)	26-12	CU	2	N/A	300	10	B,C	2(105)
ZFKKDS(1)	12-26	CU	2	N/A	300	10	B,C	2(105)
ZFKKDSA(1)	12-26	CU	2	N/A	300	10	B,C	2(105)
ZFK3DS(1)	12-26	CU	2	N/A	300	10	B,C	2(105)
ZFK3DSA(1)(3)	12-26	CU	2	N/A	300	10	B,C	2(105)
ZFK3DS1.5/18-BK	26-12	CU	2	N/A	300	10	B,C	2(105)
5650288								
<b>Note:</b> (1) Followed by suffixes 1.5, -5.08, or -6.08 all may be followed by suffix BU.								
<b>Note:</b> (2) All Cat. Nos. are with or without suffixes -F, -M, -NS35, all may be followed by suffix BU.								
<b>Note:</b> (3) May be followed by suffix -DS, all may be followed by suffix BU.								
<b>Note:</b> (4) All may be followed by suffix BU.								
ZFK3DS1.5/18-BK	26-12	CU	2	N/A	300	10	B,C	2(105)
5650288								
ZFK4DS1.5-5.08	26-12	CU	2	N/A	300	10	B,C	2(105)
ZFK4DSA1.5-6.08	26-12	CU	2	N/A	300	10	B,C	2(105)
MZB1.5(2)	26-14	CU	2	N/A	600	15	B,C	2(105)
MZDB1.5(2)	26-14	CU	2	N/A	600	15	B,C	2(105)
MZFK1.5(4)	26-14	CU	2	N/A	600	15	B,C	2(105)
MZFK1.5-PE(4)	26-14	CU	2	N/A	N/A	N/A	B,C	2 (105),4
MZB1.5-PE(4)	26-14	CU	2	N/A	N/A	N/A	B,C	2(105)
MZB1.5-NS35-PE(4)	26-14	CU	2	N/A	N/A	N/A	B,C	2(105)
ZFK6(5)	20-8	CU	2	N/A	600	20	B,C	2(105)
ZEC1.0 (7)	26-16	CU	2	N/A	300	8	D	2(105)
ZEC1.5 (8)	26-14	CU	2	N/A	300	10	B,D	2(105)
ZEC1.5/5-ST-7.5	26-14	CU	2	N/A	600	10	B,D	2(105)
with suffixes NZ:292416, NZ:292417								
<b>Note:</b> (1) Followed by suffixes 1.5 and -5.08.								

<b>Note:</b> (2) All Cat. Nos. are with or without suffixes -F, -M, -NS35, all may be followed by suffix BU.								
<b>Note:</b> (3) May be followed by suffix -DS.								
<b>Note:</b> (4) All may be followed by suffix BU.								
<b>Note:</b> (5) Followed by suffixes -DREHSILED24or -FREHSILSA250 and by (5x20) or (6.3x32).								
<b>Note:</b> (7) Followed by /1 or /2 digit number, followed by -ST-3.5C1R1 and a 1 or 2 digit number.								
<b>Note:</b> (8) Followed by /1 or /2 digit number, followed by -ST, -5.0 or -7.5 C1, followed by Suffix C2 R1 and a 1 or 2 digit number.								
ZDIK1.5(6)	26-14	CU	2	N/A	300	15	B,C	2(105)
ZVIOK1.5(6)	26-14	CU	2	N/A	300	15	B,C	2(105)
ZFKK1.5-MSTBV-5.08	26-14	CU	2	N/A	300	15	B,C	2(105)
ZFKK1.5-MSTBV- 5.08-PE/F	26-14	CU	2	N/A	Grounding	N/A	B,C	2(105)
ZFKK1.5-ICV-5.08	26-14	CU	2	N/A	300	15	B,C	2(105)
ZFKK1.5-ICV- 5.08-PE/F	26-14	CU	2	N/A	—	—	B,C	2 (105),4
ZFK1.5-TWIN(4)	26-14	CU	2	N/A	300	15	B,C	2(105)
ZFKDS2.5-5.08	26-12	CU	2	N/A	300	10	B,C	2 (105),4
ZFKDS2.5-5.08-L	26-12	CU	2	N/A	300	10	B,C	2 (105),4
ZFKDSA2.5-6.08-R	26-12	CU	2	N/A	300	10	B,C	2 (105),4
ZFKKDS2.5-5.08	26-12	CU	2	N/A	300	10	B,C	2 (105),4
ZFKKDS2.5-5.08-L	26-12	CU	2	N/A	300	10	B,C	2 (105),4
ZFKKDS2.5-6.08-R	26-12	CU	2	N/A	300	10	B,C	2 (105),4
ZFDK1.5(4)	26-14	CU	2	N/A	300	15	B,C	2(105)
ZFKK1.5(4)	26-14	CU	2	N/A	300	15	B,C	2(105)
ZFKDS1(7)	26-16	CU	2	N/A	300	10	B,C	2(105)
ZFKDSA1(7)	26-16	CU	2	N/A	300	10	B,C	2(105)
ZFK1.5-TWIN-PE	26-14	CU	2	N/A	—	—	B,C	2(105)
ZFKDS1.5C-5.0	26-12	CU	2	N/A	300	10	B,C	2(105)
ZFKDSA1.5C-6.0	26-12	CU	2	N/A	300	10	B,C	2(105)
ZFKKDS1.5C-5.0	26-12	CU	2	N/A	300	10	B,C	2(105)
ZFKKDSA1.5C-5.0L	26-12	CU	2	N/A	300	10	B,C	2(105)
ZFKKDS1.5C-6.0R	26-12	CU	2	N/A	300	10	B,C	2(105)
ZFDK1.5-PE	26-14	CU	2	N/A	—	—	B,C	2(105)
MZFKK1.5	24-14	CU	2	N/A	600	15	B,C	2(105)
MZFKK1.5-PV	24-14	CU	2	N/A	600	15	B,C	2(105)
MZFKKB1.5	26-14	CU	2	N/A	600	15	B,C	2(105)
MZFKK1.5	26-14	CU	2	N/A	600	15	B,C	2(105)
ZPV1.5/2.5(8/1)	24-10	CU	2	N/A	300	15	B,D	2 (105),4

ST4, ST4/1P	28-10	CU	2	N/A	600	30	B,C	2 (105),4
ST4-TWIN	28-10	CU	2	N/A	600	30	B,C	2 (105),4
ST4-QUATTRO, -U, /2P	28-10	CU	2	N/A	600	30	B,C	2 (105),4
STTB4	28-10	CU	2	N/A	300	30	B,C	2 (105),4
STTB4-PV	28-10	CU	2	N/A	300	30	B,C	2 (105),4
ST4-PE, ST4/1P-PE	28-10	CU	2	N/A	N/A	N/A	B,C	2 (105),4
ST4-PE-/3L	28-10	CU	2	N/A	(#)	(##)	B,C	2 (105),4
ST4-TWIN-PE	28-10	CU	2	N/A	N/A	N/A	B,C	2 (105),4
ST4-QUATTRO-PE,	28-10	CU	2	N/A	N/A	N/A	B,C	2 (105),4
ST4-QUATTRO/2P-PE								
STS4-TWIN,	28-10	CU	2	N/A	600	30	B,C	2 (105),4
STS4, -BU,								
STS4-QUATTRO								
STS4-TWIN-PE,	28-10	CU	2	N/A	—	—	B,C	2 (105),4
STS4-PE,								
STS4-QUATTRO-PE								
ST4-HESI (5x20)	28-10	CU	2	N/A	300	6.3	B,C	2 (105),4
ST4-HESILED 24	28-10	CU	2	N/A	300	6.3	B,C	2 (105),4
ST4-HESILED 60	28-10	CU	2	N/A	300	6.3	B,C	2 (105),4
ST4-HESILA 250	28-10	CU	2	N/A	300	6.3	B,C	2 (105),4
ST4-HESI (6.2x32)	28-10	CU	2	N/A	300	10	B,C	2 (120),4
ST4-HESILED24 (6.2x32)	28-10	CU	2	N/A	300	10	B,C	2 (120),4
ST4-HESILA250 (6.2x32)	28-10	CU	2	N/A	300	10	B,C	2 (120),4
SP4, SP4/1 or /2 digit number, w/wo Suffixes -L, -M, -R, w/wo Suffix BU or GNYE	24-10	CU	2	N/A	600	30	B,C	2 (120),4
ST4-MT, -MTD, -TG	28-10	CU	2	N/A	300	10	B,C	2 (120),4
<b>Note:</b> (4)All may be followed by surrix BU.								
<b>Note:</b> (6)Followed by suffixes -LA24RD/O-M or -LA24GN/O-M.								
<b>Note:</b> (7)Followed by suffixes -V and/or -W, and by -3.81 or -6.35.								
ST1.5	26-14	CU	2	N/A	300	15	B,C	2(105)

STTB1.5, -PV	26-14	CU	2	N/A	300	15	B,C	2(105)
ST1.5QUATTRO	26-14	CU	2	N/A	300	15	B,C	2(105)
ST1.5-TWIN	26-14	CU	2	N/A	300	15	B,C	2(105)
ST1.5-PE	26-14	CU	2	N/A	—	—	B,C	2(105)
ST1.5-QUATTRO-PE	26-14	CU	2	N/A	—	—	B,C	2(105)
STTB4-PE	20-14	CU	2	NA	—	—	B,C	2 (105),4
ST1.5-TWIN-PE	26-14	CU	2	NA	—	—	B,C	2(105)
ZFKDS4-7.5/X	24-10	CU	2	N/A	300/	30	B,C	2(105)
					300(1)			
ZFKDS4-9	24-10	CU	2	N/A	300/	30	B,C	2(105)
					300(1)			
ZFKDS4-10/X	24-10	CU	2	N/A	300/	30	B,C	2(105)
					600(2)			
ZFKDS4-12.5/X	24-10	CU	2	N/A	600	30	B,C	2(105)
ST4/FSI/C	24-10	CU	2	N/A	300	30	B,C	2 (105),4
ST4/FSI/C-LED12	24-10	CU	2	N/A	300	30	B,C	2 (105),4
ST4/FSI/C-LED24	24-10	CU	2	N/A	300	30	B,C	2(105)
ZFKDS407.6GNYE	24-10	CU	2	N/A	—	—	B,C	2 (105),4
ZFKDS4-10GYNE	24-10	CU	2	N/A	—	—	B,C	2 (105),4
ZFKDSA4-9GNYE	24-10	CU	2	N/A	—	—	B,C	2 (105),4
MZB-RZ, -BU	24-14	CU	2	N/A	600	15	B,C	2 (105),4
MZDB-RZ, -BU	24-14	CU	2	N/A	600	15	B,C	2 (105),4
ABD4 f/b /1 or /2 digit	24-10	CU	2	N/A	600	15	B,C	2 (105),4
number, and by -ST-7.62								
ZFKDS10-10.00	24-6	CU	2	N/A	300150	1065	B,D	2 (105),4
ZFKDSA10-11.7	24-6	CU	2	N/A	300150	1065	B,D	2 (105),4
ZFKDS10-15.00	24-6	CU	2	N/A	600	65	B,C	2 (105),4
ZFKDSA10-16.7	24-6	CU	2	N/A	600	65	B,C	2 (105),4
ZFKDS10-10.00	24-6	CU	2	N/A	300150	1065	B,D	2 (105),4
ZFKDSA10-11.7	24-6	CU	2	N/A	300150	1065	B,D	2 (105),4
ZFKDS10-15.00	24-6	CU	2	N/A	600	65	B,C	2 (105),4
ZFKDSA10-16.7	24-6	CU	2	N/A	600	65	B,C	2

								(105),4
SC4 followed	28-10	CU	2	N/A	600	30	B,C	2 (105),4
by /1 or /2 digit number, w/wo - NS, -RZ, and/or /1-L								
<b>Note:</b> (1)Limited VA 10A max for 300V general industrial use.								
<b>Note:</b> (2)Limited VA 5A max for 600V general industrial use.								
MKKDS1.5(1)	14-30	CU	2	5.0	300	10	B,D	2(105)
MKKDS3(1)(3)	12-30	CU	2	5-7	300	15	B,D	2(105)
MKKDSW3(1)	12-30	CU	2	5-7	300	20	B,D	2(105)
MKKDSH3(1)	12-30	CU	2	5-7	300	20	B,D	2(105)
MK3DS3(1)(3)	12-30	CU	2	5-7	300	20	B,D	2(105)
MK3DS1.5(1)	14-30	CU	2	5.0	300	10	B,D	2(105)
MK3DS1.5(4)	14-30	CU	2	5.0	300	10	B,D	2(105)
MK4DS1.5(4)	14-30	CU	2	5.0	300	10	B,D	2(105)
MK3DS3/18(2)	12-30	CU	2	5-7	300	10	B,D	2(105)
MKKDSG3(1)(3)	12-30	CU	2	5-7	300	10	B,D	2(105)
<b>Note:</b> (1) May be followed by suffixes /2, or /3, and/or -5.08.								
<b>Note:</b> (2) Followed by -36 or -52, and -5.08 AB.								
<b>Note:</b> (3) Multiple wire combination for field and factory-wiring, 2 No. 16 AWG sol/str. Solid and stranded wires are not intermixed.								
<b>Note:</b> (4) Followed by suffixes /2, or /3, and by -5.08, with or without suffixes -A-GNYE, -BC, OR -BCD.								
MK3DSH3(1)	12-30	CU	2	5-7	300	15	B,D	2(105)
MK3DSMH3(1)	12-30	CU	2	5-7	300	15	B,D	2(105)
<b>Note:</b> (1)May be followed by suffixes /2, /3, and/or -5.08.								
G10/2 thru /5	6-24(A)	CU	2	11-20	600	65	B,C	2(105)
<b>Note:</b> (A) Additional wire rating of 2 No. 8 AWG Cu. str., 65A max. factory wiring only.								
KDS10	24-6	CU	2	11-15	300	65	B,C,D	2(105)
KDS10/SO	24-6	CU	2	11-15	300	65	B,C,D	2(105)
KDS10-PE	24-6	CU	2	11-15	—	—	B,C,D	2(105)
KDS10-PE/SO	24-6	CU	2	11-15	—	—	B,C,D	2(105)
FRONT2.5H	12-30	CU	2	3.5 to 4.5	300	10	B,D	2 (105),4
FRONT2.5H-SA5	12-30	CU	2	3.5 to 4.5	300	10	B,D	2 (105),4
FRONT1.5-V-3.81	14-30	CU	2	2.5	300	10	B,D	2 (105),4
FRONT2.5H-SA10	12-30	CU	2	3.5 to 4.5	300	10	B,D	2 (105),4



FRONT2.5V	12-30	CU	2	3.5 to 4.5	300	10	B,C	2 (105),4
FRONT2.5V-SA5	12-30	CU	2	3.5 to 4.5	300	10	B,D	2 (105),4
FRONT2.5V-SA10	12-30	CU	2	3.5 to 4.5	300	10	B,D	2 (105),4
EP-FRONT 25-H/SA10	12-30	CU	2	3.5 to 4.5	300	10	B,D	2 (105),4
EP-FRONT2.5-H(2)	12-30	CU	2	3.5 to 4.5	300	10	B,D	2 (105),4
FRONT4H-6.35	10-24	CU	2	4.5 to 5.5	300	30	B,D	2 (105),4
FRONT4V-6.35	10-24	CU	2	4.5 to 5.5	300	30	B,D	2 (105),4
FRONT4H-7.62	10-24	CU	2	4.5 to 5.5	300	30	B,D	2 (105),4
FRONT4V-7.62	10-24	CU	2	4.5 to 5.5	300	30	B,D	2 (105),4
<b>Note:</b> (2)Followed by SA10/4BK.								
<b>Note:</b> #Denotes optional suffix -5.08.								
UK-FRONT4	10-24	CU	2	6.5-7	300	30	B,D	2 (105),4
UK-FRONT4-PE	10-24	CU	2	6.5-7	—	—	B,D	2 (105),4
FRONT-SFL2.5(1)	12-30	CU	2	6.5-7	300	4	B,D	2 (105),4
FREC2.5/X-ST-5.0	30-12	CU	2	5-7	300	10	B,D	2 (105),4
IDC0.3/X-3.81	22-28	CU	2	N/A	300	5	B,C	2 (130),4
USEN14	2-20	CU	2	35-40	600	16	B,C	2 (105),4
USEN18	2-20	CU	2	35-40	600	63	B,C	2 (105),4
QT1.5, -BU, -MT, -TG	16-22	CU	2	N/A	600	10	B,C	2(130)
QT1.5-PE	16-22	CU	2	N/A	600	10	B,C	2(130)
QT1.5-TWIN, -BU	16-22	CU	2	N/A	600	10	B,C	2(130)
QT1.5-TWIN-PE	16-22	CU	2	N/A	N/A	N/A	B,C	2(130)
QT2.5	14-18	CU	2	N/A	600	15	B,C	2 (105),4
QT2.5-BU, -MT	14-18	CU	2	N/A	600	15	B,C	2 (105),4
QT2.5-PE	14-18	CU	2	N/A	600	15	B,C	2 (105),4
QT2.5-TG	14-18	CU	2	N/A	600	15	B,C	2(105)

QT2.5-TWIN	14-18	CU	2	N/A	600	15	B,C	2 (105),4
QT2.5-TWIN-BU	14-18	CU	2	N/A	600	15	B,C	2 (105),4
QT2.5-TWIN-PE	14-18	CU	2	N/A	600	15	B,C	2 (105),4
QTU1.5/4	(@)	CU	2	5-7	600	10	B,C	2(105)
QTU1.5/4-PE	(@)	CU	2	5-7	N/A	N/A	B,C	2(105)
QTTUB1.5/4	(@)	CU	2	5-7	600	10	B,C	2(105)
QTU2.5/4	(@@)	CU	2	5-7	600	15	B,C	2(105)
QTU2.5/4-PE	(@@)	CU	2	5-7	N/A	N/A	B,C	2(105)
QTTUB2.5/4	(@@)	CU	2	5-7	600	15	B,C	2(105)
<b>Note:</b> (@) - Input side (IDC) wire range is No. 24-16 AWG Cu. str.; Output side (pressure screw) is rated No. 26-10 AWG Cu. sol/str.								
<b>Note:</b> (@@) - Input side (IDC) wire range is No. 24-14 AWG Cu. str.; Output side (pressure screw) is rated No. 26-10 AWG Cu. sol/str.								
FK-MPT 0.5(A)	20-28	CU	2	N/A	300	4	B,C	2(105)
FK-MPT 0.5(B)	—	CU	1	N/A	300	4	B,C	2(105)
CPT0.5/X-M-3.5	—	CU	1	N/A	300	4	B,C	2(105)
<b>Note:</b> (A) Followed by /1 or /2-digit number, w/wo -ST, followed by -3.5 w/wo -H.								
<b>Note:</b> (B) Followed by /1 or /2-digit number, followed by -IC or -ICV and -3.5.								

(1) Followed by suffixes /D32, /F32, /F48 with or without /ZB, or /ZD.

#(1) With or without prefix U.

#(2) Followed by suffix -FS, -FS/FS, -LOe, -LOe/LOe, -LOeR, may be followed by suffix L/B1, L/C1, may be followed by kri.

#(3) May be followed by SMDBK, -3.5, -3.81, -5.08, -6.35, -9.5.

#(4) Followed by 2 or 3, followed by suffix H, S, SH, V, VS with or without -7.5.

#(5) Followed by suffix FS, FSI.

#(6) Max. rating 15A (factory), 10A (field).

Cat. No.	Wire Size	Wire Type	FW	TQ Lb In.	V	A	UG	CA
QTS1.5/4 (1)	(1)	CU	2	N/A	600	10	B,C	2(105)
QTS1.5/4-PE (1)	(1)	CU	2	N/A	600	10	B,C	2(105)
QTS2.5/4 (2)	(2)	CU	2	N/A	600	15	B,C	2(105)
QTS2.5/4-PE (2)	(2)	CU	2	N/A	600	15	B,C	2(105)

Note: (1) Input side (IDC) wire range is No. 24-16 AWG Cu. Str.; Output side Cage Spring wire range is No. 24-10 AWG Cu. sol/str.

Note: (2) Input side (IDC) wire range is No. 18-14 AWG Cu. Str.; Output side Cage Spring wire range is No. 24-10 AWG Cu. sol/str.

Cat. No.	Wire Size	Wire Type	FW	TQ Lb In.	V	A	UG	CA

FK-MC0.5(1)	28-20	CU	2	N/A	150	4	B	2(105)
MC0.5(2)	—	CU	1	N/A	150	4	B	2(105)
MCD0.5	—	CU	1	N/A	125	4	B	2(105),9
MCDV0.5	—	CU	1	N/A	125	4	B	2(105),9
QC0.75 (2)	18-22	CU	2	N/A	300	7	B,C	2(105),4
QC1(2)	20-16	CU	2	N/A	300	10	B,C	2(105),4

(1) Followed by /1 or /2 digit numbr, followed by -ST and -2.5.

(2) Followed by /1 or 2-digit number, -ST, -ST-BUS or -STF, and by suffix -5.05.

(8) Followed by /1 or /2 digit numbr, followed by -G and -2.5.

(9) Followed by /1 or /2 digit numbers, followed by suffix -G1-2.5.

Cat. No.	Wire Size	Wire Type	FW	TQ Lb In.	V	A	UG	CA
ME17.5 (1), ME22.5(1)	30-12	CU	2	5-7 (2)	300	8	B,D	2(105)
				4 (3)				

(1) Followed by suffixes UT (L or R) BUS/5, or UT (L or R) BUS/10, and by suffixes OT-MSTBO, or OT-MKDSO, may be followed by AA to ZZ inclusive.

(2) Top terminals (MSTBT2.5, MKDSO2.5 blocks)

(3) Bottom terminals (MKCVR1.5 block)

Cat. No.	Wire Size	Wire Type	FW	TQ Lb In.	V	A	UG	CA
ST2.5	28-12	CU	2	N/A	600	20	B,C	2(105),4
ST2.5-TWIN-PE	28-12	CU	2	N/A	600	20	B,C	2(105),4
ST2.5-QUATTRO, -U	28-12	CU	2	N/A	600	20	B,C	2(105),4
ST2.5-DIO/L-R, -DIO/R-L	28-12	CU	2	N/A	600	1	B,C	2(105)
ST2.5-TWIN-DIO/L-R, -DIO/R-L	28-12	CU	2	N/A	600	20(1)	B,C	2(105)
ST2.5-QUATTRO- DIO/L-R, -DIO/R-L	28-12	CU	2	N/A	600	20(1)	B,C	2(105)
STTB2.5-LA24, -LA60	28-12	CU	2	N/A	600	20	B,C	2(105)
STTB2.5	28-12	CU	2	N/A	600	20	B,C	2(105),4
STTB2.5-PV	28-12	CU	2	N/A	600	20	B,C	2(105),4
ST2.5-PE	28-12	CU	2	N/A	N/A	N/A	B,C	2(105),4
ST2.5-PCB, ST2.5-PCBV, followed by /1 or /2 digit No. , and by -G-5.2	—	CU	1	N/A	300	15	B,C	2(105)
ST2.5-TWIN	28-12	CU	2	N/A	N/A	N/A	B,C	2(105),4
ST2.5-QUATTRO-PE	28-12	CU	2	N/A	N/A	N/A	B,C	2

								(105),4
STS2.5-TWIN, STS2.5, -BU	28-12	CU	2	N/A	600	20	B,C	2 (105),4
STS2.5-QUATTRO								
STS2.5-TWIN-PE, STSA.5PE	28-12	CU	2	N/A	—	—	B,C	2 (105),4
STS2.5-QUATTRO-PE								
STTB2.5-DIO/U-O	28-12	CU	2	N/A	600	20(1)	B,C	2 (105),4
STTB2.5-DIO/O-U	28-12	CU	2	N/A	600	20(1)	B,C	2 (105),4
STTB2.5-DIO/UL-UR	28-12	CU	2	N/A	600	20(1)	B,C	2 (105),4
STTB2.5-2DIO/O-UL/UR-UL	28-12	CU	2	N/A	600	20(1)	B,C	2 (105),4
STTB2.5-DIO/O-UL/O-UR	28-12	CU	2	N/A	600	20(1)	B,C	2 (105),4
STTB2.5-LA230	28-12	CU	2	N/A	600	20	B,C	2 (105),4
SP2.5/X, SPB2.5/X, w/wo Suffixes /1-L, /1-M, /1-R	28-12	CU	2	N/A	300/600	20(2)	B,D	2(105)
SPDB2.5/X w/wo Suffixes /1- L, /1-M, /1-R	28-12	CU	2	N/A	300/600	20(2)	B,D	2(105)
ST2.5/1P	28-12	CU	2	N/A	300/600	20(2)	B,D	2(105)
ST2.5QUATTRO/2P, -BU	28-12	CU	2	N/A	300/600	20(2)	B,D	2(105)
ST2.5-QUATTRO/4P, BU	N/A	CU	1	N/A	600	20(2)	B,D	2(105)
STTB2.5/2P	28-12	CU	2	N/A	300/600	20(2)	B,D	2(105)
STTB2.5/2P-PV	28-12	CU	2	N/A	300/600	20(2)	B,D	2(105)
STTB2.5/2P-DIO/O-U	28-12	CU	2	N/A	300/600	20(2)	B,D	2(105)
ST2.5-3L	28-12	CU	2	N/A	300	20	B,D	2 (105),4
ST2.5-3PV	28-12	CU	2	N/A	300	20	B,D	2 (105),4
ST2.5-3PE	28-12	CU	2	N/A	N/A	N/A	B,D	2 (105),4
ST2.5-PE/3L	28-12	CU	2	N/A	600	20	B,D	2 (105),4
STTB2.5-PE	28-12	CU	2	N/A	N/A	N/A	B,D	2 (105),4
ST2.5/1P-PE	28-12	CU	2	N/A	300/600	20(2)	B,D	2(105)
ST2.5-QUATTRO/2P-PE	28-12	CU	2	N/A	300/600	20(2)	B,D	2(105)
ST2.5-QUATTO/4P-PE	N/A	CU	1	N/A	N/A	N/A	B,D	2(105)
STTB2.5/2P-PE	28-12	CU	2	N/A	300/600	20(2)	B,D	2(105)
ST2.5-PE/L/L,	28-12	CU	2	N/A	300(3)	20(3)	B,C	2 (105),4
ST2.5-PE/L/N								
ST2.5-MT	28-12	CU	2	N/A	600	16	B,C	2 (105),4

ST2.5-TWIN-MT	12-26	CU	2	N/A	600	16	B,C	2 (105),4
ST2.5-QUATTRO-MT	28-12	CU	2	N/A	600	16	B,C	2 (105),4
(3) Ampere and voltage rating not applicable for lower level grounding terminals.								
STTBS2.5	28-12	CU	2	N/A	300	20	B,D	2 (105),4
STTBS2.5-PV	28-12	CU	2	N/A	300	20	B,D	2 (105),4
STS2.5-MT	28-12	CU	2	N/A	300	16	B,D	2 (105),4
STS2.5-TG	28-12	CU	2	N/A	300	16	B,D	2 (105),4
ST2.5-TG	28-12	CU	2	N/A	300	16	B,D	2 (105),4
ST2.5-TWIN-TG	28-12	CU	2	N/A	300	16	B,D	2 (105),4
ST2.5-QUATTRO-TG	28-12	CU	2	N/A	300	16	B,D	2 (105),4
STTB2.5-L/N	28-12	CU	2	N/A	300	20	B,D	2 (105),4
STTB2.5-PE/L	28-12	CU	2	N/A	300	20	B,D	2 (105),4
					(3)	(3)		
STTB2.5-PE/N	28-12	CU	2	N/A	300	20	B,D	2 (105),4
					(3)	(3)		
STI2.5, -BU	28-12	CU	2	N/A	600	20	B,D	2 (105),4
STI2.5-PE	28-12	CU	2	N/A	N/A	N/A	B,C	2 (105),4
STI2.5-L	28-12	CU	2	N/A	150/	20	B,C	2 (105),4
					/300	/10		
STI2.5-L/L	28-12	CU	2	N/A	150	20	B,C	2 (105),4
					/300	/10		
STI2.5-L/N	28-12	CU	2	N/A	150	20	B,C	2 (105),4
					/300	/10		
STI2.5-PE/L/L	28-12	CU	2	N/A	150	20	B,C	2 (105),4
					/300	/10		
					(3)	(3)		
STI2.5-PE/L/N	28-12	CU	2	N/A	150	20	B,C	2 (105),4
					/300	/10		
					(3)	(3)		
STI2.5-PE/L/NT	28-12	CU	2	N/A	150	20	B,C	2 (105),4

					(3)	(3)		
STI2.5-PE/L/NT	28-12	CU	2	N/A	150	20	B,C	2 (105),4
					/300	/10		
					(3)	(3)		
STI2.5-PE/NTB	26-12	CU	2	N/A	150	20	B,C	2 (105),4
					(3)	(3)		
STI2.5-PE/NTB	28-12	CU	2	N/A	150	20	B,C	2 (105),4
					/300	/10		
					(3)	(3)		
STTBS2.5-PE	28-12	CU	2	N/A	N/A	N/A	B,D	2 (105),4
STTB2.5-TWIN	28-12	CU	2	N/A	300	20	B,D	2 (105),4
STTB2.5-TWIN-PV	28-12	CU	2	N/A	300	20	B,D	2 (105),4
STTB2.5-TWIN-PE	28-12	CU	2	N/A	N/A	N/A	B,D	2 (105),4
SC2.5, SC2.5-RZ, SC2.5/1-L, SC2.5-NS/1-L	26-12	CU	2	N/A	300	20	B,C	2 (105),4
ST2.5/2P-PE	N/A	CU	1	N/A	N/A	N/A	B,C	2(105)
ST2.5/2P	N/A	CU	1	N/A	600	20	B,C	2(105)
ST2.5-TWIN/1P	28-12	CU	2	N/A	600	20	B,C	2 (105),4
ST2.5-TWIN/1P-PE	28-12	CU	2	N/A	N/A	N/A	B,C	2 (105),4
ST2.5-TWIN-MT/1P	28-12	CU	2	N/A	600	20	B,C	2 (105),4
ST2.5-TWIN-TG/1P	28-12	CU	2	N/A	600	20	B,C	2 (105),4
ST2.5-4L/1P	28-12	CU	2	N/A	300	10	B,C	2 (105),4
ST2.5-4L/2P, -4L/2P-Z	28-12	CU	2	N/A	300	10	B,C	2 (105),4
ST2.5-PE/3L/1P	28-12	CU	2	N/A	300/NA	10/NA	B,C	2 (105),4
CP2.5-4L, -4L-Z	28-12	CU	2	N/A	300	10	B,C	2 (105),4
<b>Note:</b> (1) 1 ampere for current paths with diode.								
<b>Note:</b> (2) 5A max. at 600V; 10A max. at 300V general industrial use.								
<b>Note:</b> (3) Ampere/voltage rating not applicable for lower level grounding terminals.								
DK-BIC-35	2-20	CU	2	40	600	100	B,C	2 (105),4
AKG4-GNYE	22-12	CU	2	7	—	—	B,C	2 (105),4
AK4, AKG4-BK	22-12	CU	2	7	300	20	B,C	2 (105),4

AKG4-BU									
AKG16-BK,	6-18	CU	2	25	300	65	B,C	2 (105),4	
AKG16-BU									
AKG16-GNYE	6-18	CU	2	25	—	—	B,C	2 (105),4	
AKG35-BK,	2-18	CU	2	50	300	115	B,C	2 (105),4	
AKG35-BU									
AKG35-GNYE	2-18	CU	2	50	—	—	B,C	2 (105),4	
QC0.5(1)-ST-3.81	24-20	CU	2	N/A	300	6	B,C	2 (105),4	
QC0.5(1)-STF-3.81	24-20	CU	2	N/A	300	6	B,C	2 (105),4	
<b>Note:</b> (1) Followed by /1 or /2-digit number.									
ST6, STS6, w/Suffixes -BU, -TWIN	24-8	CU	2	N/A	600	50	B,C	2 (105),4	
ST6, STS6, w/ Suffixes -PE, -TWIN-PE	24-8	CU	2	N/A	N/A	N/A	B,C	2 (105),4	
ST10, -BU	16-6	CU	2	N/A	600	65	B,C	2(105)	
ST10-PE	16-6	CU	2	N/A	—	—	B,C	2(105)	
ST16, -BU	16-4	CU	2	N/A	600	65	B,C	2(105)	
ST16-PE	16-4	CU	2	N/A	—	—	B,C	2(105)	
ST35, -BU	14-2	CU	N/A	2	600	115	B,C	2 (105),4	
ST35-PE	14-2	CU	N/A	2	N/A	N/A	B,C	2 (105),4	
PC6(1), PCU6(1)	20-8	CU	2	11-15	600	50	B,C	2 (115),4	
PC6(2), PCV6(2)	—	CU	1	—	300	50	B,C	2(115)	
(1) Followed by /1-digit number, and by Suffix -ST, -STD, -STF, -SH, followed by -10.16, w/wo suffix RAE.									
(2) Followed by /1-digit number, and by Suffix -G or -GF, followed by -10.16, with or without Suffix CODED.									
FRONT-ZFL	24-16	CU	2	N/A	300	4	B,C	2	
1.5/D32								(120),	
ME17.5,	12-30	CU	1 (a)	5-7	300	20	B,C	2	
ME22.5, ME35								(105)	
ME45 suffixes UT (w/wo L				(Lower),					
or R), UT/FE, F-UT (w/wo L				4.0					
or R), or F-UTG (w/wo L or				(Upper),					
R), foll. by suffixes BUS/5,									
BUS/10, BUS/5+2,									
BUS/10+2, w/wo									
suffixes AA-ZZ incl.									
ME17.5, ME22.5, ME35,	12-30	CU	1	5-7	300	20	B,C	2(105)	

			(a)					
ME45 suffixes OT-MSTBO, OT-MKDSO, OT-1MSTBO, OT-MSTBO-SET or OT- MKDSO-SET w/wo suffixes AA-ZZ incl.				(Lower) 4.0 (Upper)				
ME MAX6.2 SC(1)	12-30	CU	2	5-7	300	8	B,D	2 (105),4
ME MAX 6.2 SP(1)	12-24	CU	2	—	300	8	B,D	2 (105),4
ME MAX17.5(2)	12-30	CU	2	5-7	300	15	B,D	2 (105),4
ME MAX22.5(2)	12-30	CU	2	5-7	300	15	B,D	2 (105),4
ME MAX35(2)	12-30	CU	2	5-7	300	15	B,D	2 (105),4
ME MAX45(2)	12-30	CU	2	5-7	300	15	B,D	2 (105),4
ME6.2 TBUS-2(3)	—	CU	1	—	150	8	B,D	2(105)
ME17.5 TBUS(3)	—	CU	1	—	150	8	B,D	2(105)
ME22.5 TBUS(3)	—	CU	1	—	150	8	B,D	2(105)
<b>Note:</b> (1) Followed by -4-4 or -TBUS4-4, followed by KMGY or AA-ZZ inclusive.								
<b>Note:</b> (2) Followed by U-U1, GU-U1, 2-2, G2-2, 3-3, G3-3, FG3-3, or SFG3-3, followed by -KMGY or AA-ZZ inclusive.								
<b>Note:</b> (3) Followed by 1.5/5-ST-3.81, followed by -KMGY or AA-ZZ inclusive.								
PT1.5 f/b /1 or /2 digit No., by suffix -5.0 and by -H or -V	26-12	CU	2	4.0	300	15(1)	B,D	2 (105),4
PT1.5 f/b by /1 or /2digit No., by suffix -PVH and by -5.0	26-12	CU	2	N/A	300	15(1)	B,D	2 (105),4
PST1.3 f/b /1 or /2digit No., and by -5.0	—	CU	1	N/A	300	16	B,D	2 (105)
PTSA1.5/X-3.5 w/wo -F or -Z	24-16	CU	2	N/A	300	2	B,D	2 (105), 4
PTSA0.5/X-2.5 followed by -F, or -Z, w/wo -Hat	26-20	CU	2	N/A	300	2	B,D	2 (105),4
PT1.5/X-3.5-H, -V	26-16	CU	2	2.2	300	10	B,D	2 (105),4
PT1.5/X-PH-3.5	26-16	CU	2	2.2	300	10	B,D	2 (105),4
PT1.5/X-PH-3.5-A	26-16	CU	2	2.2	300	10	B,D	2 (105),4



PT1.5/X-PVH-3.5	26-16	CU	2	2.2	300	10	B,D	2 (105),4
PT1.5/X-PVH-3.5-A	26-16	CU	2	2.2	300	10	B,D	2 (105),4
PT2.5/X-5.0-H, -V	20-12	CU	2	4.4	300	20	B,D	2 (105),4
PST1.0/X-3.5	—	CU	1	—	300	10	B,D	2(105),
UT2.5, UT2.5/1P	26-12(2)	CU	2	5-7	600	20	B,C	2 (105),4
UT2.5-PE, UT2.5/1P-PE	26-12(2)	CU	2	5-7	N/A	N/A	B,C	2 (105),4
UT4, UT4-MTD	26-10(3)	CU	2	5-7	600	30(1)	B,C	2 (105),4
UT4-MT. -TG, -MT-P/P,	26-10(3)	CU	2	5-7	600	16	B,C	2 (105),4
-TG-P/P, -HEDI, -HEDI-P/P,								
UT4-HESI(5x20),	26-10(3)	CU	2	5-7	600	6.3	B,C	2 (105),4
-HESILED24(5x20),								
-HESILED50(5x20),								
-HESILED60(5x20),								
-HESILA250(5x20)								
UT4-MTD-DIO/L-R,	26-10(3)	CU	2	5-7	600	1.0	B,C	2 (105),4
or/R-L(w/wo -P/P)								
UT4-PE, UT4-PE/S,	26-10(3)	CU	2	5-7	N/A	N/A	B,C	2 (105),4
UT4-MTD-PE								
UT4-TWIN	26-10(3)	CU	2	5-7	150	30	B,C	2 (105),4
UT4-TWIN-PE	26-10(3)	CU	2	5-7	N/A	N/A	B,C	2 (105),4
UT4-QUATTRO	26-10(3)	CU	2	5-7	150	30	B,C	2 (105),4
UT4-QUATTRO-PE	26-10(3)	CU	2	5-7	N/A	N/A	B,C	2 (105),4
UT2.5-TWIN	26-12(2)	CU	2	4-5	150	20	B,C	2 (105),4
UT2.5-TWIN-PE	26-12(2)	CU	2	4-5	N/A	N/A	B,C	2 (105),4
UT2.5-QUATTRO	26-12(2)	CU	2	4-5	150	20	B,C	2 (105),4
UT2.5-QUATTRO-PE	26-12(2)	CU	2	4-5	N/A	N/A	B,C	2 (105),4
UT4-TWIN	26-10(3)	CU	2	5-7	150	30	B,C	2 (105),4
UT4-TWIN-PE	26-10(3)	CU	2	5-7	N/A	N/A	B,C	2 (105),4
UT4-QUATTRO	26-10(3)	CU	2	5-7	150	30	B,C	2 (105),4

UT4-QUATTRO-PE	26-10(3)	CU	2	5-7	N/A	N/A	B,C	2 (105),4
UT6	24-8(4)	CU	2	13-15	600	50	B,C	2 (105),4
UT6-PE	24-8(4)	CU	2	13-15	N/A	N/A	B,C	2 (105),4
UT10	20-6(4)	CU	2	13-15	600	65	B,C	2 (105),4
UT10-PE	20-6(4)	CU	2	13-15	N/A	N/A	B,C	2 (105),4
UTTB4, UTTB4-PV	26-10(3)	CU	2	5-7	300	30	B,C	2 (105),4
UTTB4-PE	26-10(3)	CU	2	5-7	N/A	N/A	B,C	2 (105),4
<b>Note:</b> (1) 40A max. for factory wiring								
<b>Note:</b> (2) Additional multiple wire combination rating of two No. 16-26 AWG Cu. stranded wires (same size only) for field and factory wiring.								
<b>Note:</b> (3) Additional multiple wire combination rating of two No. 14-26 AWG Cu. stranded wires (same size only) for field and factory wiring.								
<b>Note:</b> (4) Additional multiple wire combination rating of two No. 12-24 AWG Cu. stranded wires (same size only) for field and factory wiring.								
PC16, DFK-PC16 foll. by /1 digit No., -ST, -STF, -STF-SH, -STGF, -STGF-SH, -10.16, w/wo -RAE	20-6	CU	2	15	600	55	B,C	2 (120),4
IPC16, DFK-IPC16 foll. by /1 digit No., -ST, -STF, -STF-SH, -STGF, -STGF-SH, -10.16, w/wo -RAE	20-6	CU	2	15	600	55	B,C	2 (120),4
PC6-16, DFK-PC6-16 foll. by /1 digit No., by -G, -G1, -GU, -G1U, -GF, -G1F, -GFU, -G1FU w/wo -SH, and -10.16	—	CU	1	—	600300	555	DB,C	2 (120),4
PCV6-16, DFK-PC6-16 foll. by /1 digit No., by -G, -G1, -GU, -G1U, -GF, -G1F, -GFU, -G1FU w/wo -SH, and -10.16	—	CU	1	—	600300	555	DB,C	2 (120),4
IPC16, DFK-IPC16 foll. by /1 digit No., by -G, -GU, -GF, -GFU, w/wo -SH, and -10.16	—	CU	1	—	600300	555	DB,C	2 (120),4
IPCV16, DFK-IPCV16 foll. by /1 digit No. by -G, -GU, -GF, -GFU, w/wo -SH, and -10.16	—	CU	1	—	600300	555	DB,C	2 (120),4
QTC1.5, -MT, -TG, -QUATTRO, -TWIN, /1P	24-16	CU	2	N/A	600	10	B,C	2  (120),4
QTTCB1.5, -DIO/O-U, -PV, /2P, /2P-PV	24-16	CU	2	N/A	600	10	B,C	2  (120),4
QTC1.5-PE, -QUATTRO-PE, -TWIN-PE, /1P-PE	24-16	CU	2	N/A	N/A	N/A	B,C	2  (120),4
QTTCB1.5PE, QTTCB1.5/2P-PE	24-16	CU	2	N/A	N/A	N/A	B,C	2 (120),4
QTC2.5, QTC2.5-TWIN	20-14	CU	2	N/A	600	15	B,C	2 (105),4
QTC2.5-PE, QTC2.5-TWIN-PE	20-14	CU	2	N/A	N/A	N/A	B,C	2 (105),4

QTC2.5-HESI (5X20), -HESILED 24, -HESILED 60, -HESILA 250	20-14	CU	2	N/A	300	15	B,C	2 (105),4
QTC2.5-HEDI, -MT, -TG	20-14	CU	2	N/A	300	15	B,C	2 (105),4
ABS3/2, ABS3/6	24-14	CU	2	4,5-5.3	300	15	B,C	2 (105),4
DT2.5-PE,	24-12	CU	2	—	—	—	B,C	2 (105),4
DT2.5-QUATTRO-PE,								
DT2.5-TWIN-PE								
DT2.5, -TWIN,	24-12	CU	2	—	600	20	B,C	2 (105),4
-QUATTRO, all								
w/wo Suffixes								
-DIO/L-R, -DIO/R-L								
QTCS1.5,-BU, -TWIN	Input 24-26; Output 26-12	CU	2	N/A	600	10	B,C	2 (105),4
QTTCBS1.5-BU, -PV	Input 24-26; Output 26-12	CU	2	N/A	300	10	B,C	2 (105),4
QTCU1.5-BU, -TWIN	Input 24-26; Output 26-12	CU	2	5-7	600	10	B,C	2 (105),4
QTTCBU1.5-BU, -TWIN	Input 24-26; Output 26-12	CU	2	5-7	300	10	B,C	2 (105),4
QTCS1.5-PE	Input 24-26; Output 28-12	CU	2	N/A	N/A	N/A	B,C	2 (105),4
QTCS1.5-TWIN-PE	Input 24-26; Output 28-12	CU	2	N/A	N/A	N/A	B,C	2 (105),4
QTTCBS1.5-PE	Input 24-26; Output 28-12	CU	2	N/A	N/A	N/A	B,C	2 (105),4
QTCU1.5-PE	Input 24-26; Output 26-12	CU	2	5-7	N/A	N/A	B,C	2 (105),4
QTCU1.5-PE	Input 24-26; Output 26-12	CU	2	5-7	N/A	N/A	B,C	2 (105),4
QTTCBU1.5-PE	Input 24-26; Output 26-12	CU	2	5-7	N/A	N/A	B,C	2 (105),4
QTCS2.5/X, -BU, -TWIN	20-14 (Input); 28-10 (Output)	CU	2	N/A	600	15	B,C	2 (105),4
QCTS2.5-PE, -TWIN-PE	20-14 (Input); 28-10 (Output)	CU	2	N/A	N/A	N/A	B,C	2 (105),4
QTCU2.5/X, -BU, -TWIN	20-14 (Input); 26-10 (Output)	CU	2	5-7 (Input) N/A (Output)	600	15	B,C	2 (105),4

QTCU2.5/X-PE, -TWIN-PE	20-14 (Input); 26-10 (Output)	CU	2	5-7 (Input) N/A (Output)	N/A	N/A	B,C	2(105)
------------------------	--	----	---	-----------------------------------	-----	-----	-----	--------

All Cat. Nos. may be followed by a two to four character suffix (any combination of letters and/or numbers) designating nonelectrical variations such as color, customer identification, packaging or plating options.

/X One or two digit number.

(#) - feedthrough levels - 600; gndg. level-N/A.

(##) - feedthrough level - 30; gndg. level N/A.

All Cat. Nos. in reports dated 4-27-1977/3-31-1987/10-11-1993/10-11-1993/10-12-1993/10-13-1993 which provide pressure screw terminals may have Suffix H0L, H1L, SO1 or Z1L denoting combination Phillips/slotted head screws) added to end of Cat. No.

(a) - Field wiring for MSTBT2.5 or MKDSO2.5 terminals.

(1) 16A max. fro factory-wiring only.

(2) 5A max. at 600V (Limited VA, industrial use).



Marking: Company name or trademark  catalog and type designation.  
Last Updated on 2006-02-28

[Questions?](#)

[Notice of Disclaimer](#)

[Page Top](#)

[Copyright © 2006 Underwriters Laboratories Inc.®](#)

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Listed and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Designs and/or Listings (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from Underwriters Laboratories Inc." must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "Copyright © 2006 Underwriters Laboratories Inc.®"

An independent organization working for a safer world with integrity, precision and knowledge.

