

Rittal – The System.

Faster – better – everywhere.

▶ **Socket strip in a plastic housing – DK 7000.630**

Date : Apr 26, 2021

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



Socket strip in a plastic housing – DK 7000.630

created: 26.04.2021 build on www.rittal.com/uk-en



Product description

Description: 8-way socket strip for earthing-pin plug (type F, CEE 7/4) The strip may be mounted vertically on the enclosure frame or in the rear 482.6 mm (19") section. In the 482.6 mm (19") section, more than 2 U of space is required. The sockets are arranged at an angle of 45° so that angular connectors are also easily used. The connection cable is contacted in a terminal slot in the strip. The terminal slot has a separate cover and external terminals for separate earthing.

Material: Plastic

Supply includes: Connection cable
Assembly screws
2 serrated washers
Captive nuts M6, conductive
Nuts

Product description

Design: Without switch

Installation options: TE 7000, rear 482.6 mm (19") section (> 2 U)
TE 7000, vertically mounted on the frame

Type of electrical connection: Wire end ferrules

Rated voltage: 230 V AC

Rated current (max.): 16 A

Equipment (electrical): Number of sockets: 8
Jack/socket (type): D, earthing-pin (type F, CEE 7/3)
No. of sockets and type: 8 x earthing-pin, type F, CEE 7/3

Colour of socket: Black
Length of connection cable: 2 m

Connection cable (type):	H05VV-F3G1.5 with wire end ferrules
Packs of:	1 pc(s).
Weight/pack:	0.92 kg
Copper weight (kg per piece):	0
EAN:	4028177438569
Customs tariff number:	85369095
ETIM 7.0:	EC000330
ETIM 6.0:	EC000330
eCl@ss 8.0/8.1:	27142604
eCl@ss 6.0/6.1:	27142604
Product description:	DK-TS Socket strip, CEE 7/3 (type F), 8-way, 230 V, 16 A, LHD:
Approvals	
Certificates:	EAC
Declarations:	Declaration of conformity