


PRODUCT-DETAILS

# ZLS908

## ZLS908 Sockets



### General Information

Extended Product Type	ZLS908
Product ID	2CCA183030R0001
EAN	7612271413965
Catalog Description	ZLS908 Sockets
Long Description	SMISLINE TP 8-module socket for the 125A system, length 144 mm (includes base and cover). The pluggable socket system is completely finger safe (IP2XB) together with the socket end piece

### Technical

Standards	IEC/EN 61439-6
Rated Operational Voltage	690/1000 V AC/DC
Options Provided	ZLS
Model Number	Flat

### Environmental

RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
Environmental Information	2CCY451206D0201

### Dimensions

Product Net Width	111 mm
Product Net Height	144 mm
Product Net Depth / Length	34 mm
Product Net Weight	92 g

### Container Information

Package Level 1 Units	carton 1 piece
Package Level 1 Width	150 mm
Package Level 1 Height	124 mm
Package Level 1 Depth / Length	417 mm
Package Level 1 Gross Weight	222 g
Package Level 1 EAN	7612271413965

### Ordering

Minimum Order Quantity	1 piece
Customs Tariff Number	85389040
E-Number (Finland)	3210896
E-Number (Sweden)	2100366
E-Number (Switzerland)	809995155
Country of Origin	Switzerland (CH)

### Certificates and Declarations (Document Number)

Declaration of Conformity - CE	9AKK107991A9646
Environmental Information	2CCY451206D0201
Instructions and Manuals	9AKK107680A2315
RoHS Information	9AKK107991A9646

### Popular Downloads

Data Sheet, Technical Information	9AKK107492A6192
Instructions and Manuals	9AKK107680A2315
Dimension Diagram	9AKK107492A6192

### Classifications

ETIM 7	EC001522 - Busbar
ETIM 8	EC001522 - Busbar
EPLAN Catalog Tree	Electrical engineering / Protection devices / General
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
WEEE B2C / B2B	Business To Business
CN8	85389040
eClass	V11.0 : 27370303
Object Classification Code	W

---

## Categories

---

Low Voltage Products and Systems → Modular DIN Rail Products → Plug-in Distribution Systems Accessories → Accessories for Plug-in Distribution Systems 125A

