



PC ADAPTER USB A2 USB-ADAPTER (USB V2.0) FOR CONNECTING A PG/PC OR NOTEBOOK TO SIMATIC S7 VIA PROFIBUS OR MPI USB CABLE 5M INCLUDED MPI-KABEL 0,3M CAN BE USED UNDER WINXP/VISTA/ WINDOWS 7 32/64BIT

Transmission rate

Transmission rate

- at interface 1 / in accordance with PROFIBUS

9,6 kbit/s ... 12 Mbit/s

Interfaces

Number of electrical connections / at interface 1 / in accordance with PROFIBUS

1

Aantal interfaces / conform USB

1

Standard for interfaces / USB 2.0

Ja

Supply voltage, current consumption, power loss

Type spanning

DC

Type of power supply / optional external supply

Nee

Supply voltage

- from USB

5 V

Relative symmetrical tolerance

- at 5 V / with DC

5 %

Consumed current

- from USB

0,2 A

Werkelijk vermogensverlies

1 W

Permitted ambient conditions

Omgevingstemperatuur

- tijdens de werking

0 ... 60 °C

| | |
|---|----------------|
| • tijdens opslag | -40 ... +70 °C |
| • tijdens transport | -40 ... +70 °C |
| Relatieve luchtvochtigheid | |
| • at 30 °C / during the operating phase / maximum | 95 % |
| Beschermingsklasse IP | IP20 |
| Design, dimensions and weight | |
| Breedte | 58 mm |
| Hoogte | 26 mm |
| Diepte | 105 mm |
| Nettogewicht | 0,365 kg |
| Mounting type / 35 mm DIN rail mounting | Nee |
| Product properties, functions, components / general | |
| Number of plug-in cards in the same design / can be plugged in / per PC station | 1 |
| Product function / Port diagnostics | Ja |
| Standards, specifications, approvals | |
| Norm | |
| • voor EMC | 2004/108/EG |
| Geschiktheidsbewijs | |
| • EG-conformiteitsmerkteken | Ja |
| • C-Tick | Ja |
| letzte Änderung: | 21-jul-2014 |