

PRODUCT-DETAILS

# DS203NC B32 A30

## DS203NC B32 A30 Residual Current Circuit Breaker with Overcurrent Protection



### General Information

Extended Product Type	DS203NC B32 A30
Product ID	2CSR256140R1325
EAN	8012542077626
Catalog Description	DS203NC B32 A30 Residual Current Circuit Breaker with Overcurrent Protection
Long Description	DS203NC is a 3P+N residual current circuit breaker with overcurrent protection (RCBO) in four modules for the protection against short-circuit currents, overload, earth fault currents, indirect contacts, additional protection against direct contacts (30 mA versions).

### Technical

Standards	IEC 61009-1 IEC 61009-2-1 EN 61009-1 EN 61009-2-1
Tripping Characteristic	B
Type of Residual Current	A type
Rated Voltage ( $U_r$ )	400-415 V AC
Rated Operational Voltage	400 ... 415 V AC
Rated Insulation Voltage ( $U_i$ )	500 V
Rated Impulse Withstand Voltage ( $U_{imp}$ )	4 kV

Input Voltage Type	AC
Rated Current ( $I_n$ )	32 A
Rated Residual Current	30 mA
Rated Short-Circuit Capacity	(230 / 400 V AC) 6 kA
Rated Ultimate Short-Circuit Breaking Capacity ( $I_{cu}$ )	10 kA
Rated Conditional Short-Circuit Current ( $I_{nc}$ )	10 kA
Rated Service Short-Circuit Breaking Capacity, in % of $I_{cu}$ ( $I_{cs}$ )	6 kA
Leakage Current Type	A
Frequency (f)	50/60 Hz
Rated Frequency (f)	50/60 Hz
Power Loss	15.1 W
Power Supply Connection	Arbitrary
Energy Limiting Class	3
Electrical Endurance	10000 cycle
Mechanical Endurance	20000 cycle
Number of Poles	4
Number of Protected Poles	3
Operating Characteristic	Instantaneous
Overvoltage Category	III
Position of Neutral Terminals	Right
Earthing Switch Type	Undelayed
Release Type	B
Options Provided	None
Accessories Available	Yes
Connecting Capacity	Busbar 10 mm <sup>2</sup> Rigid 25 ... 25 mm <sup>2</sup> Flexible 25 ... 25 mm <sup>2</sup>
Rated Cross-Section	4 - Multi-Wired 1...25 mm <sup>2</sup> 1 - Solid-Core 25...25 mm <sup>2</sup>

## Environmental

Ambient Temperature	-25...55 °C
Ambient Air Temperature	Operation -25...55 °C
Degree of Protection	IP2X
Pollution Degree	2
RoHS Status	Following EU Directive 2011/65/EU
Environmental Information	refer to RoHS information

## Technical UL/CSA

Short-Circuit Current	0.03 A
-----------------------	--------

## Rating (SCCR)

## Dimensions

Width in Number of Modular Spacings	4
Product Net Width	0.071 m
Product Net Height	0.085 m
Product Net Depth / Length	0.069 m
Product Net Weight	0.480 kg
Built-In Depth (t <sub>2</sub> )	69 mm

## Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	0.076 m
Package Level 1 Height	0.096 m
Package Level 1 Depth / Length	0.073 m
Package Level 1 Gross Weight	0.530 kg
Package Level 1 EAN	8012542077626

## Ordering

Minimum Order Quantity	1 piece
Customs Tariff Number	85363030
E-Number (Finland)	3211119
Country of Origin	Italy (IT)

## Certificates and Declarations (Document Number)

CCC Certificate	2021980307001650
Declaration of Conformity - CE	9AKK106713A5597
Environmental Information	refer to RoHS information
Instructions and Manuals	9AKK106713A8790
RoHS Information	9AKK106713A8875

## Popular Downloads

Data Sheet, Technical Information	2CSC423030B0201
Instructions and Manuals	9AKK106713A8790

## Classifications

ETIM 7

EC000905 - Earth leakage circuit breaker

ETIM 8	EC000905 - Earth leakage circuit breaker
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
WEEE B2C / B2B	Business To Consumer
CN8	85363030
eClass	V11.0 : 27142207
Object Classification Code	F

## Accessories

Identifier	Description	Type	Quantity	Unit Of Measure
2CDS200912R0001	S2C-H6R Auxiliary Contact	S2C-H6R	1	piece
2CDS200922R0001	S2C-S/H6R Signal / Auxiliary Contact	S2C-S/H6R	1	piece
2CSS200910R0005	S2C-OVP1 Overvoltage release	S2C-OVP1	1	piece
2CSS200911R0002	S2C-UA 24 AC Undervoltage release	S2C-UA 24 AC	1	piece
2CSS200911R0003	S2C-UA 48 AC Undervoltage release	S2C-UA 48 AC	1	piece
2CSS200911R0004	S2C-UA 110 AC Undervoltage release	S2C-UA 110 AC	1	piece
2CSS200911R0005	S2C-UA 230 AC Undervoltage release	S2C-UA 230 AC	1	piece
2CSS200911R0006	S2C-UA 400 AC Undervoltage release	S2C-UA 400 AC	1	piece
2CSS200923R0001	SN201-IH Interface module with auxiliary contact	SN201-IH	1	piece
2CSS200924R0001	SN201-S Signal contact	SN201-S	1	piece
2CSS200933R0011	F2C-A1 Shunt trip	F2C-A1	1	piece
2CSS200933R0012	F2C-A2 Shunt trip	F2C-A2	1	piece
2CSS200993R0005	S2C-OVP2 Overvoltage release	S2C-OVP2	1	piece

## Categories

Low Voltage Products and Systems → Modular DIN Rail Products → Residual Current Devices RCDs → Residual Current Circuit Breakers with Overcurrent Protection RCBO

