

# PRODUCT DATASHEET SMART+ ZB FLEX 2P EXT RGB + W

SMART+ Flex RGBW | Flexible LED strips for indoor use with Zigbee technology

#### Areas of application

- General illumination



## Product benefits

- Splittable in three parts and extendable with SMART+ FLEX 2P EXTENSION
- Easy to install and use

#### **Product features**

- Flexible, self-adhesive RGBW strip with wireless smart lighting function
- RGB color control, approx. 16 million color options adjustable
- Adjustable color temperature via Tunable White: 2,000...6,500 K
- Dimmable
- Network protocol: ZigBee
- Lifetime: up to 20,000 h
- Controllable via compatible smart home system (gateway and app) or SMART+ Switch
- For full functionality, connection to a compatible smart home System (gateway and app) required



- Extendable up to 5 meters

## **TECHNICAL DATA**

## **Electrical data**

Nominal wattage	6.00 W
Nominal voltage	220240 V
Mains frequency	5060 Hz
Nominal current	430.000 mA
Protection class	11
Operating mode	External LED driver

## Photometrical data

Luminous flux	500 lm
Total luminous flux of contained light sources	920 lm
Luminous efficacy	83 lm/W
Color temperature	20006500 K
Light color (designation)	RGBW
Color rendering index Ra	80
Standard deviation of color matching	≤6 sdcm
Beam angle	120 °

# **Dimensions & Weight**

Length	1200.00 mm
Width	12.00 mm
Height	3.00 mm
Product weight	65.00 g



## Materials & Colors

Product color	Transparent
Housing color	White
Body material	Plastic
Cover material	Polycarbonate (PC)

Mercury content	0.0 mg

#### **Application & Mounting**

Ambient temperature range	-20+40 °C	
Temperature range at storage	-20+80 °C	
Type of protection	IP20	
Dimmable	Yes	
Type of dimming	ZIGBEE	
Mounting type	Surface	
Mounting location	All surfaces	
Application environment	Indoor	
LED module replaceable	Not replaceable	
With light source	Yes	

## Lifespan

Lifespan L70/B50 at 25 °C	20000 h	
Number of switching cycles	1000000	

## Certificates & Standards

Standards	CE
Additional product data	
Product remark	Reset settings to default by switching the product on for five seconds and off for five seconds and repeating this five times.

## **EQUIPMENT / ACCESSORIES**

- Control via app requires LIGHTIFY system (app and gateway) or other compatible Smart home system

- Power supply included (except extension version of product)

## DOWNLOAD DATA

	Documents and certificates
PDF	User instruction
PDF	Declarations Of Conformity CE

#### LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075208612	Folding box 1	61 mm x 190 mm x 154 mm	200.00 g	1.78 dm³
4058075212770	Shipping box 4	327 mm x 202 mm x 138 mm	950.00 g	9.12 dm³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.