

## PRODUCT DATASHEET

### P MR11 35 36 ° 4.2 W/4000 K GU4

PARATHOM® MR11 12 V | Low-voltage LED reflector lamps MR11 with retrofit pin base



#### Areas of application

- Shops and exhibition rooms
- Domestic applications
- Commercial applications
- Accent lighting
- Outdoor use in suitable outdoor luminaires only

#### Product benefits

- Quick, simple and safe replacement without rewiring
- Design, dimensions, luminous flux comparable to an incandescent or halogen lamp
- Low maintenance costs thanks to long lifetime
- No UV and near-IR radiation in the light beam
- Compatible with many common conventional and electronic control gears (see also compatibility list)
- Instant 100 % light, no warm-up time

#### Product features

- LED alternative to low voltage halogen lamps
- High color consistency:  $\leq 6$  SDCM
- Not dimmable
- Base: GU4



- Lamp made of glass
- Good quality of light; color rendering index  $R_a \geq 80$
- Lifetime: up to 15,000 h


---

**TECHNICAL DATA****Electrical data**

|  |          |
|--|----------|
| Nominal wattage                          | 4.2 W    |
| Construction wattage                     | 4.20 W   |
| Nominal voltage                          | 12 V     |
| Claimed equiv. conventional lamp power   | 35 W     |
| Nominal current                          | 500 mA   |
| Type of current                          | AC       |
| Inrush current                           | < 18 A   |
| Operating frequency                      | 50/60 Hz |
| Mains frequency                          | 50/60 Hz |
| Max. lamp no. on circuit break. 10 A (B) | 40       |
| Max. lamp no. on circuit break. 16 A (B) | 50       |
| Power factor $\lambda$                   | > 0.50   |

**Photometrical data**


|   |                     |
|---|---------------------|
| Luminous intensity                      | 650 cd              |
| Luminous flux                           | 360 lm              |
| Nominal useful luminous flux 90°        | 360 lm              |
| Luminous efficacy                       | 85 lm/W             |
| Lumen main.fact.at end of nom.life time | 0.70                |
| Light color (designation)               | Cool White          |
| Color temperature                       | 4000 K              |
| Color rendering index Ra                | ≥80                 |
| Light color                             | 840                 |
| Standard deviation of color matching    | ≤6 sdc <sub>m</sub> |
| Rated peak intensity                    | 650 cd              |
| Rated LLMF at 6,000 h                   | 0.80                |
| Flickering metric (Pst LM)              | 1.0                 |
| Stroboscope effect metric (SVM)         | 0.4                 |



### Light technical data

|                     |          |
|---------------------|----------|
| Beam angle          | 36 °     |
| Warm-up time (60 %) | < 0.50 s |
| Starting time       | < 0.5 s  |

### Dimensions & Weight



|                  |          |
|------------------|----------|
| Overall length   | 38.00 mm |
| Diameter         | 35.00 mm |
| Maximum diameter | 35 mm    |
| Product weight   | 22.00 g  |

### Temperatures & operating conditions

|                                      |              |
|--------------------------------------|--------------|
| Ambient temperature range            | -20...+40 °C |
| Maximum temperature at tc test point | 85 °C        |

### Lifespan

|  |                       |
|--|-----------------------|
| Lifespan                                     | 15000 h <sup>1)</sup> |
| Number of switching cycles                   | 100000                |
| Lumen maintenance at end of service lifetime | 0.70                  |
| Rated lamp survival factor at 6,000 h        | ≥ 0.90                |

1) L70/B50

**Additional product data**

|                             |        |
|-----------------------------|--------|
| Base (standard designation) | GU4    |
| Mercury content             | 0.0 mg |

**Capabilities**

|          |    |
|----------|----|
| Dimmable | No |
|----------|----|

**Certificates & Standards**

|  |                |
|--|----------------|
| Energy efficiency class                      | F 1)           |
| Energy consumption                           | 5.00 kWh/1000h |
| Type of protection                           | IP20           |
| Standards                                    | CE / EAC / CB  |
| Photobiological safety group acc. to EN62778 | RG1            |

1) Energy efficiency class (EEC) on a scale of A (highest efficiency) to G (lowest efficiency)

**Country-specific categorizations**

|                 |                 |
|-----------------|-----------------|
| Order reference | LEDPMR113536 4, |
|-----------------|-----------------|

**Energy labelling regulation data acc EU 2019/2015**

|   |              |
|---|--------------|
| Lighting technology used                            | LED          |
| Non-directional or directional                      | DLS          |
| Mains or non-mains                                  | NMLS         |
| Light source cap-type (or other electric interface) | GU4          |
| Connected light source (CLS)                        | No           |
| Color-tuneable light source                         | No           |
| Envelope  | No           |
| High luminance light source                         | No           |
| Anti-glare shield                                   | No           |
| Correlated colour temperature type                  | SINGLE_VALUE |
| Claim of equivalent power                           | Yes          |
| Length  | 38.00 mm     |
| Height  | 35.00 mm     |
| Width   | 35.00 mm     |
| Chromaticity coordinate x                           | 0.382        |
| Chromaticity coordinate y                           | 0.380        |

|  |                |
|--|----------------|
| R9 Colour rendering index                            | 1              |
| Beam angle correspondence                            | NARROW_CONE_90 |
| Survival factor                                      | 0.90           |
| LED light source replaces a fluorescent light source | Yes            |
| EPREL ID   | 522966         |
| Model number   | AC32698        |

**DOWNLOAD DATA**

**Documents and certificates**



Declarations Of Conformity CE

**Photometric and lighting design files**



Spectral power distribution

**LOGISTICAL DATA**

| Product code  | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume               |
|---------------|------------------------------|--------------------------------------|--------------|----------------------|
| 4058075636606 | Folding box<br>1             | 36 mm x 36 mm x 46 mm                | 27.00 g      | 0.06 dm <sup>3</sup> |
| 4058075636613 | Shipping box<br>10           | 188 mm x 78 mm x 69 mm               | 303.00 g     | 1.01 dm <sup>3</sup> |
| 4058075637528 | Shipping box<br>80           | 201 mm x 169 mm x 240 mm             | 2567.00 g    | 8.15 dm <sup>3</sup> |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

**References / Links**

- For further products and actual information concerning LED lamps see [www.ledvance.com/ledlamps](http://www.ledvance.com/ledlamps)
- For Guarantee see [www.ledvance.com/guarantee](http://www.ledvance.com/guarantee)
- Further information see [www.ledvance.com/low-voltage-ledlamps](http://www.ledvance.com/low-voltage-ledlamps)

**DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.