



Features

- - Quick-start without increasing the starting current, - Immediate switch off in case of flickering or defective lamp (end of life), - Prevents overheating of the ballast,
- Extended life compared to standard starters, - Reduced maintenance cost due to longer lifetime, - For single lamps operation

Product Overview

Product name	Starter COP-11A
Technology	Accessory
General application	Office, Hospitality, Retail, Logistics & Industry, Education, Residential & Consumer, Museums & Galleries
ETIM Class	EC000260
E-number FI	4045121
E-number SE	7902068
Wattage (W)	36.58
Non-reclosure Voltage	N/s
Nominal Line Voltage Single Operation	220-240V
Nominal Line Voltage Tandem Operation	N/s
Product EAN number	5410288244716

Data table

GENERAL DATA

Product name	Starter COP-11A
Technology	Accessory

Starter COP-11A 0024471

General application	Office, Hospitality, Retail, Logistics & Industry, Education, Residential & Consumer, Museums & Galleries
ETIM Class	EC000260
E-number FI	4045121
E-number SE	7902068

OPTICAL DATA

Adjustable chromaticity	N
--------------------------------	---

ELECTRICAL DATA

Wattage (W)	36.58
Mains voltage (V)	220-240V
Control gear required	No
Transformer required	Yes
Non-reclosure Voltage	N/s
Nominal Line Voltage Single Operation	220-240V
Nominal Line Voltage Tandem Operation	N/s

PHYSICAL DATA

Nominal Product Height (mm)	36
Max. Lamp Diameter (mm) - D	21.5
Weight (kg)	0.007

PACKAGING

Single packaging type	Without Packaging
Product EAN number	5410288244716
Packaging single length / height (cm)	2.15
Packaging single width (cm)	2.15
Packaging single depth (cm)	4.03
Units per inner package	25
Packaging inner length / height (cm)	12.0
Packaging inner width (cm)	11.7

Starter COP-11A 0024471

Packaging inner depth (cm)	4.6
Units per outer package	200
Packaging outer length / height (cm)	24.4
Packaging outer width (cm)	23.8
Packaging outer depth (cm)	9.9

SAFETY DATA

Special purpose lamp	No
Dry applications use only	No
Suitable for household illumination	No