

# PRODUCT DATASHEET LED TUBE T8 EM STARTER

LED TUBE T8 EM STARTER | Starter for LED TUBE EM (CCG)



### Areas of application


- Not suitable for operation with electronic control gears

### **Product features**

- LED tube starter for the replacement of a fluorescent lamp with a T8 EM LED tube
- Suitable for operation with low loss or conventional control gear or line voltage

## **TECHNICAL DATA**

# **Dimensions & Weight**



Diameter	21 mm
Product weight	5.00 g

# Country-specific categorizations

# Energy labelling regulation data acc EU 2019/2015

Length	40 mm
Height	21 mm
Width	21 mm

## **DOWNLOAD DATA**

	Documents and certificates
POF	Installation guide
POF	Declarations Of Conformity CE
POF	Declarations Of Conformity UKCA

# LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075013674	Folding box 2	46 mm x 25 mm x 42 mm	9.00 g	0.05 dm <sup>3</sup>
4058075013681	Shipping box 20	99 mm x 32 mm x 218 mm	169.00 g	0.69 dm³
4058075013698	Shipping box 840	446 mm x 309 mm x 246 mm	7.42 g	33.90 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## References / Links

- For current information see www.ledvance.com/osram-led-tube

## **DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.