DATA SHEET



PROTECTOR K 9 V

Item number

GTIN

ER10018909

4015120018909















Product description

- Photoelectric smoke detector for battery operation with in-built relay driver for the PROTECTOR K switching relay
- Safety through automatic self-test with fault display
- Extra safety through genuine electronic smoke chamber testing at the push of a button



Technical data

| r | FN | IFI | 7 4 1 |
|-----|----|-----|-------|
| la. | ΕŊ | | ₹AI |

| Device category | Smoke alarm | |
|-------------------------------|---|--|
| Remote controllable | - | |
| Conformity | CE, EAC, RoHS, WEEE | |
| Electronic smoke chamber test | at the push of a button | |
| Automatic testing | approx. every 45 seconds with fault display | |
| Model name | K12 | |
| Tested in accordance with | EN 14604:2005 + AC:2008 | |
| CPD number | 0786-CPD-20470 | |
| Networkability | up to 30 detectors by wire | |
| Signal volume | approx. 85 dB/3 m | |
| Warranty | 3 years | |
| | | |
| ATTACHMENT | | |
| Installation type | Surface mounted (plaster) | |
| | | |

| Installation position | Ceiling | |
|---------------------------------|------------------------------|--|
| Connectable wire cross section | 0.75 — 2.5 mm² | |
| HOUSING | | |
| Dimensions | Height/Depth 48 mm, Ø 106 mm | |
| Weight | 127 g | |
| Protection type | IP20 | |
| Permissible ambient temperature | 0 °C+55 °C | |
| Relative humidity | 5 – 93 %, non-condensing | |
| Colour | white, similar to RAL 9010 | |
| ELECTRICAL VERSION | | |
| Control system | ON/OFF | |
| Protection class | III | |
| Nominal voltage | 9 V DC | |

Accessories

| Product designation | Item number | Product description | GTIN |
|-----------------------------------|-------------|---|---------------|
| Electrical accessories | | | |
| PROTECTOR K RELAY | ER10018923 | Switching relay for PROTECTOR K series for triggering external devices such as sounders, flash lights and alarm horns | 4015120018923 |
| Mounting | | | |
| PROTECTOR K MOUNTING BOX 20 SM WH | ER10018992 | Surface-mounted box for PROTECTOR K series, 20 mm | 4015120018992 |
| PROTECTOR K MOUNTING BOX 27 SM WH | ER10018985 | Surface-mounted box for PROTECTOR K series, 27 mm | 4015120018985 |

DATA SHEET



PROTECTOR K 9 V


Item number GTIN


ER10018909 4015120018909

Accessories

| Product designation | Item number | Product description | GTIN |
|--------------------------|-------------|--|---------------|
| Protection | | | |
| BASKET GUARD ROUND LARGE | EM10425608 | Basket guard for presence and motion detectors and smoke detectors, Ø 180 mm, height 90 mm | 4015120425608 |
| BASKET GUARD ROUND SMALL | EM10425615 | Basket guard for presence and motion detectors and smoke detectors, Ø 165 mm, height 70 mm | 4015120425615 |

Dimension drawing Circuit diagram





9-V battery operation. Optional networking with max. 30 detectors (max. line length 300 m) and PROTECTOR K relay.

Detailed product description

- Photoelectric smoke detector for battery operation with in-built relay driver for the PROTECTOR K switching relay
- Safety through automatic self-test with fault display
- $\bullet\;$ Extra safety through genuine electronic smoke chamber testing at the push of a button
- Protection against false alarm thanks to antistatic smoke chamber