DATA SHEET



PROTECTOR K 9 V Lithium

Item number

GTIN

ER10018930

4015120018930















Product description

- Photoelectric smoke detector for battery operation with in-built relay driver for the PROTECTOR K switching relay
- Safety through automatic self-test with fault display
- Extra safety through genuine electronic smoke chamber testing at the push of a button



Technical data

Smoke alarm	
-	
CE, EAC, RoHS, WEEE	
at the push of a button	
approx. every 45 seconds with fault display	
K13	
EN 14604:2005 + AC:2008	
0786-CPD-20470	
up to 30 detectors by wire	
approx. 85 dB/3 m	
3 years	
Surface mounted (plaster)	

Installation position	Ceiling		
Connectable wire cross section	0.75 — 2.5 mm ²		
HOUSING			
Dimensions	Height/Depth 48 mm, Ø 106 mm		
Weight	138 g		
Protection type	IP20		
Permissible ambient temperature	0 °C+55 °C		
Relative humidity	5 – 93 %, non-condensing		
Colour	white, similar to RAL 9010		
ELECTRICAL VERSION			
Control system	ON/OFF		
Protection class	III		
Nominal voltage	9 V DC		

Accessories

Product designation	Item number	Product description	GTIN
Electrical accessories			
PROTECTOR K RELAY	ER10018923	Switching relay for PROTECTOR K series for triggering external devices such as sounders, flash lights and alarm horns	4015120018923
Mounting			
PROTECTOR K MOUNTING BOX 20 SM WH	ER10018992	Surface-mounted box for PROTECTOR K series, 20 mm	4015120018992
PROTECTOR K MOUNTING BOX 27 SM WH	ER10018985	Surface-mounted box for PROTECTOR K series, 27 mm	4015120018985

DATA SHEET



PROTECTOR K 9 V Lithium


Item number GTIN


ER10018930 4015120018930

Accessories

Product designation	Item number	Product description	GTIN
Protection			
BASKET GUARD ROUND LARGE	EM10425608	Basket guard for presence and motion detectors and smoke detectors, Ø 180 mm, height 90 mm	4015120425608
BASKET GUARD ROUND SMALL	EM10425615	Basket guard for presence and motion detectors and smoke detectors, Ø 165 mm, height 70 mm	4015120425615

Dimension drawing Circuit diagram





9-V battery operation. Optional networking with max. 30 detectors (max. line length 300 m) and PROTECTOR K relay.

Detailed product description

- Photoelectric smoke detector for battery operation with in-built relay driver for the PROTECTOR K switching relay
- Safety through automatic self-test with fault display
- $\bullet\;$ Extra safety through genuine electronic smoke chamber testing at the push of a button
- Protection against false alarm thanks to antistatic smoke chamber