

6.6.05 – Update with applications

Dual-duct units, electrical re-heater and radiator heating

A4 Application library CR24 V1.1 EN

Single room applications

CR



Key to IRC application numbering



Layout

System	-	Application	-	Number	->					
I	R	C	-	V	A	V	-		IRC	VAV application
I	R	C	-	V	A	V	-	0	0	1 1 . 0
I	R	C	-	V	A	V	-	0	0	1 1 . 1

- **IRC system** VAV **variant 0011.0**

- **sub-variant 0001.1**

Key

System	-	Application	-	Number	-> System	Application				
I	R	C	-	A	I	R	-		IRC	Air (damper)
I	R	C	-	V	A	V	-		IRC	VAV
I	R	C	-	W	A	T	-		IRC	Water
I	R	C	-	C	L	C	-		IRC	Chilled/heated ceiling
I	R	C	-	V	A	R	-		IRC	Various

Overview IRC applications

The application library consists of various singles room applications based on the proofed Belimo actuators for motorized air and water applications and the new CR24 single room controller range. The applications are subdivided according to its system type.

The library is being update regularly, please check for the lasted issue: on the INTRANET or under www.belimo.ch

The detailed function description and technical data of the CR24 controller can be found in the CR24 Product-Information: www.belimo.ch

Air-Systems, pressure dependent

Application	Description	CR24 Type
IRC-AIR-0011.0	Single-duct – Damper control, Room temperature controlled – cooling mode	CR24-B1
IRC-AIR-0015.0	Single-duct – Damper control, with Change/over function	CR24-B1

VAV-Systems, pressure independent

Application	Description	CR24 Type
IRC-VAV-0011.0	VAV - Single-duct application, Room temperature controlled	CR24-B1
IRC-VAV-0011.1	VAV - Single-duct application, with Boost option: Temperature controlled	CR24-B3
IRC-VAV-0013.0	VAV – Dual duct application, with room temperature controller	new CR24-B1
IRC-VAV-0015.0	VAV - Single-duct application, Room temperature controlled with 0...10V reheat valve	CR24-B3
IRC-VAV-0015.1	VAV - Single-duct application, Room temperature controlled with 3-Point reheat valve	CR24-B2
IRC-VAV-0016.0	VAV - Single-duct application, Room temperature controlled with 1-stage electrical reheat	new CR24-B2E
IRC-VAV-0016.1	VAV - Single-duct application, Room temperature controlled with 2-stage electrical reheat	new CR24-B2E
IRC-VAV-0018.0	VAV - Single-duct application, Room temperature controlled with ON/OFF radiator valve	new CR24-B2E
IRC-VAV-0111.0	VAV - Single-duct application, with chilled ceiling	CR24-B3

Water applications

Application	Description	CR24 Type
IRC-WAT-0011.0	2-pipe system with 3-point reheat valve, Room temperature controlled	CR24-B2
IRC-WAT-0015.0	2-pipe system Heat exchanger, with Change/Over function	CR24-B1

Heat-/Chilled Ceiling-Systems

Application	Description	CR24 Type
IRC-CLC-0011.0	Chilled ceiling - 2-pipe-system, Room temperature controlled	CR24-B3
IRC-CLC-0015.0	Heat-/Chilled ceiling - 2-pipe-system, with Change-over function	CR24-B3

Air-Systems, pressure dependent


<i>Application</i>	<i>Description</i>	<i>CR24 Type</i>
IRC-AIR-0011.0	Single-duct – Damper control, Room temperature controlled – cooling mode	CR24-B1
IRC-AIR-0015.0	Single-duct – Damper control, with Change/over function	CR24-B1

IRC-AIR-0011.0

**Single-duct Damper control,
Room temperature controlled – cooling mode**



Wiring diagram CR24-B1



Mode setting actuator: 2...10V

In- & Output assignment

Inputs

- ai/di1 EHO / ext. Sensor *
- di2 Stand by *
- ai2 Remote setpoint shift *

Outputs

- ao1 System output (0)2...10V

* Optional

Note

The pin numbering corresponds to the Belimo actuator connections.

Refer to the CR24 Product-Information for technical data and detailed information.

Configuration, settings CR24-B1

DIP-Switch setting:


- 1 P-Band: normal - breit
- 2 di2: Stand by - Change over



Setpoint W_H range:


15...36 °C

Description, functional diagram



Pressure depending damper application. The room temperature aims as the demand related control value of the connected damper actuators.

Functional diagram



Hints

Mode setting damper: 2...10 V

Options

- ◆ di1 – EHO Energy hold off, e.g. window switch, ext. time switch
- ◆ di2 – Stand by, e.g. motion detector
- ◆ ai1 – external temperature sensing – exhaust duct
- ◆ ai2 – external setpoint shift, e.g. So/Wi-compensation

Operations - MMI

CR24-A1 without user interface
CR24-B1 with user interface

Mode: *AUTO*
Mode: *AUTO-ECO-MAX*



Air-System, pressure depending

IRC-AIR-0015.0

**Single duct – Damper control,
with Change/Over function**



Wiring diagram CR24-B1



In- & Output assignment

Inputs

- ai/di1 EHO / ext. Sensor *
- di2 Change/Over
- ai2 Remote setpoint shift *

Outputs

- ao1 Change/over actuator 2...10V

* Optional

Note

The pin numbering corresponds to the Belimo actuator connections.

Refer to the CR24 Product-Information for technical data and detailed information.

Configuration, setting CR24-B1

DIP-Switch setting:


- 1 P-Band: normal - wide
2 di2: Stand by - Change over



Setpoint WH range:


15...36 °C

Description, functional diagram



Pressure depending single-duct damper application with Change/Over-function heating - cooling. Change/over Heating \leftrightarrow cooling switching action via dry contact depending e.g. via the temperature of the supply system.

Functional diagram



Hint

Mode setting actuator: 2...10 V

Options

- ◆ di1 – EHO Energy hold off, e.g. window switch, ext. timeswitch
- ◆ ai1 – external temperature sensing – exhaust duct
- ◆ ai2 – external setpoint shift, e.g. So/Wi-compensation

Bedienung

CR24-A1 without user interface
CR24-B1 with user interface

Mode: AUTO
Mode: AUTO-ECO-MAX

VAV-Systems, pressure independent


<i>Application</i>	<i>Description</i>	<i>CR24</i>	<i>Type</i>
IRC-VAV-0011.0	VAV - Single-duct application, Room temperature controlled		CR24-B1
IRC-VAV-0011.1	VAV - Single-duct application, with Boost option: Temperature controlled		CR24-B3
IRC-VAV-0013.0	VAV – Dual duct application, with room temperature controller	new	CR24-B1
IRC-VAV-0015.0	VAV - Single-duct application, Room temperature controlled with 0...10V reheat valve		CR24-B3
IRC-VAV-0015.1	VAV - Single-duct application, Room temperature controlled with 3-Point reheat valve		CR24-B2
IRC-VAV-0016.0	VAV - Single-duct application, Room temperature controlled with 1-stage electrical reheat	new	CR24-B2E
IRC-VAV-0016.1	VAV - Single-duct application, Room temperature controlled with 2-stage electrical reheat	new	CR24-B2E
IRC-VAV-0018.0	VAV - Single-duct application, Room temperature controlled with ON/OFF radiator valve	new	CR24-B2E
IRC-VAV-0111.0	VAV - Single-duct application, with chilled ceiling		CR24-B3

IRC-VAV-0011.0


**VAV – Single duct application
Room temperature controlled**



Wiring diagram CR24-B1




Description, functional diagram



The room temperature aims as the demand related control value of the connected VAV units. The variable volumetric flow range $V_{\min} \dots V_{\max}$ equals to:

- V_{\min} - to the hygienic air change
- V_{\max} - to the maximum cooling demand.

Functional diagram



In- & Output assignment

Inputs

- ai/di1 EHO / ext. Sensor *
- di2 Stand by *
- ai2 Remote setpoint shift *

Outputs

- ao1 VAV system output (0)2...10V

* Optional

Note

The pin numbering corresponds to the Belimo actuator connections.

Refer to the CR24 Product-Information for technical data and detailed information.

Configuration, settings CR24-B1

DIP-Switch setting:

- 1 P-Band: normal - wide
- 2 di2: Stand by - Change over



Setpoint W_H range:

15...36 $^{\circ}\text{C}$

Hints

Application requires VAV - controller mode setting: 2...10 V

Options


- ◆ di1 – EHO Energy hold off, e.g. window switch, ext. timeswitch
- ◆ di2 – Stand by, e.g. motion detector
- ◆ ai1 – external temperature sensing – exhaust duct
- ◆ ai2 – external setpoint shift, e.g. So/Wi-compensation

Operations - MMI

CR24-A1 without user interface Mode: AUTO
CR24-B1 with user interface Mode: AUTO-ECO-MAX



Wiring diagram CR24-B3



Mode setting VAV-controller: 2...10V

In- & Output assignment

Inputs

- ai/di1 EHO / ext. Sensor *
- di2 Stand by *
- di3 Boost**
- ai2 Remote setpoint shift *

Outputs

- ao1 VAV system output (0)2...10V**

* Optional

Note


The pin numbering corresponds to the Belimo actuator connections.

Refer to the CR24 Product-Information for technical data and detailed information.

Configuration, settings CR24-B3

DIP-Switch setting:


- | | |
|-------------------------|----------------|
| 1 P-Band: normal | - wide |
| 2 V'max Hz: Off | - 80% |
| 3 ao2: heating | - cooling/C-O |
| 4 di3: Boost | - Dewpoint/C-O |
| 5 Boost: Temp. | - V'max |
| 6 controller: P1 | - P |



Setpoint W_H range:

15...36 °C

Description, functional diagram




The room temperature aims as the demand related control value of the connected VAV units. The variable volumetric flow range V'min...V'max equals to: hygienic air change ... maximum cooling demand.

Room preconditioning can be triggered via Boost input di3, e.g. via external timer, building management system.

Function ,Boost Temperature controlled'

- ON: di3 active -> VAV output ao1 10 V (V'max)
- OFF: di3 inactive or comfort setpoint reached -> Auto operation

Functional diagram



Hints

Application requires VAV - controller mode setting: 2...10 V

Options

- ◆ di1 – EHO Energy hold off, e.g. window switch, ext. timeswitch
- ◆ di2 – Stand by, e.g. motion detector
- ◆ ai1 – external temperature sensing – exhaust duct
- ◆ ai2 – external setpoint shift, e.g. So/Wi-compensation

Operations - MMI

CR24-A3 without user interface

Mode: AUTO

CR24-B3 with user interface

Mode: AUTO-ECO-MAX


VAV-System, pressure independent

IRC-VAV-0013.0

**VAV – Dual duct application
with room temperature controller**



Wiring diagram CR24-B1



Mode setting VAV-controller: 2...10V

In- & Output assignment

Inputs

- ai/di1 ext. Sensor * / Shut-off cold air duct *
- di2 St-By Stand by *
- ai2 Remote setpoint shift *

Outputs

- ao1 VAV system output (0)2...10V

* Optional

Note

The pin numbering corresponds to the Belimo actuator connections

Refer to the CR24 Product-Information for technical data and detailed information.

Configuration, settings CR24-B1


DIP-Switch setting:

- 1 P-Band: normal - wide
- 2 di2: Stand by - Change over

Setpoint W_H range:

15...36 °C

Description, functional diagram




The cold and the hot air supplied by the dual duct system get mixed by the two volume controller according to the required room demand.

The hot air constant volume (CAV) controller is supporting the required hot air for the heating condition. At cooling demand the cold air (VAV) controller adds the cold air part as required by the CR24 room temperature controller. In case the cold air parts exceeds the hot air part, the hot air damper gets closed and the cold air supply is in work only.

Option:

The cold air duct can be shut-off by the use of a switch contact connected to input di1.

Functional diagram



Hints

Application requires VAV - controller mode setting: 2...10 V

Options

- ◆ di1 – Shut off cold air duct, e.g. ext. time switch
- ◆ di2 – Stand by, e.g. motion detector
- ◆ ai1 – external temperature sensing – exhaust duct
- ◆ ai2 – external setpoint shift, e.g. So/Wi-compensation

Operations - MMI


CR24-A1 without user interface	Mode: AUTO
CR24-B1 with user interface	Mode: AUTO-ECO-MAX

IRC-VAV-0015.0

**VAV – single duct application
with 0...10V reheat valve**



Wiring diagram CR24-B3



Hint: Mode setting VAV controller: 2...10V

In- & Output assignment

Inputs

- ai/di1 EHO / ext. Sensor *
- di2 Stand by *
- di3 Boost *
- ai2 Remote setpoint shift *

Outputs

- ao1 VAV system output (0)2...10V
- ao3 Heating output 3-point

* Optional

Note


The pin numbering corresponds to the Belimo actuator connections.

Refer to the CR24 Product-Information for technical data and detailed information.

Configuration, settings CR24-B3

DIP-Switch setting:


- | | |
|-------------------------|----------------|
| 1 P-Band: normal | - wide |
| 2 V'max Hz: Off | - 80% |
| 3 ao2: heating | - cooling/C-O |
| 4 di3: Boost | - Dewpoint/C-O |
| 5 Boost: Temp. | - V'max |
| 6 controller: P1 | - P |



Setpoint W_H range:

15...36 °C

Description, functional diagram



The room temperature aims as the demand related control value of the connected VAV units. The variable volumetric air flow range V'min...V'max equals to:
 - V'min - to the hygienic air change
 - V'max - to the maximum cooling demand.


The reheat gets controlled via the connected 0...10 V valve at heating request. To ensure the required airflow over the reheat the volumetric air flow gets controlled V'min.... 80% V'max during that condition.

Option:

Digital input di3 driven by a Boost signal allows the preconditioning of the room. Two Boost modes can be used:

- Boost – *'Temperature controlled'*: quick-heating and/or, -cooling
- Boost – V'max: room flush, support smoke extraction

Functional diagram



Hints

- Application requires VAV - controller mode setting: 2...10 V
- Heating output ao2: 0...10 V

Options

- ◆ di1 – EHO Energy hold off, e.g. window switch, ext. time switch
- ◆ di2 – Stand by, e.g. motion detector
- ◆ di3 – Boost, e.g. BMS, ext. time switch
- ◆ ai1 – external temperature sensing – exhaust duct
- ◆ ai2 – external setpoint shift, e.g. So/Wi-compensation

Operations - MMI


CR24-A3 without user interface Mode: *AUTO*
 CR24-B3 with user interface Mode: *AUTO-ECO-MAX*

IRC-VAV-0015.1

**VAV - single duct application
with 3-point reheater valve**



Wiring diagram CR24-B2



Hint: Mode setting VAV-controller: 2...10V

In- & Output assignment

Inputs

- ai/di1 EHO / ext. Sensor *
- di2 Stand by *
- di3 Air flush *
- ai2 Remote setpoint shift *

Outputs

- ao1 VAV system output (0)2...10V
- ao3 Heating output 3-point

* Optional

Note

The pin numbering corresponds to the Belimo actuator connections.

Refer to the CR24 Product-Information for technical data and detailed information.

Configuration, settings CR24-B2

DIP-Switch setting:


- 1 P-Band: normal - wide
- 2 V'max htg Off - 80%



Setpoint W_H range:

15...36 °C

Description, functional diagram




The room temperature aims as the demand related control value of the connected VAV units. The variable volumetric air flow range $V'\min \dots V'\max$ equals to:
 - $V'\min$ - to the hygienic air change
 - $V'\max$ - to the maximum cooling demand.

A reheater gets activated via the connected 3-point valve at heating request. To ensure the required airflow over the reheater the volumetric air flow gets controlled $V'\min \dots 80\% V'\max$ during that condition.

Option:

The VAV-application can be forced to the ' $V'\max$ ' step by the use of the digital input $di3$. Typical use air flush via an independent air quality control loop, support of smoke extraction, etc. The heating output does not get influenced during that condition.

Functional diagram



Hints

- Application requires VAV - controller mode setting: 2...10 V
- Heating output $ao3$: 3-point actuator, optimized for 150 s running time

Options

- ◆ di1 – EHO Energy hold off, e.g. window switch, ext. time switch
- ◆ di2 – Stand by, e.g. motion detector
- ◆ di3 – Air flush, e.g. air quality control, ext. time switch
- ◆ ai1 – external temperature sensing – exhaust duct
- ◆ ai2 – external setpoint shift, e.g. So/Wi-compensation

Operations - MMI

- | | |
|--------------------------------|--------------------|
| CR24-A2 without user interface | Mode: AUTO |
| CR24-B2 with user interface | Mode: AUTO-ECO-MAX |

VAV-System, pressure independent


BELIMO®

IRC-VAV-0016.0

VAV – single duct application
with 1-stage electrical reheater



Wiring diagram CR24-B2E



In- & Output assignment

Inputs

- ai/di1 supply air limitation * / EHO *
- di2 Stand by *
- di3 Boost *
- ai2 Remote setpoint shift *

Outputs

- ao1 VAV system output (0)2...10V
- do3/1 Heating output 24 VAC ON/OFF

* Optional

Note

The pin numbering corresponds to the Belimo actuator connections.

Refer to the CR24 Product Information and the data sheet CR24-B2E for technical data and detailed information..

Configuration, settings CR24-B2E

DIP-Switch setting:


1 Steps: 1 or 2 - binary
2 V'max Htg: Off - 80%



Setpoint W_H range:

15...36 °C

Description, functional diagram



The room temperature aims as the demand related control value of the connected VAV units. The variable volumetric air flow range V'min...V'max:


- V'min - to the hygienic air change
- V'max - to the maximum cooling demand.

At heating conditions the reheater gets controlled via the ON/OFF Triac-output. The volumetric flow gets increased 35 ... 80% V'max to ensure the thermal transfer.

Options:

By the use of an external sensor mounted in the supply duct the air injection temperature can be limited to a maximum of about 50°C.

Functional diagram



Hints

- Application requires VAV - controller mode setting: 2...10 V

Options

- ◆ di1 – EHO Energy hold off, e.g. window switch, ext. time switch
- ◆ di2 – Stand by, e.g. motion detector
- ◆ di3 – Boost, e.g. BMS, ext. time switch
- ◆ ai1 – Supply air limitation, NTC5k sensor
- ◆ ai2 – external setpoint shift, e.g. So/Wi-compensation

Operations - MMI

CR24-A2E without user interface Mode: AUTO
CR24-B2E with user interface Mode: AUTO-ECO-MAX

VAV-System, pressure independent


BELIMO®

IRC-VAV-0016.1

**VAV – single duct application
with 2-stage electrical reheater**



Wiring diagram CR24-B2E



In- & Output assignment

Inputs

- ai/di1 supply air limitation * / EHO *
- di2 Stand by *
- di3 Boost *
- ai2 Remote setpoint shift *

Outputs

- ao1 VAV system output (0)2...10V
- do3/1 Heating output I 24 VAC ON/OFF
- do3/2 Heating output II 24 VAC ON/OFF

* Optional

Note

The pin numbering corresponds to the Belimo actuator connections.

Refer to the CR24 Product-Information and the data sheet CR24-B2E for technical data and detailed information..

Configuration, settings CR24-B2E

DIP-Switch setting:


1 Steps: 1 or 2 - binary
2 V'max Hgt: Off - 80%



Setpoint W_H range:

15...36 °C

Description, functional diagram



The room temperature aims as the demand related control value of the connected VAV units. The variable volumetric air flow range V'min...V'max:


- V'min - to the hygienic air change
- V'max - to the maximum cooling demand.

At heating conditions the 2-step re-heater gets controlled via the two ON/OFF Triac-outputs in a binary mode which gives an almost modulating control mode. The volumetric flow gets increased 35 ... 80% V'max to ensure the thermal transfer.

Options:

By the use of an external sensor mounted in the supply duct the air injection temperature can be limited to a maximum of about 50°C.

Functional diagram



Hints

- Application requires VAV - controller mode setting: 2...10 V

Options

- ◆ di1 – EHO Energy hold off, e.g. window switch, ext. time switch
- ◆ di2 – Stand by, e.g. motion detector
- ◆ di3 – Boost, e.g. BMS, ext. time switch
- ◆ ai1 – Supply air limitation, NTC5k sensor
- ◆ ai2 – external setpoint shift, e.g. So/Wi-compensation

Operations - MMI

CR24-A2E without user interface Mode: AUTO
CR24-B2E with user interface Mode: AUTO-ECO-MAX

VAV-System, pressure independent


BELIMO®

IRC-VAV-0018.0

VAV- single duct application
with radiator heating ON/OFF



Wiring diagram CR24-B2E



In- & Output assignment

Inputs

- di1 EHO *
- di2 Stand by *
- di3 Boost *
- ai2 Remote setpoint shift *

Outputs

- ao1 VAV system output (0)2...10V
- do3/1 Heating output 24 VAC ON/OFF

* Optional

Note

The pin numbering corresponds to the Belimo actuator connections.

Refer to the CR24 Product-Information and the data sheet CR24-B2E for technical data and detailed information.

Configuration, settings CR24-B2E

DIP-Switch setting:


1 Steps: 1 or 2 - binary
2 V'max Htg: Off - 80%



Setpoint W_H range:

15...36 °C

Description, functional diagram




The room temperature aims as the demand related control value of the connected VAV units. The variable volumetric air flow range V'min...V'max:

- V'min - to the hygienic air change
- V'max - to the maximum cooling demand.

At heating conditions the ON/OFF radiator valve gets controlled via the CR24 Triac-output.

Functional diagram



Hints

- Application requires VAV - controller mode setting: 2...10 V

Options

- ◆ di1 – EHO Energy hold off, e.g. window switch, ext. time switch
- ◆ di2 – Stand by, e.g. motion detector
- ◆ di3 – Boost, e.g. BMS, ext. time switch
- ◆ ai2 – external setpoint shift, e.g. So/Wi-compensation

Operations - MMI


CR24-A2E without user interface Mode: AUTO
CR24-B2E with user interface Mode: AUTO-ECO-MAX

IRC-VAV-0111.1

**VAV - single duct application
with Chilled ceiling**



Wiring diagram CR24-B3



In- & Output assignment

Inputs

- ai/di1 EHO / ext. Sensor *
- di2 Stand by *
- di3 Dew point control
- ai2 Remote setpoint shift *

Outputs

- ao1 VAV system output (0)2...10V
- ao3 Cooling output 0....10V

* Optional

Note

The pin numbering corresponds to the Belimo actuator connections.

Refer to the CR24 Product-Information for technical data and detailed information.

Configuration, settings CR24-B3


DIP-Switch setting:

1	P-Band: <u>normal</u>	- wide
2	V'max Hz:	<u>Off</u> - 80%
3	ao2:	heating - <u>cooling/C-O</u>
4	di3:	Boost - <u>Dewpoint/C-O</u>
5	Boost:	<u>Temp.</u> - V'max
6	controller:	<u>PI</u> - P

Setpoint WH range:

15...36 °C

Description, functional diagram



The room temperature aims as the demand related control value of the connected VAV units and chilled ceiling. The variable volumetric air flow range $V_{min} \dots V_{max}$ equals to: hygienic air change ... maximum cooling demand.


Option – unit sequencing:

The two cooling units can also be used in control sequencing:

Unit 1 - Chilled ceiling: 0 ... 5 V (MFT-actuator)

Unit 2 - VAV: 5 ...10 V (MFT-controller. E.g. NMV-D2M)

Functional diagram



Hints

- Application requires VAV - controller mode setting: 2...10 V
- Cooling output 0 ... 10 V

By the use of the control sequencing option the control input of the MFT-actuators need to be adjusted (PC-Tool or MFT-Handy)

Options

- ♦ di1 – EHO Energy hold off, e.g. window switch, ext. time switch
- ♦ di2 – Stand by, e.g. motion detector
- ♦ ai1 – external temperature sensing – exhaust duct
- ♦ ai2 – external setpoint shift, e.g. So/Wi-compensation

Operations - MMI

CR24-A3 without user interface Mode: AUTO


CR24-B3 with user interface Mode: AUTO-ECO-MAX

Water applications


<i>Application</i>	<i>Description</i>	<i>CR24 Type</i>
IRC-WAT-0011.0	2-pipe system with 3-point reheat valve, Room temperature controlled	CR24-B2
IRC-WAT-0015.0	2-pipe system Heat exchanger, with Change/Over function	CR24-B1



Wiring diagram CR24-B2



Description, functional diagram



Energy demand controlled reheater application, based on the room temperature.


In- & Output assignment

- Inputs**
- ai/di1 EHO / ext. Sensor *
 - di2 St-By Standby *
 - ai2 Remote setpoint shift *

- Outputs**
- ao1 Heating valve 3-point

* Optional

Functional diagram



Note

The pin numbering corresponds to the Belimo actuator connections.

Refer to the CR24 Product-Information for technical data and detailed information.

Configuration, settings CR24-B2

DIP-Switch setting:

- 1 P-Band: normal - wide
2 V'max htg Off - 80%



Options

- ◆ di1 – EHO Energy hold off, e.g. window switch, ext. timeswitch
- ◆ ai1 – external temperature sensing – exhaust duct
- ◆ ai2 – external setpoint shift, e.g. So/Wi-compensation

Setpoint W_{htg} range:

15...36 °C


Operations - MMI

CR24-A2 without user interface
CR24-B2 with user interface


Mode: AUTO
Mode: AUTO-ECO-MAX



Wiring diagram CR24-B1



Description, functional diagram



2-pipe demand controlled application supporting Change/over operation. Heating \leftrightarrow cooling switching action via a dry contact depending e.g. on the flow temperature of the supply system.

In- & Output assignment

Inputs


- ai/di1 EHO / ext. Sensor *
- di2 Change/over signal
- ai2 Remote setpoint shift *

Outputs

- ao1 Change/over actuator 2...10V

* Optional

Functional diagram



Note

The pin numbering corresponds to the Belimo actuator connections.

Hint

Actuator setting: 2...10 V

Refer to the CR24 Product-Information for technical data and detailed information.

Configuration, settings CR24-B1

DIP-Switch setting:

- | | |
|-------------------------|--------------------|
| 1 P-Band: <u>normal</u> | - wide |
| 2 di2: Stand by - | <u>Change over</u> |



Options

- ◆ di1 – EHO Energy hold off, e.g. window switch, ext. timeswitch
- ◆ ai1 – external temperature sensing – exhaust duct
- ◆ ai2 – external setpoint shift, e.g. So/Wi-compensation

Setpoint WH range:

15...36 °C

Operations - MMI

CR24-A1 without user interface

Mode: AUTO

CR24-B1 with user interface

Mode: AUTO-ECO-MAX

Heat-/Chilled Ceiling-Systems



<i>Application</i>	<i>Description</i>	<i>CR24 Type</i>
IRC-CLC-0011.0	Chilled ceiling - 2-pipe-system, Room temperature controlled	CR24-B3
IRC-CLC-0015.0	Heat-/Chilled ceiling - 2-pipe-system, with Change-over function	CR24-B3

IRC-CLC-0011.0

**Chilled ceiling - 2-pipe-system
Room temperature controlled**



Wiring diagram CR24-B3



In- & Output assignment

Inputs

- ai/di1 EHO / ext. Sensor *
- di2 Stand by *
- di3 Dew point limiter
- ai2 Remote setpoint shift *

Outputs

- ao2 Cooling output 0...10V

* Optional

Note


The pin numbering corresponds to the Belimo actuator connections.

Refer to the CR24 Product-Information for technical data and detailed information.

Configuration, settings CR24-B3

DIP-Switch setting:


- 1 P-Band: normal - wide
- 2 V'max Hz: Off - 80%
- 3 ao2: heating - cooling/C-O
- 4 di3: Boost - Dewpoint/C-O
- 5 Boost: Temp - V'max
- 6 controller: Pi - P



Setpoint W_H range:


15...36 °C

Description, functional diagram



The Chilled ceiling application existing of a room temperature controller and a 0...10 V cooling valve. The dew point limiter cares for perspiration water free operation as it switches off the cooling by a 2-point signal.

Functional diagram



Hint

- Cooling output $ao2$: 0...10 V

Options

- ♦ di1 – EHO Energy hold off, e.g. window switch, ext. time switch
- ♦ di2 – Stand by, e.g. motion detector
- ♦ ai1 – external temperature sensing – exhaust duct
- ♦ ai2 – external setpoint shift, e.g. So/Wi-compensation

Operations - MMI


- | | |
|--------------------------------|--------------------|
| CR24-A3 without user interface | Mode: AUTO |
| CR24-B3 with user interface | Mode: AUTO-ECO-MAX |

IRC-CLC-0015.0


**Chilled ceiling - 2-pipe-system
with Change/over function**



Wiring diagram CR24-B3



Function input di3:



In- & Output assignment

Inputs

- ai/di1 EHO / ext. Sensor *
- di2 Stand by *
- di3 Dew point limiter / Change/over**
- ai2 Remote setpoint shift *

Outputs

- ao2 Cooling/Heating 0...10V**

* Optional

Note


The pin numbering corresponds to the Belimo actuator connections.

Refer to the CR24 Product-Information for technical data and detailed information.

Configuration, settings CR24-B3

DIP-Switch setting:


- 1 P-Band: normal - wide
- 2 V'max Hz: Off - 80%
- 3 ao2: **heating** - cooling/C-O
- 4 di3: **Boost** - Dewpoint/C-O
- 5 Boost: Temp - V'max
- 6 controller: Pi - P



Setpoint W_H range:


15...36 °C

Description, functional diagram



This water ceiling system can be used to cover heating and cooling demand due to the build-in Change/over function of the room temperature controller controlling the common 0...10 V valve. Change/over gets activated by an external command wired to digital input di3. The dew point limiter cares for perspiration water free operation as it switches off the cooling via a 2-point signal.

Functional diagram



Hint


- Cooling output ao2: 0...10 V

Options

- ◆ di1 – EHO Energy hold off, e.g. window switch, ext. timeswitch
- ◆ di2 – Stand by, e.g. motion detector
- ◆ ai1 – external temperature sensing – exhaust duct
- ◆ ai2 – external setpoint shift, e.g. So/Wi-compensation

Operations - MMI

- | | |
|--------------------------------|--------------------|
| CR24-A3 without user interface | Mode: AUTO |
| CR24-B3 with user interface | Mode: AUTO-ECO-MAX |



All-inclusive.



5

5 year
warranty



On site around
the globe



A complete
range of products
from one source



Tested quality



Short delivery
times



Comprehensive
support

Headquarters

BELIMO Holding AG
Brunnenbachstrasse 1
CH-8340 Hinwil
Tel. +41 (0)43 843 62 11
Fax +41 (0)43 843 62 68
info@belimo.ch
www.belimo.ch

Subsidiaries, Representatives and Agencies

Argentina	Denmark	Lebanon	Rumania
Australia	Egypt	Liechtenstein	Russia
Bahrain	Estonia	Lithuania	Saudi Arabia
Belgium	Finland	Luxembourg	Singapore
Bosnia-Herzegovina	France	Malaysia	Slovakia
Brazil	Great Britain	Mexico	Slovenia
Bulgaria	Germany	Morocco	South Africa
Canada	Greece	Netherlands	Spain
Chile	Hong Kong	New Zealand	Sweden
Croatia	Hungary	Norway	Switzerland
Cyprus	Iceland	Oman	Taiwan
Czech Republic	India	Pakistan	Turkey
	Indonesia	People's Republic	Ukraine
	Ireland	of China	United Arab
	Israel	Philippines	Emirates
	Italy	Poland	United States
	Japan	Portugal	of America
	Jordan	Qatar	
	Kuwait	Republic of Korea	
	Latvia	(South Korea)	

Romania
Russia
Saudi Arabia
Singapore
Slovakia
Slovenia
South Africa
Spain
Sweden
Switzerland
Taiwan
Turkey
Ukraine
United Arab
Emirates
United States
of America