

# CL42-F - series

Compressor couplings with female thread (similar to DIN 3489), 42 mm



Reference	Material	Seal	Thread	DN (mm)	PN (bar)	Weight (g)
CL42-15-F-IN-038	Cast iron	NBR	Rp 3/8 inch	15	10	150
CL42-19-F-IN-012	Cast iron	NBR	Rp 1/2 inch	19	10	155
CL42-20-F-IN-034	Cast iron	NBR	Rp 3/4 inch	20	10	155
CL42-20-F-IN-100	Cast iron	NBR	Rp 1 inch	20	10	185
CL42-17-F-IB-012	Cast iron	Brass	Rp 1/2 inch	17	10	220
CL42-17-F-IB-034	Cast iron	Brass	Rp 3/4 inch	17	10	190
CL42-17-F-IB-100	Cast iron	Brass	Rp 1 inch	17	10	250
CL42-15-F-SF-038	Stainless steel	FPM/FKM	Rp 3/8 inch	15	16	170
CL42-19-F-SF-012	Stainless steel	FPM/FKM	Rp 1/2 inch	19	16	155
CL42-20-F-SF-034	Stainless steel	FPM/FKM	Rp 3/4 inch	20	16	155
CL42-20-F-SF-100	Stainless steel	FPM/FKM	Rp 1 inch	20	16	175

**ENGLISH**

Temperature range:  
-40°C bis +95°C

**NEDERLANDS**

Materialen  
Temperatuurbereik:  
-40°C bis +95°C

**DEUTSCH**

Temperaturbereich:  
-40°C bis +95°C

**FRANÇAIS**

Plage de température:  
-40°C bis +95°C