

# CL42-H - series

Compressor couplings with hose pillar connection (similar to DIN 3489), 42 mm



Reference	Material	Hose inside (mm)	DN (mm)	PN (bar)	Weight (g)
CL42-6-H-IN-10	Cast iron	10	6.5	10	160
CL42-8-H-IN-012	Cast iron	13 (1/2 inch)	8.5	10	155
CL42-8-H-IB-012	Cast iron	13 (1/2 inch)	8.5	10	250
CL42-14-H-IN-034	Cast iron	19 (3/4 inch)	14	10	175
CL42-15-H-IB-034	Cast iron	19 (3/4 inch)	15	10	200
CL42-19-H-IN-100	Cast iron	25 (1 inch)	19	10	180
CL42-19-H-IB-100	Cast iron	25 (1 inch)	19	10	250
CL42-20-H-IN-114	Cast iron	32 (1 1/4 inch)	20	10	240
CL42-6-H-SF-10	Stainless steel	10	6.5	16	125
CL42-9-H-SF-012	Stainless steel	13 (1/2 inch)	9	16	85
CL42-15-H-SF-034	Stainless steel	19 (3/4 inch)	15	16	190
CL42-20-H-SF-100	Stainless steel	25 (1 inch)	20	16	240

**ENGLISH**

Temperature range:  
-40°C bis +95°C

**NEDERLANDS**

Temperatuurbereik:  
-40°C bis +95°C

**DEUTSCH**

Temperaturbereich:  
-40°C bis +95°C

**FRANÇAIS**

Plage de température:  
-40°C bis +95°C