

# CL42-M - series

Compressor couplings with male thread (similar to DIN 3489), 42 mm



Reference	Material	Seal	Thread	DN (mm)	PN (bar)	Weight (g)
CL42-11-M-IB-012	Cast iron	Brass	G 1/2 inch	11	10	185
CL42-17-M-IB-034	Cast iron	Brass	G 3/4 inch	17	10	195
CL42-17-M-IB-100	Cast iron	Brass	G 1 inch	17	10	200
CL42-8-M-IN-038	Cast iron	NBR	G 3/8 inch	8.5	10	170
CL42-12-M-IN-012	Cast iron	NBR	G 1/2 inch	12	10	175
CL42-17-M-IN-034	Cast iron	NBR	G 3/4 inch	17	10	185
CL42-20-M-IN-100	Cast iron	NBR	G 1 inch	20	10	210
CL42-10-M-SF-038	Stainless steel	FPM/FKM	G 3/8 inch	10	16	120
CL42-14-M-SF-012	Stainless steel	FPM/FKM	G 1/2 inch	14	16	150
CL42-19-M-SF-034	Stainless steel	FPM/FKM	G 3/4 inch	19	16	160
CL42-20-M-SF-100	Stainless steel	FPM/FKM	G 1 inch	20	16	220

**ENGLISH**

Temperature range:  
-40°C bis +95°C

**NEDERLANDS**

Materialen  
Temperatuurbereik:  
-40°C bis +95°C

**DEUTSCH**

Temperaturbereich:  
-40°C bis +95°C

**FRANÇAIS**

Plage de température:  
-40°C bis +95°C