

CLP7-NX - series

Coupling plug with union nut for PVC hose, DN 7.2



Reference	Material	Hose inside x outside (mm)	Double sided shut-off *	PN (bar)	Weight (g)
CLP7-NX-B-4	Brass	4x10	N		31
CLP7-NX-B-6	Brass	6x12	N		36
CLP7-NX-B-8	Brass	8x14	N		55
CLP7-NX-B-9	Brass	9x15	N		60
CLP7-NX-B-10	Brass	10x16	N		65

* Note: Coupling plugs with valve for double-sided shut off (-SV) can only be used with the special coupling sockets (-SV) provided for them.

ENGLISH

Materials:

Housing: Brass, union nut:
Aluminium

Temperature range:

-10°C bis +60°C

Advantages:

•Frequent assembly and disassembly possible, •No hose clip - no risk of injury

NEDERLANDS

Materialen

Behuizing: Messing, wartelmoer:
Aluminium

Temperatuurbereik:

-10°C bis +60°C

Voordelen:

•Veelvuldige montage en demontage mogelijk, •Geen slangkleem - geen letselgevaar.

DEUTSCH

Werkstoffe:

Gehäuse: Messing, Überwurfmutter:
Aluminium

Temperaturbereich:

-10°C bis +60°C

Vorteile:

•häufige Montage und Demontage möglich, •keine Schlauchschelle - keine Verletzungsgefahr

FRANÇAIS

Matériaux:

boîtier: laiton, écrou-raccord:
aluminium

Plage de température:

-10°C bis +60°C

Avantages:

•Permet un montage et un démontage fréquents •Pas de collier à tuyau, donc pas de risque de blessures