

FL2E-MM-O - series

Angle-ORFS-screwed connections (G-thread)



Reference	Material	Surface protection	Nominal outer diameter of connection 1	Nominal outer diameter of connection 2 (inch)	Max pressure (bar)
FL2E-M-EZE-009U-018G-O	Steel	Zinc plated	UNF 9/16inch-18	G 1/8	400
FL2E-M-EZE-009U-014G-O	Steel	Zinc plated	UNF 9/16inch-18	G 1/4	400
FL2E-M-EZE-009U-038G-O	Steel	Zinc plated	UNF 9/16inch-18	G 3/8	400
FL2E-M-EZE-011U-014G-O	Steel	Zinc plated	UN 11/16inch-16	G 1/4	400
FL2E-M-EZE-011U-038G-O	Steel	Zinc plated	UN 11/16inch-16	G 3/8	400
FL2E-M-EZE-011U-012G-O	Steel	Zinc plated	UN 11/16inch-16	G 1/2	400
FL2E-M-EZE-013U-014G-O	Steel	Zinc plated	UN 13/16inch-16	G 1/4	400
FL2E-M-EZE-013U-038G-O	Steel	Zinc plated	UN 13/16inch-16	G 3/8	400
FL2E-M-EZE-013U-012G-O	Steel	Zinc plated	UN 13/16inch-16	G 1/2	400
FL2E-M-EZE-013U-034G-O	Steel	Zinc plated	UN 13/16inch-16	G 3/4	400
FL2E-M-EZE-100U-038G-O	Steel	Zinc plated	UNS 1inch-14	G 3/8	400
FL2E-M-EZE-100U-012G-O	Steel	Zinc plated	UNS 1inch-14	G 1/2	400
FL2E-M-EZE-100U-034G-O	Steel	Zinc plated	UNS 1inch-14	G 3/4	400
FL2E-M-EZE-100U-100G-O	Steel	Zinc plated	UNS 1inch-14	G 1	315
FL2E-M-EZE-103U-012G-O	Steel	Zinc plated	UN 1-3/16inch-12	G 1/2	400
FL2E-M-EZE-103U-034G-O	Steel	Zinc plated	UN 1-3/16inch-12	G 3/4	400
FL2E-M-EZE-103U-100G-O	Steel	Zinc plated	UN 1-3/16inch-12	G 1	315
FL2E-M-EZE-107U-034G-O	Steel	Zinc plated	UN 1-7/16inch-12	G 3/4	315
FL2E-M-EZE-107U-100G-O	Steel	Zinc plated	UN 1-7/16inch-12	G 1	315
FL2E-M-EZE-107U-114G-O	Steel	Zinc plated	UN 1-7/16inch-12	G 1 1/4	250
FL2E-M-EZE-111U-100G-O	Steel	Zinc plated	UN 1-11/16inch-12	G 1	250
FL2E-M-EZE-111U-114G-O	Steel	Zinc plated	UN 1-11/16inch-12	G 1 1/4	250
FL2E-M-EZE-111U-112G-O	Steel	Zinc plated	UN 1-11/16inch-12	G 1 1/2	200
FL2E-M-EZE-200U-112G-O	Steel	Zinc plated	UN 2inch-12	G 1 1/2	200