

FL3T-M - series

T-pieces with male thread



T-pieces (male / male / male), PN 16

Reference	Material	Surface protection	Nominal outer diameter connection 1, 2 and 3 (inch)	Max pressure (bar)
FL3T-M-BN-018R	Brass	Nickel-plated	R 1/8	16
FL3T-M-BN-014R	Brass	Nickel-plated	R 1/4	16
FL3T-M-BN-038R	Brass	Nickel-plated	R 3/8	16
FL3T-M-BN-012R	Brass	Nickel-plated	R 1/2	16
FL3T-M-BN-034R	Brass	Nickel-plated	R 3/4	16
FL3T-M-BN-100R	Brass	Nickel-plated	R 1	16
FL3T-M-B-018R	Brass		R 1/8	16
FL3T-M-B-014R	Brass		R 1/4	16
FL3T-M-B-038R	Brass		R 3/8	16
FL3T-M-B-012R	Brass		R 1/2	16
FL3T-M-B-034R	Brass		R 3/4	16
FL3T-M-B-100R	Brass		R 1	16



T-pieces (outside / outside / outside) with NPT-thread, up to 345 bar

Reference	Material	Surface protection	Nominal outer diameter connection 1, 2 and 3 (inch)	Max pressure (bar)
FL3T-M-EZ-018N	Steel	Zinc plated	1/8 NPT	345
FL3T-M-EZ-014N	Steel	Zinc plated	1/4 NPT	275
FL3T-M-EZ-038N	Steel	Zinc plated	3/8 NPT	210
FL3T-M-EZ-012N	Steel	Zinc plated	1/2 NPT	210
FL3T-M-EZ-034N	Steel	Zinc plated	3/4 NPT	170
FL3T-M-EZ-100N	Steel	Zinc plated	1 NPT	140