

# FL3Y-F - series

Air junction 2-fold, up to 25 bar



Reference	Material	Surface protection	Nominal outer diameter connection 1, 2 and 3	Max pressure (bar)
FL3Y-F-BN-018G	Brass	Nickel-plated	G 1/8	16
FL3Y-F-BN-014G	Brass	Nickel-plated	G 1/4	16
FL3Y-F-BN-038G	Brass	Nickel-plated	G 3/8	16
FL3Y-F-BN-012G	Brass	Nickel-plated	G 1/2	16
FL3Y-F-B-038R	Brass	Nickel-plated	Rp 3/8	16
FL3Y-F-B-012R	Brass	Nickel-plated	Rp 1/2	16
FL3Y-F-SH-014R	Stainless steel		Rp 1/4	16
FL3Y-F-SH-038R	Stainless steel		Rp 3/8	16
FL3Y-F-SH-012R	Stainless steel		Rp 1/2	16
FL3Y-F-SH-034R	Stainless steel		Rp 3/4	16
FL3Y-F-SH-100R	Stainless steel		Rp 1	16
FL3Y-F-SH-114R	Stainless steel		Rp 1 1/4	16
FL3Y-F-SH-112R	Stainless steel		Rp 1 1/2	16
FL3Y-F-SH-200R	Stainless steel		Rp 2	16
FL3Y-F-SH-212R	Stainless steel		Rp 2 1/2	16
FL3Y-F-SH-300R	Stainless steel		Rp 3	16
FL3Y-F-IZ-038R	Cast iron	Zinc plated	Rp 3/8	25
FL3Y-F-IZ-012R	Cast iron	Zinc plated	Rp 1/2	25
FL3Y-F-IZ-034R	Cast iron	Zinc plated	Rp 3/4	25
FL3Y-F-IZ-100R	Cast iron	Zinc plated	Rp 1	25