


ML-R series

Pressure Gauges Reducer (accessories)



Reference	Body material	Length (L)	Max pressure	Reference	Body material	Length (L)	Max pressure	Outer Thread	Inner Thread
ML-R-B1814	Brass	29	250	ML-R-S1814	Stainless steel	25	400	G 1/8"	G 1/4"
ML-R-B1418	Brass	28	250	ML-R-S1418	Stainless steel	27	400	G 1/4"	G 1/8"
ML-R-B1438	Brass	37	250	ML-R-S1438	Stainless steel	37	400	G 1/4"	G 3/8"
ML-R-B1412	Brass	41	250	ML-R-S1412	Stainless steel	41	400	G 1/4"	G 1/2"
ML-R-B3814	Brass	33	250	ML-R-S3814	Stainless steel	35	400	G 3/8"	G 1/4"
ML-R-B3812	Brass	45	250	ML-R-S3812	Stainless steel	45	400	G 3/8"	G 1/2"
ML-R-B1218	Brass	35	250	ML-R-S1218	Stainless steel	32	400	G 1/2"	G 1/8"
ML-R-B1214	Brass	38	250	ML-R-S1214	Stainless steel	38	400	G 1/2"	G 1/4"
ML-R-B1238	Brass	45	250	ML-R-S1238	Stainless steel	45	400	G 1/2"	G 3/8"
ML-R-B1234	Brass	45	250	ML-R-S1234	Stainless steel	45	400	G 1/2"	G 3/4"
ML-R-B3412	Brass	45	250	ML-R-S3412	Stainless steel	45	400	G 3/4"	G 1/2"
ML-R-BM121514	Brass	32	250	ML-R-SM121514	Stainless steel	28	400	M 12 X 1,5	G 1/4"
ML-R-B14M1215	Brass	32	250	ML-R-S14M1215	Stainless steel	28	400	G 1/4"	M 12 X 1,5
ML-R-BM121512	Brass	41	250	ML-R-SM121512	Stainless steel	39	400	M 12 X 1,5	G 1/2"
ML-R-B12M1215	Brass	37	250	ML-R-S12M1215	Stainless steel	37	400	G 1/2"	M 12 X 1,5
ML-R-BM201512	Brass	46	250	ML-R-SM201512	Stainless steel	46	400	M 20 X 1,5	G 1/2"
ML-R-B12M2015	Brass	46	250	ML-R-S12M2015	Stainless steel	46	400	G 1/2"	M 20 X 1,5
ML-R-B14NPT14	Brass	30	250	ML-R-S14NPT12	Stainless steel	43	400	NPT 1/4"	G 1/4"
ML-R-B12NPT12	Brass	44	250	ML-R-S12NPT12	Stainless steel	44	400	NPT 1/4"	G 1/2"
ML-R-B1214-19mm	Brass	19	400	ML-R-S1214-19mm	Stainless steel	19	400	NPT 1/2"	G 1/2"
ML-R-B1418-15mm	Brass	15	400					G 1/2"	G 1/4"
								G 1/4"	G 1/8"